

Leaking Petroleum Storage Tanks MPCA, MAR DIVISION PLR/SS Section Political Political

http://www.pca.state.mn.us/programs/lust_p.html

Investigation Report Form

Fact Sheet #3.24

Complete this form to document remedial investigation (RI) activities, including Limited Site Investigations (LSIs) and full RIs. Do not revise or delete any text or questions from this report form. Include any additional information that is important for making a site cleanup decision. If only a LSI is necessary, you may skip Section 6 and Section 7 of this report form.

Refer to Minnesota Pollution Control Agency (MPCA) fact sheet 3.1 Leaking Underground Storage Tank Program for the overall RI objectives, and to other MPCA fact sheets for details on investigation methods. When a tank has been excavated, refer to fact sheets 3.6 Excavation of Petroleum Contaminated Soil During Tank Removal and 3.7 Excavation Report Worksheet for Petroleum Release Sites for reporting requirements. Document the occurrence of free product using fact sheet 3.3 Free Product: Evaluation and Recover, and fact sheet 3.4 Free Product Recovery Report Worksheet.

MPCA Site ID: Leak: 00014698

Date: August 19, 2003

Responsible Party: North American State Bank

R.P. phone #: (320) 254-8271

Consultant: Coteau Environmental Consultant phone #: (320) 846-4668

Facility Name: Former K-C Kwik Stop

Facility Address: 230 1st Street

City: Brooten, Minnesota

County: Stearns

Zip Code: 56316

Site location: The required coordinate scheme for reporting site location is Universal Transverse Mercator (UTM), Extended Zone 15, 1983 North American Datum (NAD83). Refer to http://www.ot.state.mn.us/ot files/handbook/standard/std17-1.html for Minnesota spatial data standards, or http://mac.usgs.gov/mac/isb/pubs/factsheets/fs15799.html for more information about UTM Coordinates.

X coordinate (Easting) 15 333791E meters Y coordinate (Northing) 5040564N meters Page 2 Investigation Report Form February 2001

What feature does the coordinate represent? (i.e. center of parcel, approximate center of source area, etc. Please describe)

The coordinates represent the approximate center of the source area.

What method was used to determine the coordinate? (i.e. GPS receiver, map interpolation, address matching, etc. Please describe)

The coordinates were determined from a digital topographic map at the website www.topozone.com.

If a paper map, digital map, aerial photo or digital orthophotoquad was used to find the site location, please provide the scale of the map or photo (i.e. 1:24,000, etc.)

The scale of the digital map is 1:25,000.

Section 1: Emergency and High Priority Sites

1. Is an existing drinking water well impacted or likely to be impacted within a two-year travel time?	No
2. Are there existing vapor impacts?	No
3. Is there an existing surface water impact as indicated by 1) a product sheen on the surface water or 2) a product sheen or volatile organic compounds in the part per million (ppm) range in ground water in a well located close to the surface water.	No
4. Has the release occurred in the last 30 days?	No
5. Has free product been detected at the site? If YES, attach fact sheet 3.4 Free Product Recovery Report Worksheet.	No
6. Is sand or gravel aquifer impacted which is tapped by water wells within or potentially within 500 feet from the release source or does impacted soil overlie a geologically sensitive area? If YES, explain:	Yes

If you answered YES to any of questions 1 through 6 above describe below the actions taken to date to reduce or eliminate the risk posed by the release.

Five (5) monitor wells were installed at the site on August 7, 2002. Ground water monitoring was conducted at the site. An additional monitor well was completed at the site on February 4, 2003. A vapor survey was conducted in the vicinity of the site on August 8, 2002. Residential basements and utility manholes were screened for organic vapors during the survey. No elevated organic vapor concentrations were identified during the vapor survey.

Section 2: Site and Release Information

2.1 Attach Table 1 - Tank Information. Describe the status of the other components of the tank system(s), (i.e., piping and dispensers).

The pump dispensers formerly located at the site were removed on April 17, 2002. The pump dispensers were removed prior to Coteau personnel arriving at the site. Reportedly, the pump dispensers were in good condition at the time of removal.

- 2.2a Describe the land use and pertinent geographic features within 1,000 feet of the site.

 Residential and commercial properties are located within 1,000 feet of the site.
- 2.2b List other potential leak sources within 500 feet of the site.

None

- 2.3 Identify and describe the source or suspected source(s) of the release.

 The suspected source(s) of the release is/are the gasoline UST (s) formerly located at the site.
- 2.4 What was the volume of the release? (if known): Unknown gallons
- 2.5 When did the release occur? (if known):Unknown

Page 5 Investigation Report Form February 2001

Section 3: Excavated Soil Information

3.1 Include the Fact Sheet 3.7 Excar	vation Report Worksheet in Appendix A
3.2 Was soil excavated for off-site t	reatment? No
Date excavated: N/A	
Volume removed: cubic y	yards
3.3 Indicate soil treatment type:	☐ land treatment ☐ thermal treatment ☐ composting/biopiling ☐ other () Name and location of treatment facility:
	N/A

Section 4: Extent and Magnitude of Soil Contamination

	Were soil borings conducted in or immediately adjacent to all likely sources including:	YES
	dispensers,	yes
	underground storage tank basins,	yes
	above ground storage tank areas,	not present
	piping,	yes
	remote fill pipes,	not present
	and known spill areas	not present
4.2	To adequately define the vertical extent of contamination, soil borings should be completed at least five feet below the water table or ten feet below the deepest measurable (field screening and visual observation) contamination, whichever is deeper. Were all soil borings completed to the required depth?	NO
4.3	To adequately evaluate site stratigraphy complete at least one boring to 20 feet below the water table, or to 20 feet below the deepest <u>site</u> contamination, whichever is deeper. If a confining layer is present, drill the boring in an uncontaminated area. Was this done?	NO

If you answered NO to any of the three previous questions, explain why the borings were not conducted in the required locations or to the required depths (see fact sheet #3.19, Soil and Ground Water Investigations Performed During Remedial Investigations regarding exceptions and MPCA approval for depth of drilling):

Soil borings were not completed at the locations of the former pump dispensers because soil samples were collected from beneath the locations of the former dispensers during UST system excavation activities at the site on April 17, 2002. Based on field screening and laboratory analysis, no petroleum impacts were identified at the former locations of the pump dispensers.

Soil boring B-1 was completed to a depth of 20 feet below the water table, but could not be completed to a depth of 20 feet below the deepest measurable contamination due to refusal. In addition, borings B-5, B-6, B-7 and B-8 could not be completed to a depth of five (5) feet below the deepest measurable contamination because of refusal.

4.4 Indicate the drilling method:	X hollow-stem auger
_	sonic drilling
	X push probes
	\Box other .

Note: MPCA staff hydrologist approval is required before use of flight augers
4.5 Discuss soil borings drilled and provide rationale for their locations. Attach boring logs in Appendix D.

Soil borings completed at the site were located to determine the horizontal extent of soil impacts. Placement of the borings was conducted in accordance with MPCA guidelines.

- 4.6 Attach Table 2 Results of Soil Headspace Screening, In Appendix C, discuss soil headspace screening method and describe any deviation from recommended and/or required methods and procedures.
- 4.7 Attach Table 3 Analytical Results of Soil Samples. Provide analytical results in Appendix B. In Appendix C, discuss soil sampling and analytical methods used and describe any deviation from recommended and/or required methods and procedures
- **4.8** Describe the vertical and horizontal extent and magnitude of soil contamination. Provide a plan-view map and two cross-sections that illustrate both soil head space and laboratory analytical results. See Section 13.

The approximate horizontal extent of soil impacts is shown on Figures 4 and 5. The maximum benzene and MTBE concentrations (29.000 and 150.000 ppm, respectively) were identified in the soil sample collected from boring B-4 (9-11 feet bg). The maximum TPH as GRO concentration (9,100 ppm) was identified in the soil sample collected from boring B-3 (9-12 feet bg). Geologic cross-sections of the soil borings are shown on Figures 11 and 12.

4.9 Attach Table 4 - Other Contaminants Detected in Soils (Petroleum or Non-petroleum Derived). Discuss the possible sources of these compounds.

Methyl tertiary butyl ether (MTBE) was identified by laboratory analysis in soil samples collected from borings B-1 (9-12 feet bg), B-3 (9-12 feet bg), B-4 (9-11 feet bg) and B-5 (17-19 feet bg) at concentrations of 94.000, 67.000, 150.000 and 0,300 parts per million (ppm), respectively. The likely source(s) of this compound is gasoline released from UST's formerly located at the site.

4.10 Is contaminated soil in contact with ground water?

Yes

If YES or if ground water contamination appears likely, then complete Section 5.

If NO (contaminated soil is not in contact with ground water), what is the distance separating the deepest contamination from the surface of the water table? Was this distance measured during site activities, referenced from geologic information, or estimated based on feet

Page 8 Investigation Report Form February 2001

professional opinion during a site visit?

4.10Describe observations of any evidence of a fluctuating water table and a seasonal high water table (e.g., mottling). Also, from other sources of information describe the range of natural water table fluctuations in the area.

No mottling was observed during soil boring activities on June 13, August 6 and 7, 2002 and February 4, 2003. Based on information from water well logs obtained from the Minnesota Geological Survey (MGS), static water levels in four (4) water wells located approximately 300 feet to one (1) mile from the former KC Kwik Stop site ranged from five (5) to 22 feet bg at the time of construction. Ground water levels measured in the monitor wells completed at the site averaged 9.04, 9.48, 8.90 and 10.00 feet bg during monitoring events conducted on August 12 and November 6, 2002 and February 27 and May 1, 2003, respectively. Based on this information, the water table in the vicinity of the site appears to be near a seasonal high level.

4.12 In your judgment, is there a sufficient distance separating the petroleum contaminated soil (or an impacted non- aquifer) from the underlying aquifer to prevent petroleum contamination of the aquifer? Please explain in detail. In your explanation, consider the data and information of this section as well as the nature of the petroleum release (i.e., volume, when it occurred, petroleum product).

No

If YES, a ground water contamination assessment is not necessary as part of the LSI.

If NO, a ground water contamination assessment is necessary. Complete Section 5.

Significant soil impacts were identified by laboratory analysis in borings B-1 (9-12 feet),

B-3 (9-12 and 15-18 feet) and B-4 (9-11 feet). As previously mentioned, the average depth to water was measured at 9.04, 9.48, 8.90 and 10.00 feet bg on August 12 and November 6, 2002 and February 27 and May 1, 2003, respectively. Therefore, soil impacts are below the water table at the site. In addition, based on water supply well logs obtained from the MGS, it appears that nearby water wells utilize the impacted aquifer. Ground water impacts were identified in monitor wells MW-4 and MW-5 during the August 12, 2002 monitoring event and in monitor wells MW-3, MW-4 and MW-5 during the November 6, 2002 and February 27 and May 1, 2003 monitoring events.

Section 5: Aquifer Characteristics/Ground Water Contamination Assessment

Complete Section 5 if groundwater has been contaminated or may become contaminated. Aquifer determination is made during the LSI. It is based upon the stratigraphy and a hydraulic conductivity measurement calculated from grain size distribution analysis. The site stratigraphy gives the context within which the hydraulic conductivity measurement can be interpreted. Please refer to Fact Sheet 3.19, Soil and Ground Water Investigations Performed During Remedial Investigations for methods and requirements.

5.1 Provide an average hydraulic conductivity value (K) measured:

$$K = 638.74 \text{ ft/day}$$

Indicate the method of measurement (i.e., Hazen, Masch and Denny, Kozeny-Carmen, etc.): Hydraulic conductivity measured by Hazen, Masch and Denny approximation. Grain-size distribution approximations by sieve analysis method(s).

Indicate the locations and depths of soil samples submitted for grain size analyses. Provide the results of grain size analyses and other information used for the determination of K-values in Appendix F.

Soil samples were collected for grain size analyses from soil borings B-1 (16-18 feet bg), B-2 (15-17 feet bg) and B-3 (21-23 feet bg).

5.2 Calculate a range for aquifer transmissivity (T) using the equation T = Kb, where b is the thickness of the aquifer:

$$T_{High} = 26,387 \text{ ft}^2/\text{day}$$
 b = 19 feet
 $T_{Low} = 4,527 \text{ ft}^2/\text{day}$

Determine the aquifer thickness (b) from geologic logs of soil borings, water well logs, and available published information. Attach water well logs in Appendix D. If the transmissivity of a contaminated hydrogeologic unit is greater than 50 ft²/day, it is considered an aquifer (for the purpose of the LUST program), and monitoring wells will be necessary.

Page 10 Investigation Report Form February 2001

5.3 Discuss in detail the site geology and stratigraphy, including a discussion of local and regional hydrogeology, using soil boring data and cross sections, geologic logs of near-by water wells, and available published information.

Based on water supply well logs for water wells located within one (1) mile of the site, obtained from the Minnesota Geological Survey (MGS), sand and gravel are present from approximately one (1) to three (3) feet bg to a depth ranging from 25 to 45 feet bg. Below these depths, interbedded layers of clay and sand are present to a depth of approximately 140 feet bg.

Soil sediments encountered during soil boring activities consisted of approximately two (2) to four (4) feet of fill and/or topsoil, underlain by approximately two (2) to three (3) feet of alluvium, underlain by fine to coarse sand and fine gravel outwash to a depth of approximately 28 feet bg. Clay till was encountered in boring B-1 at a depth of approximately 28 feet bg.

5.4 Attach Table 5- Water Level Measurements and Depths of Water Samples Collected from Borings. Indicate the method used to measure the water levels in borings, and the depth water samples were collected from borings. Allow water levels in borings to equilibrate to static conditions, and the adjust the effective screened intervals in borings to intercept the static water table prior to water sample collection. Discuss groundwater flow direction.

Water levels in the soil borings were allowed to equilibrate to static conditions prior to measurement. Based on the results of ground water monitoring conducted on August 12 and November 6, 2002, the ground water flow direction was to the east-northeast. Based on ground water monitoring conducted at the site on February 27 and May 1, 2003, ground water flow was to the east-southeast in the vicinity of the site. Additional ground water monitoring will be required to determine the predominant flow direction at the site.

5.5 Attach Table 6 - Analytical Results of Water Samples Collected from Borings. Summarize the analytical results of groundwater samples collected as part of an LSI. Discuss the extent and magnitude of groundwater contamination. Also provide a discussion on QA/QC, including information on the samples collected and laboratory analyses performed.

Ground water samples were collected from borings B-1, B-2, B-3 and B-4 on June 13, 2002. Ground water was not encountered in boring B-5 during drilling on August 6, 2002 and therefore, a water sample was not collected from boring B-5. Benzene, toluene and ethyl benzene were identified in the ground water sample collected from boring B-1 at concentrations of 1,254.0, 4,798.0 and 763.0 parts per billion (ppb), respectively. Benzene, toluene and ethyl benzene were also identified in the ground water sample collected from boring B-3 at concentrations of 101.0, 4,696.0 and 1,259.0 ppb, respectively. In addition, benzene, toluene, ethyl benzene and xylenes (BTEX) were identified in ground water collected from boring B-4 at concentrations of 209.0, 9,054.0, 2,686.0 and 16, 028.0 ppb, respectively. These concentrations are above the Health Risk Limits (HRL's) for these constituents. TPH as GRO was also identified by laboratory analysis in ground water

Page 11 Investigation Report Form February 2001

collected from borings B-1, B-2, B-3 and B-4 at concentrations of 44,993.0, 4,211.0, 350,157.0 and 338,583.0 ppb, respectively. The horizontal extent of ground water impacts is illustrated on Figures 6A, 6B, 7A and 7B. Ground water samples collected from the soil borings were laboratory analyzed for volatile organic compounds (VOC's) and TPH as GRO.

5.6 Attach Table 7 - Other Contaminants Detected in Water Samples Collected from Borings (Petroleum or Non-petroleum Derived). Discuss the possible sources of these contaminants and provide a discussion of QA/QC information.

Laboratory analysis identified naphthalene, above the HRL of 300 ppb, in ground water collected from borings B-1, B-3 and B-4. 1,2,4-Trimethylbenzene was identified in ground water collected from borings B-1, B-2, B-3 and B-4 at concentrations of 725.0, 336.0, 2,338.0 and 6,246.0 ppb, respectively. Laboratory analysis identified 1,3,5-Trimethylbenzene in ground water from borings B-2, B-3 and B-4 at concentrations of 100.0, 1,008.0 and 1,960.0 ppb, respectively. Isopropylbenzene was identified in ground water collected from borings B-2, B-3 and B-4 at concentrations of 7.0, 144.0 and 227.0 ppb, respectively. In addition, n-Propylbenzene was identified in ground water from borings B-2, B-3 and B-4 at concentrations of 11.0, 488.0 and 915.0 ppb, respectively. The likely source of these compounds is the former gasoline stored in the UST's at the site.

5.7 Laboratory certification number: Northeast Technical Services (027-137-157)

Summit Environmental Technologies (039-999-385)

Additional Ground Water Investigation

Complete Section 6 only if: 1) an aquifer has been impacted at or above Minnesota Department of Health HRLs, 2) an aquifer has been impacted below the HRLs, but the levels are likely to reach the HRLs, or 3) there is an insufficient distance separating the petroleum contaminated soil (or an impacted non- aquifer) from the underlying aquifer. Complete Section 7 only if remediation is anticipated. Regardless of whether you are submitting a LSI or a full RI, all sections following Section 7 must be completed.

Section 6. Extent and Magnitude of Ground Water Contamination

6.1 Discuss drilling and installation of wells, including the rationale for their locations. Attach boring logs in Appendix D.

Monitor wells MW-1, MW-2, MW-3, MW-4 and MW-5 were installed on August 7, 2002. Monitor well MW-6 was completed on February 4, 2003. The monitor wells were completed to a depth of 19 feet bg, utilizing 15-foot PVC screens. Monitor wells MW-1, MW-5 and MW-6 were completed as flush-grade wells, while MW-2, MW-3 and MW-4 were completed as above-grade wells.

- **6.2** Attach Table 8 Monitoring Well Completion Information.
- 6.3 Attach Table 9 Summary of Water Levels Measured in Wells.
- 6.4 Attach Table 10 Analytical Results of Water Samples Collected from Wells. Indicate here whether samples were purged or unpurged (see fact sheet 3.23). If purged, indicate purging method.

Ground water samples collected from the monitor wells were purged by collecting five (5) well volumes using a dedicated polyethylene bailer, then allowing the water table to stabilize before samples were collected (Appendix C).

6.5 Attach Table 11 - Other Contaminants Detected in Water Samples Collected from Wells (Petroleum or Non-Petroleum Derived). Indicate here whether samples were purged or unpurged (see fact sheet 3.23). If purged, indicate purging method.

Ground water samples collected from the monitor wells were purged by collecting five (5) well volumes using a dedicated polyethylene bailer, then allowing the water table to stabilize before samples were collected (Appendix C).

Page 13 Investigation Report Form February 2001

6.6 Describe the extent and magnitude of the ground water contamination. Discuss the presence of non-petroleum compounds, if detected, and identify possible sources of these compounds. Also provide a discussion on QA/QC, including information on the samples collected and laboratory analyses performed.

Monitor well locations are shown on Figure 2. Ground water sampling of the monitor wells was conducted on August 12 and November 6, 2002. During the August 12, 2002 monitoring event, benzene and toluene were identified in ground water collected from monitor well MW-5 at concentrations of 503.0 and 1,187.0 ppb, respectively. These concentrations are above the HRL's for these constituents. In addition, TPH as GRO was identified in ground water from MW-5 at a concentration of 13,919.0 ppb on August 12, 2002. Acetone was also identified in ground water from MW-5 at a concentration of 910.0 ppb during the August 12, 2002 monitoring event. The possible source of acetone identified in ground water collected from MW-1 may have been a spill of paint or antifreeze at the site in the past. It is also possible that propane, a naturally-occurring organic chemical found in soil, may have been converted to acetone by hydrolysis of the beta carbon of straight-chain alkanes by the enzyme monooxygenase during the beta-oxidation metabolic pathway.

During the November 6, 2002 monitoring event, benzene, toluene and ethyl benzene were identified in ground water collected from monitor well MW-3 at concentrations of 728.0, 3,111.0 and 1,011.0 ppb, respectively. In addition, benzene and toluene were identified in ground water from monitor well MW-5 at concentrations of 1,167.0 and 5,320.0 ppb, respectively. These concentrations are above the HRL's for these constituents. TPH as GRO was also identified in ground water collected from monitor wells MW-3 and MW-5 at concentrations of 18,550.0 and 56,660.0 ppb, respectively, on November 6, 2002. In addition, laboratory analysis identified naphthalene at a concentration of 917.0 ppb in ground water from monitor well MW-3 on November 6, 2002.

During the February 27, 2003 monitoring event, benzene, toluene, ethyl benzene xylenes and TPH as GRO were identified in the ground water sample collected from monitor well MW-3 at concentrations of 349.0, 307.0, 655.0, 1,790.0 and 7,101.0 ppb, respectively. The benzene concentration is above the HRL for benzene. Benzene and TPH as GRO were identified in ground water collected from monitor well MW-4 at concentrations of 9.4 and 206.0 ppb, respectively. Benzene, toluene, ethyl benzene, xylenes and TPH as GRO were identified in ground water collected from monitor well MW-5 at concentrations of 4,888.0, 13,065.0, 1,165.0, 9,325.0 and 54,146.0 ppb, respectively. These concentrations are above the HRL's for benzene, toluene and ethyl benzene.

Ground water monitoring was again conducted at the site on May 1, 2003. Benzene, toluene, ethyl benzene, xylenes and TPH as GRO were identified in the ground water sample collected from monitor well MW-3 at concentrations of 201.0, 424.0, 493.0, 1,522.0 and 5,827.0 ppb, respectively. In addition, benzene was identified in ground water from monitor well MW-4 at a concentration of 5.0 ppb. Benzene, toluene, ethyl benzene xylenes and TPH as GRO were identified in ground water from MW-5 at concentrations of 2,566.0, 12,436.0,

1,089.0, 5,809.0 and 34,537.0 ppb, respectively. These concentrations are above the HRL's for benzene, toluene and ethyl benzene.

A duplicate ground water sample was collected from one (1) monitor well during each monitoring event, and was laboratory analyzed for BTEX and TPH as GRO. In addition, a trip blank was laboratory analyzed for BTEX. No field or laboratory interferences were identified in the trip blanks. Benzene was identified in the field duplicate sample collected during the February 27, 2003 sampling event at a concentration of 9.0 ppb.

- 6.7 Is there a clean or nearly clean (below HRLs) down-gradient monitoring well located along the longitudinal axis of the contaminant plume?

 (approximately 20 degrees plus or minus the axis)
- **6.8** Is there a worst case well completed through the source area(s) of the release?

If you have answered NO to any of the above two questions, please explain why a well was not completed in the required location.

- **6.9** Provide an estimate of the longitudinal length of the dissolved contaminant plume:
- 6.10 Calculate groundwater flow velocity (based on Darcy's Law) using the average K-value, average horizontal hydraulic gradient, and effective porosity. Provide documentation in Appendix F.

Hydraulic Conductivity (K) = 0.129 cm/sec Method: Grain-size analysis Porosity (n) = 0.35 method/reference: Freeze and Cherry, Groundwater, 1979, p. 37). Average horizontal gradient (dh/dl) = 0.0027 Calculated GW velocity (v) = $9.95 \times 10^{-4} \text{ cm/s} = 2.82 \text{ ft/day}$

- 6.11 Using the calculated groundwater flow velocity (above), is there a receptor within a five-year travel time?
 - If YES, provide the unique well number and identify the location of the receptor(s).

A domestic water supply well (Unique # 00458780) is located approximately 320 feet southeast of the release source area. In addition, municipal water supply wells #00102020 and #00215137 are located approximately 2,592 feet southeast and 1,120 feet northeast of the release source area, respectively. Based on the distances of these water wells from the release source area and natural attenuation of the petroleum impacts over time, the risk of impacts to these water wells is minimal. A six (6)-inch diameter PVC municipal water line

Page 15 Investigation Report Form February 2001

is located beneath Western Avenue, approximately 40 feet east of the release source area. This water line is at a reported depth of seven (7) feet bg. A one (1)-inch diameter copper water service line extends onto the former K-C Kwik Stop property from the abovementioned municipal water line, also at a reported depth of approximately seven (7) feet bg. In addition, a 12-inch diameter concrete storm sewer line is also located beneath Western Avenue, approximately 25 feet cast of the release source area. This storm sewer line is at a reported depth of approximately six (6) feet bg. Eight (8)-inch diameter sanitary sewer lines are reportedly located in the alleys approximately 130 feet west and 190 feet east of the release source area. These sanitary sewer lines are at a reported depth of approximately eight (8) feet bg.

6.12 Were any deep monitoring wells completed at the site?

No

If YES, list them and indicate their depths:

Contact the MPCA project hydrologist before installing a deep monitoring well. A deep monitoring well may be necessary if: 1) Contamination exists more than 10 feet below the water table or 2) the impacted aquifer is a drinking water aquifer or is hydraulically connected to the aquifer(s) presently utilized by a water supply well located within 500 feet of the release source.

If contamination is present at depth in the aquifer or in deeper aquifers, additional deep wells may be required. Provide the following information if deep wells are installed:

Vertical Gradient (dv/dl)
Inferred GW Flow Direction

Provide the following information for the deep aquifer unit if it appears to be hydrogeologically distinct from the upper unit.

Porosity (n): Hydraulic Conductivity (K)

Submit this RI report after completing a minimum of two quarterly sampling events. Groundwater monitoring should continue until MPCA response is received.

Page 16 Investigation Report Form February 2001

Section 7: Evaluation of Natural Attenuation

Refer to the fact sheet #3.21 Assessment of Natural Attenuation at Petroleum Release Sites. **Note**: Evaluation of natural attenuation is not required unless requested by MPCA staff.

- 7.1 Attach Table 12 Natural Attenuation Parameters. Discuss the results. Specifically, compare the concentrations of the inorganic parameters inside and outside the plume.

 Natural Attenuation Parameters were not analyzed per MPCA directive.
- 7.2 In your judgment, is natural biodegradation occurring at this site? Please Yes No Explain.

If active remediation is anticipated, discuss reasons why natural attenuation (including biodegradation) can not adequately remediate the contaminants to acceptable risk levels.

Section 8: Well Receptor Information/Assessment

Include in Appendix E, copies of the water supply well logs obtained from MGS, MDH, drillers, and where applicable, from County well management authorities.

- 8.1 Attach Table 13 Properties Located Within 500 Feet of the Release Source. Provide a map identifying the features listed in Table 13.
- 8.2 Were all property owners within 500 feet of the release source successfully No contacted to determine if water wells are present? If NO, please explain.

 Several residential property owners were not available for contact when Coteau personnel were onsite. A water well survey form was left at each property where the occupant was not available. The survey form indicates that if the survey is not returned to Coteau, it is assumed that no water well is present on the property. No water well survey forms have been returned to Coteau as of the date of this report.
- 8.3 Attach Table 14 Water Supply Wells Located within 500 Feet of the Release Source and Municipal or Industrial Wells Within ½ Mile.
- 8.4 Discuss the results of the ground water receptor survey and any analytical results from sampling conducted at nearby water wells. Comment on the risks to water supply wells identified within 500 feet from the release source as well as the risk posed by or to any municipal or industrial wells found within ½ mile. Specifically indicate whether water supply wells identified utilize the impacted aquifer. (Note: an impacted aquifer separated from another aquifer by a clay lens may not be considered a separate aquifer).

Water supply well boring records were obtained from the MGS. A domestic water supply well (#00458780) is located approximately 320 feet southeast of the release source area. This water well is at a total depth of 45 feet bg and had a static water level of 12 feet bg at the time of construction. Two municipal water supply wells (00102020 and 00215137) are located approximately 2,590 feet southeast and 1,120 feet northeast of the release source area, respectively. These municipal water wells are at total depths of 166 and 220 feet bg, respectively, and had static water levels of 21 and 22 feet bg, respectively, at the time of construction. The above-mentioned water wells appear to utilize the impacted aquifer beneath the site. The risk to these water wells from petroleum impacts at the former K-C Kwik Stop property appears to be present, but minimal. Water samples were not collected from any of the above-mentioned water wells.

8.5 Is municipal water available in the area?

Yes

Page 18 Investigation Report Form February 2001

8.6 Are there any plans for ground water development in the impacted aquifer within 1/2 mile of the site, or one mile down-gradient of the site if the aquifer is fractured? Please give the name, title and telephone number of the person that was contacted for this information (below).

No

Mr. Mike Rooney Telephone: (320) 346-2630

Page 19 Investigation Report Form February 2001

Section 9: Surface Water Risk Assessment

9.1 Are there any surface waters or wetlands located within ¼ mile of the site?							
If	YES, list them:						
gra	surface water is present down-gradient of the site adient monitoring well (temporary or permanent) d the surface water?		N/A				
	you answered <i>NO</i> to question 9.2, we assume thater. Therefore, complete the following informations		surface				
	Name of receiving water:						
	Receiving water classification						
	ORVW?	☐ Yes ☐ No					
	Plume width, (W):	feet					
	Plume thickness, (H):	feet					
	Hydraulic conductivity, (K):	gal/day/ft²					
	Horizontal gradient, (dh/dl):	(unitless)					
	Discharge, (Q) = $H*W*K*(dh/dl)/1440$	gal/min					
	Applicable chronic standard (7050 or 7052)						
	Applicable max. standard (7050 or 7052)						
	Applicable FAV (7050 or 7052)						
	Contaminant concentration in ground water						
9.4 If	you answered YES to question 9.2, identify the cl	ean down-gradient boring or	monitor				

well, the distance to the surface water feature, and discuss the contamination risk potential.

Section 10: Vapor Risk Assessment/Survey

10.1 Is there a history of vapor impacts in the vicinity of the site?

No

No

If YES, describe:

10.2 Is there any indication that free product or contaminated ground water may be traveling off-site within the utility corridors?

If YES, utility backfill investigation is required (refer to Fact Sheet 3.19). Discuss the investigation rationale and results.

10.3 Discuss the potential for vapor migration/accumulation near the site. Your discussion should consider: Soil types, product type, presence and distribution of free product or high concentrations of dissolved product. Also, using cross-sections to illustrate the relationship, compare the depth of contamination with the location of underground utility lines, location and depth of storm and sanitary sewers, and location of nearby basements and sumps.

Locations and depths of utility lines in the vicinity of the release source area were discussed in section 6.11. The average depth-to-water levels measured in the monitor wells on August 12 and November 12, 2002 and February 27 and May 1, 2003 were 9.04, 9.48, 8.90 and 10.00 feet bg, respectively. A PVC municipal water line located approximately 40 feet east of the property is at a depth of approximately seven (7) feet bg. A concrete storm sewer line located approximately 25 feet east of the release source area is at a reported depth of six (6) feet bg. Sanitary sewer lines located near the site are constructed of PVC pipe and are at a reported depth of approximately eight (8) feet bg. Based on this information, it appears that the potential for vapor migration/accumulation in the vicinity of the site is present.

Page 21 Investigation Report Form February 2001

10.4 Conduct a vapor survey if the vapor risk assessment indicated a risk of vapor impacts to buildings or utilities. Ask occupants of nearby buildings if they have smelled petroleum odors. See fact sheet 3.20 Potential Receptor Surveys and Risk Evaluation Procedures at Petroleum Release Sites. Identify all vapor monitoring locations on an attached site map by labeling each monitoring location with a number. Tabulate the list of vapor monitoring locations in Table 15. Vapor monitoring methods, including instruments used, must be discussed in Appendix C. Provide a detailed description of each vapor monitoring location and an interpretation of the vapor monitoring results below.

A vapor survey was conducted in the vicinity of the site on August 8, 2002. Eight (8) residential basements, four (4) sanitary sewer manholes, three (3) storm sewer manholes and two (2) storm sewer drain basins were screened for organic vapors during the survey. A PID reading of 2.1 ppm was measured in one (1) sanitary sewer manhole (location #23 on Figure 10). A water sample was collected from the manhole. A PID reading was taken from the water sample headspace, with a resulting reading of 0.5 ppm. No other elevated organic vapor concentrations were identified during the vapor survey on August 8, 2002.

10.5 Attach Table 15 - Results of Vapor Monitoring.

Page 22 Investigation Report Form February 2001

Section 11: Discussion

11.1 Discuss the risks associated with the remaining soil contamination:

Municipal water, sanitary sewer and storm sewer lines are present in the vicinity of the site. However, soil impacts appear to be limited to the former K-C Kwik Stop property (Figures 4 and 5). Soil borings B-2, B-6, B-8 and B-7 surround the release source area, and are clean or have relatively low soil impacts. A copper water service line extends onto the property and is located within the impacted area. However, due to the copper construction of the water service line, the risk of impacts to the water line appear to be minimal. It appears that the extent of soil impacts has been defined. Therefore, risks associated with the remaining soil contamination on the property appear to be minimal.

11.2 Discuss the risks associated with the impacted ground water:

It appears that a resource aquifer has been impacted. Based on two (2) ground water monitoring events conducted on August 6 and November 6, 2002, ground water flow in the vicinity of the site to the east-northeast. During two (2) monitoring events conducted on February 27 and May 1, 2003, ground water flow was to the east-southeast. Additional monitoring will be required to determine the predominant flow direction at the site. The extent of ground water impacts appears to be defined. Based on the anticipated easterly ground water flow direction, there appears to be a potential risk to PVC water and sanitary sewer lines and concrete storm sewer lines located east and northeast of the site. In addition, several residential basements are located approximately 60 feet east of the release source area, in the apparent downgradient direction from the site. A vapor survey was conducted in the vicinity of the site on August 8, 2002. No elevated concentrations of organic vapors were identified during the vapor survey. Also, one (1) domestic and two (2) municipal water supply wells are located within a calculated five (5) year travel time of the contaminant plume. The ground water impacts at the site appear to pose a potential risk to these water wells, but because of the distances of the wells from the release source area and natural attenuation of the petroleum impacts over time, the risk appears to be minimal.

11.3 Discuss other concerns not mentioned above:

NONE

Page 23 Investigation Report Form February 2001

Section 12: Conclusions and Recommendations

site closure
additional vapor monitoring
X additional ground water monitoring
active remediation

12.2 Base the recommendation above on fact sheet #3.1 Leaking Underground Storage Tank Program. Describe below how you applied the policy to support your recommendation. If closure is recommended, please summarize significant site investigative events and describe how site specific risk issues have been adequately addressed or minimized to acceptable low risk levels.

It appears that a resource aquifer has been impacted. The extent of ground water impacts has been defined. A risk of vapor migration and/or accumulation and a risk to water supply wells in the vicinity of the site appears to be present. Water wells within 0.5 mile of the site appear to utilize the impacted resource aquifer. No surface water is located within 0.25 mile of the site.

- 12.3 If additional monitoring is recommended, indicate the proposed monitoring schedule and frequency. Conduct quarterly monitoring until the MPCA responds to this report.
 - Coteau recommends quarterly ground water monitoring of all monitor wells at the site for a period of one (1) year. Fluid levels will be measured in the monitor wells on a quarterly basis to determine the predominant ground water flow direction at the site. If free-phase product is identified in any of the wells, product recovery will be initiated immediately utilized a disposable polyethylene bailer. A petroleum-absorbent sock will be placed in the well immediately following free product recovery. Ground water samples will be collected from all wells not containing 0.10 foot or greater of free product on a quarterly basis for laboratory analysis of BTEX and TPH as GRO. Coteau also recommends that sanitary and storm sewer manholes located on Western Avenue, south of Highway 55, and residential basements at 100, 110 and 120 South Western Avenue be surveyed for organic vapors on a semi-annual basis.
- 12.4 If active remediation is proposed, then recommend a conceptual approach by listing the remedial technologies or combination of technologies that are likely feasible. MPCA staff will review this RI report at a higher than normal priority to determine if active remediation is required. We will respond with either a request for proposal for additional monitoring or a Corrective Action Design report.

Section 13: Figures

Attach the following figures in order of discussion in the text:

- X Site location map using a U.S. Geological Survey 7.5 minute quadrangle map.
- X One or more site map showing:
 - Structures
 - Locations and depths of on-site buried utilities
 - All past and present petroleum storage tanks, piping, and dispensers
 - Extent of soil excavation
 - Boring and well locations (including any drinking water wells on site)
 - Horizontal extent of soil contamination
 - Horizontal extent of ground water contamination
 - Location of end points for all geologic cross sections.

Distinguish sequential elements of investigations by dates, symbols, etc. in the key.

- X Ground water gradient contour maps (for sites with monitoring wells) for each gauging event.
- X Well receptor survey map showing 1/2 mile radius, 500 foot radius, water supply wells, other potential sources of contamination, using a U.S. Geological Survey 7.5 minute quadrangle.
- X Vapor survey map showing utilities and buildings with basements and monitoring locations (if a survey was required).
- X Provide at least two (2) geologic cross sections, including utilities.

lables

Section 14: Tables

Table 1
Tank Information

Tank #	UST or AST	Capacity	Contents	Year Installed	Status*	Condition
1	UST	4,000	Diesel Fuel	1986	Removed 4-17-02	Good
2	UST	6,000	Gasoline	1986	Removed 4-17-02	Fair; some pitting
3	UST	6,000	Gasoline	1986	Removed 4-17-02	Fair

^{*}Indicate: removed (date), abandoned in place (date), or currently used Notes:

Table 2
Results of Soil Headspace Screening

Depth	Soil Boring									
(ft)	1	2	3	4	5	6	7	8	9	10
0-4	NS**	11.5*	ND	4.1	402.0*	61.0*	ND	4.0	4.3	ND
4-8	NS**	63.1*	ND	808.2	250.0*	60.0*	3.4	13.0*	11.5*,	0.5
8-12	653.0	198.0	881.0	1,363.0	92.0*	32.0*	15.0	11.0*	4.0	2.8
12-16	308.0	40.1	1,130.0	212.2	94.0	2.3	50.0	8.6	2.8	0.7
16-20	3.9	2.9	NS	21.9	526.0	ND	ND	ND	1.4	0.4
20-24	0.2	3.2	1.1	2.4						
24-28	ND	ND	ND	ND						
28-32	ND									

List instruments used and discuss field methods and procedures in Appendix C.

Notes: NS = Not sampled

ND = Nondetectable

^{*} PID malfunction suspected.

^{**} Soil boring B-1 was sampled non-continuously to a depth of 10 feet because the boring was completed in the UST excavation basin.

Table 3
Analytical Results of Soil Samples

Boring, Depth(ft)	Date Sampled	Benzene	Toluene	Ethyl benzene	Xylenes	GRO	DRO	Lab Type
B-1(9-12)	6-13-02	19.000	300.000	140.000	610.000	4,600	NA	F
B-2(10-12)	6-13-02	< 0.050	< 0.050	< 0.050	0.380	4	NA	F
B-3(9-12)	6-13-02	23.000	660.000	320.000	2,100.000	9,100	NA	F
B-3(15-18)	6-13-02	<1.000	21.000	13.000	65.000	490	NA	F
B-4(9-11)	6-13-02	29.000	590.000	180.000	800.000	5,900	NA	F
B-5(8-10)	8-6-02	< 0.050	< 0.050	< 0.050	< 0.060	<4	NA	F
B-5(17-19)	8-6-02	0.260	0.110	0.410	2.100	17	NA	F
B-6(2-4)	8-7-02	< 0.050	< 0.050	< 0.050	<0.060	<4	NA	F
B-6(8-10)	8-7-02	< 0.050	< 0.050	< 0.050	< 0.060	<4	NA	F
B-7(8-10)	8-7-02	< 0.050	< 0.050	< 0.050	< 0.060	<4	NA	F
B-7(12-14)	8-7-02	< 0.050	< 0.050	< 0.050	< 0.060	<4	NA	F
B-8(8-10)	8-7-02	< 0.050	< 0.050	0.090	0.270	<4	NA	F
B-8(13-15)	8-7-02	< 0.050	< 0.050	< 0.050	< 0.060	<4	NA	F
B-9(8-10)	8-7-02	< 0.050	< 0.050	< 0.050	< 0.060	<4	NA	F
B-10(10-12)	2-4-03	< 0.100	< 0.100	< 0.070	< 0.200	<4	NA	F

Report results in mg/kg. Use less than symbols to show detection limit. Indicate mobile or fixed based in the lab type column.

Notes: NA = Not analyzed for parameter

Table 4
Other Contaminants Detected in Soils (Petroleum or Non-petroleum Derived)

Boring, Depth (ft)	Date Sampled	МТВЕ		Lab Type
B-1(9-12)	6-13-02	94.000		F
B-2(10-12)	6-13-02	< 0.050		F
B-3(9-12)	6-13-02	67.000		F
B-3(15-18)	6-13-02	8.000		F
B-4(9-11)	6-13-02	150.000		F
B-5(8-10)	8-6-02	< 0.050		F
B-5(17-19)	8-6-02	0.300		F
B-6(2-4)	8-7-02	< 0.050		F
B-6(8-10)	8-7-02	< 0.050		F
B-7(8-10)	8-7-02	< 0.050		F
B-7(12-14)	8-7-02	< 0.050		F
B-8(8-10)	8-7-02	< 0.050		F
B-8(13-15)	8-7-02	< 0.050		F
B-9(8-10)	8-7-02	< 0.050		F
B-10(10-12)	2-4-03	<0.120		F

Report results in mg/kg. Indicate other contaminants (either petroleum or non-petroleum derived) detected in soil collected from borings.

Notes:

Page 29 Investigation Report Form February 2001

Table 5
Water Level Measurements and Depths of Water Samples Collected from Borings

		Soil Boring								
	1	2	3	4	5	6	7	8	9	10
Static Water	10.2	9.7	12.85	10.2		NM	NM	NM	NM	NM
level depth (ft)										
Sampled	10.2	9.7	12.85	10.2	NS	NS	NS	NS	NS	NS
Depth (ft)										

Describe in Appendix C, the methods and procedures used to measure water levels in borings. Notes: Ground water samples were not collected from borings B-6, B-7, B-8, B-9 and B-10 because these borings were completed as monitor wells at the time of drilling. Ground water was not encountered in boring B-5 during drilling on August 6, 2002.

Table 6
Analytical Results of Water Samples Collected from Borings

Boring	Date	Sampled	Benzene	Toluene	Ethyl	Xylenes	MTBE	GRO	DRO	Lab Type
Number	Sampled	Depth			benzene					
B-1	6-13-02	10.2	1,254.0	4,798:0	763.0	3,684.0	<20.0	44,993.0	NA	F
B-2	6-13-02	9.7	< 0.010	98.0	66.0	761.0	< 0.40	4,211.0	NA	F
B-3	6-13-02	12.85	101.0	4,696:0	1,259.0	7,057.0	< 2.0	350,157.0	NA	F
B-4	6-13-02	10.2	209:0	9,054.0	2;686:03	16,028.0	<10.0	338,583.0	NA	F
										<u> </u>
Trip						i				
Blank										
Field			1	ļ	ļ					1
Blank									<u> </u>	ļ
Lab			1							
Blank									<u> </u>	-
HRL			10	1000	700	10000				

Report results in ug/L. Use less than symbols to show detection limit. Indicate mobile or fixed based in the lab type column.

Notes: Ground water samples were not collected from borings B-5, B-6, B-7, B-8 and B-9.

Borings B-6, B-7, B-8 and B-9 were completed as monitor wells at the time they were drilled.

Page 30 Investigation Report Form February 2001

Table 7
Other Contaminants Detected in Water Samples
Collected from Borings (Petroleum or Non-petroleum Derived)

Boring Number	Date Sampled	1,2 DCA	EDB	1,2,,4-Tri methyl benzene	1,3,5-Tri methyl benzene	Naph- thalene	Isopropyl benzene	n-Propyl benzene
B-1	6-13-02	<3.0	<25.0	725.0	<1.0	1,265.0	<1.0	<1.0
B-2	6-13-02	< 0.060	< 0.50	336.0	100.0	75.0	7.0	11.0
B-3	6-13-02	<0.30	<2.5	2,338.0	1,008.0	825.0	144.0	488.0
B-4	6-13-02	<1.5	<12.5	6,246.0	1,960.0	2,940:0	227.0	915.0
Trip								
Blank								
Field				E				
Blank								
Lab								į
Blank			i					
HRL (ug/L)		4	0.004			300	<u> </u>	

Report results in ug/L. Indicate other contaminants (either petroleum or non-petroleum derived) detected in water samples collected from the borings, temporary wells or push probes.

Notes:

Table 8
Monitoring Well Completion Information

Well Number	Unique Well Number	Date Installed	Surface Elevation	Top of Riser Elevation	Bottom of Well (Elevation)	Screen Interval (Elev Elev.)
MW-1	672919	8-7-02	99.88	100.00	80.88	95.88-80.88
MW-2	672922	8-7-02	99.67	102.46	80.67	95.67-80.67
MW-3	672921	8-7-02	99.69	102.58	80.69	95.69-80.69
MW-4	672920	8-7-02	99.99	102.73	80.99	95.99-80.99
MW-5	672918	8-2-02	99.57	99.64	80.57	95.57-80.57
MW-6	672950	2-4-03	99.74	99.76	80.74	95.74-80.74
L			<i>c</i>	11) (III 1 D - C		100 C4

Notes: Benchmark is the top of riser of monitor well MW-1. Reference elevation = 100 feet

Page 31 Investigation Report Form February 2001

Table 9
Water Level Measurements in Wells

Well Number	Date Sampled	Depth of Water from Top of Riser	Product Thickness	Depth of Water Below Grade	Relative Groundwater Elevation	Water Level Above Screen (Y/N)
MW-1	8-12-02	8.97		8.85	91.03	N
	11-6-02	9.51		9.39	90.49	N
	2-27-03	10.76		10.64	89.24	N
	5-1-03	10.24		10.12	89.76	N
MW-2	8-12-02	11.97		9.18	90.49	N
	11-6-02	12.23		9.44	90.23	N
	2-27-03	13.39		10.60	89.07	N
	5-1-03	12.97		10.18	89.49	N
MW-3	8-12-02	11.95		9.06	90.63	N
	11-6-02	12.39		9.50	90.19	N
	2-27-03	13.67		10.78	88.91	N
	5-1-03	12.20		9.31	90.38	N
MW-4	8-12-02	12.03		9.29	90.70	N
	11-6-02	12.51		9.77	90.22	N
	2-27-03	13.74		11.00	88.99	N
· · · · · · · · · · · · ·	5-1-03	12.32		9.58	90.41	N
MW-5	8-12-02	8.89		8.82	90.75	N
	11-6-02	9.38		9.31	90.26	N
	2-27-03	10.60		10.53	89.04	N
	5-1-03	10.16		10.09	89.48	N
MW-6	2-27-03	11.10		11.08	88.66	N
	5-1-03	10.74		10.72	89.02	N

Describe in Appendix C, the methods and procedures used to measure water levels. Notes:

Table 10
Analytical Results of Water Samples Collected from Wells

Well#	Date Sampled	Benzene	Toluene	Ethyl benzene	Xylenes	МТВЕ	GRO	DRO	Lab Type
MW-1	8-12-02	< 0.010	< 0.010	< 0.010	< 0.010	< 0.40	<100.0	NA	F
	11-6-02	<0.010	< 0.010	<0.010	< 0.010	<0.40	<100.0	NA	F
	2-27-03	<1.0	<1.0	<1.0	<1.0	NA	<100.0	NA	F
	5-1-03	<1.0	<1.0	<1.0	<1.0	NA	<100.0	NA	F
MW-2	8-12-02	< 0.010	< 0.010	< 0.010	< 0.010	< 0.40	<100.0	NA	F
	11-6-02	<0.010	< 0.010	< 0.010	< 0.010	< 0.40	<100.0	NA	F
	2-27-03	<1.0	<1.0	<1.0	<1.0	NA	<100.0	NA	F
	5-1-03	<1.0	<1.0	<1.0	<1.0	NA	<100.0	NA	F
MW-3	8-12-02	< 0.010	< 0.010	< 0.010	< 0.010	< 0.40	<100.0	NA	F
	11-6-02	728:0	3,1111:0	1,0,11.0	4,667.0	<40.0	18,550.0	NA	F
	2-27-03	349.0	307.0	655.0	1,790.0	NA	7,101.0	NA	F
	5-1-03	201:0	424.0	493.0	1,522.0	NA	5,827.0	NA	F
MW-4	8-12-02	< 0.010	< 0.010	< 0.010	< 0.010	< 0.40	288.0	NA	F
	11-6-02	< 0.010	< 0.010	< 0.010	< 0.010	<0.40	186.0	NA	F
	2-27-03	9.4	<1.0	<1.0	<1.0	NA	206.0	NA	F
	5-1-03	5.0	<1.0	<1.0	<1.0	NA	<100.0	NA	F
MW-5	8-12-02	503:0	1,187.0	347.0	1,863.0	<4.0	13,919.0	NA	F
	11-6-02	1,167/0	5,320,0	647.0	3,548.0	<4.0	56,660.0	NA	F
	2-27-03	4,888:0	(13,065:0)	1,165.0	9,325.0	NA	54,146.0	NA	F
	5-1-03	2,566:0	12,436.0	41,089.0	5,809.0	NA	34,537.0	NA	F
MW-6	2-27-03	< 0.010	< 0.010	< 0.010	< 0.010	< 0.40	<100.0	NA	F
	5-1-03	< 0.010	< 0.010	< 0.010	< 0.020	< 0.40	<100.0	NA	F
Trip Blank	8-12-02	<1.0	<1.0	<1.0	<1.0	NA	NA	NA	F
	11-6-02	<1.0	<1.0	<1.0	<1.0	NA	<100.0	NA	F
	2-27-03	<1.0	<1.0	<1.0	<1.0	NA	NA	NA	F
	5-1-03	<1.0	<1.0	<1.0	<1.0	NA	NA	NA	F
Field Duplicate	8-12-02	<1.0	<1.0	<1.0	<1.0	NA	<100.0	NA	F
	11-6-02	<1.0	<1.0	<1.0	<1.0	NA	<100.0	NA	F
	2-27-03	9.0	<1.0	<1.0	<1.0	NA	<100.0	NA	F
	5-1-03	<1.0	<1.0	<1.0	<1.0	NA	<100.0	NA	F
Lab Blank HRL(ug/L)		10	1000	700	10000				

Report results in ug/L. Use less than symbols to show detection limit. Indicate mobile or fixed based in the lab type column. Notes: NA = Not analyzed for parameter F = Fixed-based laboratory

Table 11
Other Contaminants Detected in Water Samples
Collected from Wells (Petroleum or Non-petroleum Derived)

Well Number	Date Sampled	1,2 DCA	EDB	1,2,4-Tri methyl benzene	1,3,5-Tri methyl benzene	Acetone	Naph- thalene	n-Propyl benzene	1,4- Dichloro benzene	Chloro- form
MW-1	8-12-02	< 0.060	< 0.50	<0.020	< 0.020	<2.0	< 0.070	< 0.020	<0.080	< 0.050
	11-6-02	< 0.060	< 0.50	< 0.020	< 0.020	<2.0	< 0.070	< 0.020	5.0	6.0
MW-2	8-12-02	< 0.060	< 0.50	<0.020	< 0.020	<2.0	< 0.070	< 0.020	<0.080	< 0.050
	11-6-02	< 0.060	< 0.50	< 0.020	< 0.020	<2.0	< 0.070	< 0.020	<0.080	< 0.050
MW-3	8-12-02	< 0.060	< 0.50	< 0.020	< 0.020	<2.0	< 0.070	< 0.020	<0.080	< 0.050
	11-6-02	<6.0	<50.0	1,011.0	<2.0	<200.0	917:0	<2.0	<8.0	<5.0
MW-4	8-12-02	< 0.060	< 0.50	< 0.020	< 0.020	<2.0	< 0.070	< 0.020	<0.080	< 0.050
	11-6-02	< 0.060	< 0.50	< 0.020	< 0.020	<2.0	< 0.070	< 0.020	<0.080	<0.050
MW-5	8-12-02	< 0.60	<5.0	373.0	107.0	910:0	281.0	< 0.20	<0.80	< 0.50
	11-6-02	< 0.60	<5.0	866.0	254.0	<20.0	269.0	110.0	<0.80	< 0.50
MW-6	2-27-03	< 0.060	< 0.50	< 0.020	< 0.020	<2.0	< 0.070	< 0.020	<0.080	< 0.050
	5-1-03	< 0.060	< 0.50	< 0.020	< 0.020	<2.0	< 0.070	< 0.020	<0.080	<0.050
Field Blank										
Trip Blank										
Lab Blank										
HRL (ug/L)		4	0.004			700	300			60

Report results in ug/L. Indicate other contaminants (either petroleum or non-petroleum derived) detected in water samples collected from the borings, temporary wells or push probes.

Notes:

Page 34 Investigation Report Form February 2001

Table 12 Natural Attenuation Parameters

Sample Date	Temp. °C	pН	Dissolved Oxygen (mg/L)	Nitrate (mg/L)	(Fe II) (mg/L)	(H ₂ S, HS ⁻) (mg/L)
NOT						
ANALYZED						
	NOT	°C NOT	NOT °C	°C Oxygen (mg/L)	°C Oxygen (mg/L) NOT Oxygen (mg/L)	°C Oxygen (mg/L) (mg/L) NOT Oxygen (mg/L) Oxygen (mg/L)

In Appendix C, describe the methods and procedures used.
Notes

Properties Located Within 500 Feet of the Release Source. Table 13

							_	_	- 1		1			- 1				
Comments (including property use)	Residential-Vacant	Residential-occupant not present	Residential	Residential- refused access	Residential-occupant not present	Residential	Residential	Residential	Residential-occupant not present	Residential	Residential	Residential-occupant not present	Residential	Residential	Residential-occupant not present	Residential-occupant not present	Residential-occupant not present	Residential-occupant not present
Possible Petroleum Sources (Y or N)	Unknown	Unknown	Z	Unknown	Unknown	z	z	Z	Unknown	Z	Z	Unknown	z	Z	Unknown	Unknown	Unknown	Unknown
Basement Or Sumps (Y or N)	z	Å ,	Y	Υ	>	Υ	λ	Y	Ϋ́	Y	,	7	Å	Υ	Y	7	٨	z
Confirmed By City (Y or N)	λ	\	λ	Å	X	¥	Y	Y	Υ	Å	Å	λ	¥	λ	X	*	A	>
Public Water Supply (Y or N)	Y	٨	Y	γ	¥	>-	*	Y	¥	>	٨	Y	Y	λ	٨	X	Y	Y
Well Use**	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Not Used	Not Used	N/A	N/A	N/A	N/A	N/A	N/A	N/A
How Determined*	0/	Assumed	PC	PC	Assumed	PC	PC	PC	Assumed	PC	PC	Assumed	PC	PC	Assumed	Assumed	Assumed	Assumed
Water Well (Y or N)	z	z	z	z	z	z	Z	z	z	>	>	z	z	Z	z	z	z	z
Property Address	111 N. Western Ave.	121 N. Western Ave.	131 N. Western Ave.	141 N. Western Ave.	141 S. Western Ave.	121 S Western Ave	111 S. Western Ave.	100 N. Western Ave.	120 N. Western Ave.	130 N. Western Ave.	110 S Western Ave.	120 S. Western Ave.	130 S Western Ave	221 1St Street	201 School Ave.	100 S. Western Ave.	140 S. Western Ave.	131 S. Western Ave.
# (From Map)	-	2	3	4	\$	4	> -	. 00	6	10	Ξ	12		51	15	91	17	81

*E.g., visual observation, personal contact, telephone, returned postcard, assumed (i.e., no postcard returned). **E.g., domestic, industrial, municipal, livestock, lawn/gardening, irrigation. $VO = Visual \ Observation$

Fact Sheet 3 24. February 2001 Leaking Petroleum Storage Tanks

Table 14
Water Supply Wells Located Within 500 Feet of the
Release Source and Municipal or Industrial Wells Within ½ Mile

Unique Well #	Ground Elevation	Total Depth (ft)	Base of Casing (ft)	Static Elevation	Aquifer	Use	Owner	Distance & Direction from source
00458780	1310	45	40	1298	QWTA	D	John Bohmer	320 feet SE
00102020	1308	166	141	1287	QBAA	M	City of Brooten	2,590 feet SE
00215137	1312	220	210	1290	QBAA	М	City of Brooten	1,120 feet NE

Notes: D = Domestic

M = Municipal

Fact Sheet 3.24: February 2001 Leaking Petroleum Storage Tanks

Table 15
Results of Vapor Monitoring

Location # and description	Date	PID reading	Percent
		(ppm)	of the LEL
3-Residential Basement	8-8-02	0.0	000
6-Residential Basement	8-8-02	0.0	000
7-Residential Basement	8-8-02	0.0	000
8-Residential Basement	8-8-02	0.0	000
10-Residential Basement	8-8-02	0.0	000
11-Residential Basement	8-8-02	0.0	000
13-Residential Basement	8-8-02	0.0	000
14-Residential Basement	8-8-02	0.0	000
19-Sanitary Sewer Manhole	8-8-02	Top-0.0	Top-000
(Approx. 12 feet deep)		Middle-0.0	Middle-000
		Bottom-0.0	Bottom-000
20-Storm Sewer Manhole	8-8-02	Top-0.0	Top-000
(Approx. 4 feet deep)		Bottom-0.0	Bottom-000
21-Sanitary Sewer Manhole	8-8-02	Top-0.0	Top-000
(Approx. 15 feet deep)		Middle-0.0	Middle-000
1		Bottom-0.0	Bottom-000
22-Sanitary Sewer Manhole	8-8-02	Top-0.0	Top-000
(Approx. 6 feet deep)		Bottom-0.0	Bottom-000
23-Sanitary Sewer Manhole	8-8-02	Top-2.1*	Top-000
(Approx. 6 feet deep)		Bottom-0.0	Bottom-000
24-Storm Sewer Manhole	8-8-02	0.0	000
(No flow)			
25-Storm Sewer Manhole	8-8-02	0.0	000
(No flow)			
26-Storm Sewer Basins	8-8-02	0.0	000

Notes: Location numbers must match locations on the site map. Provide a brief description of the monitoring point (e.g., sump, basement corner, sanitary sewer manhole, storm sewer basin, etc.).

^{*} A water sample was collected from the sanitary sewer manhole (location #23). A PID reading was taken from the sample headspace, with a result of 0.5 ppm.

Section 15: Appendices

Attach the following appendices.

X	Appendix A	Excavation Report Worksheet for Petroleum Release Sites.
X	Appendix B	Laboratory Analytical Reports for Soil and Ground Water. Include laboratory QA/QC data and laboratory certification number.
X	Appendix C	Methodologies and Procedures, Including Field Screening of Soil, Other Field Analyses, Soil Boring, Soil Sampling, Well Installation, and Water Sampling.
X	Appendix D	Geologic Logs of Soil Borings, Including Construction Diagrams of Temporary and Permanent Wells, and Copies of the Minnesota Department of Health Well Record.
X	Appendix E	Copies of Water Supply Well Logs With Legible Unique Numbers.
X	Appendix F	Grain Size Analysis, Hydraulic Conductivity Measurements, and Other Calculations.

Section 16: Consultant (or other) Information

By signing this document, I/we acknowledge that we are submitting this document on behalf of and as agents of the responsible person or volunteer for this leak site. I/we acknowledge that if information in this document is inaccurate or incomplete, it will delay the completion of remediation and may harm the environment and may result in reduction of reimbursement awards. In addition, I/we acknowledge on behalf of the responsible person or volunteer for this leak site that if this document is determined to contain a false material statement, representation, or certification, or if it omits material information, the responsible person or volunteer may be found to be in violation of Minn. Stat. § 115.075 (1994) or Minn. R. 7000.0300 (Duty of Candor), and that the responsible person or volunteer may be liable for civil penalties.

MPCA staff are instructed to reject unsigned investigation reports or if the report form has been altered.

Name and Title:

Andrew M. Schmidt, EIT Environmental Engineer Nathan T. Hunke, P.G., M.S. Senior Hydrogeologist

Signature:

Date signed:

Company and mailing address:

Coteau Environmental

728 Janes Circle Drive SW

605/ 29c/ 40ch Alexandria, Minnesota 56308

Phone:

(320) 846-4668


Fax:


(320) 846-4668


Upon request, this document can be made available in other formats, including Braille, large print and audio tape. TTY users call 651/282-5332 or Greater Minnesota 1-800/657-3864.


Printed on recycled paper containing at least 10 percent fibers from paper recycled by consumers.


Figures

























































Appendices



APPENDIX A EXCAVATION REPORT WORKSHEET



Leaking Petroleum Storage Tanks

Minnesota Pollution Control Agency

http://www.pca.state.mn.us/programs/lust_p.html

EXCAVATION REPORT WORKSHEET FOR PETROLEUM RELEASE SITES

Fact Sheet #3.7

Complete the information below to document excavation and treatment of petroleum contaminated soil. Conduct excavations in accordance with fact sheet #3.6 Excavation of Petroleum Contaminated Soil During Tank Removal. Please attach any available preliminary site investigation reports to this excavation report, and attach additional pages if necessary. Please type or print clearly. Do not revise or delete text or questions from this report form.

The excavation worksheet deadline is 10 months from the date of receipt of the MPCA "Petroleum Storage Tank Release Investigation and Corrective Action" letter. MPCA staff may establish a shorter deadline for high priority sites.

PART I: BACKGROUND

A. Site: Former K-C Kwik Stop MPCA Site ID#: LEAK00014698

Street: 230 1st Street

City, Zip: Brooten, Minnesota 56316

County: Stearns

Latitude 45^o 30' 03"N Longitude 95^o 07' 39"W Circle one: <u>UTM</u> / State 15 333791E, 5040564N

C. Excavating Contractor:

Rollie's Sales and Service

Contact: Marvin Rollie Telephone: (320) 859-4811

Tank Contractor Certification Number: 1371

B. Tank Owner/Operator:

North American State Bank Mailing Address: P.O. Box 189

Street/Box: 321 Washburn Ave. City, Zip: Belgrade, MN 56312 Telephone: (320) 254-8271

D. Consultant: Coteau Environmental

Contact: Nathan Hunke

Street/Box: 3930 Sunnybrook Drive NW

City, Zip: Alexandria, MN 56308 Telephone: (320) 846-4668

E. Others on-site during site work (e.g., fire marshal, local officials, MPCA staff, etc.): None

Note: If person other than tank owner and/or operator is conducting the cleanup, provide name, address, and relationship to site on a separate attached sheet.

PART II: DATES

- A. Date release reported to MPCA: April 17, 2002
- B. Dates site work performed (tanks removed, piping removed, soil excavation, soil borings, etc.):

Work Performed UST system removal

Date April 17, 2002

PART III: SITE AND RELEASE INFORMATION

- A. Describe the land use and pertinent geographic features within 1,000 feet of the site. (i.e. residential property, industrial, wetlands, etc.)

 Residential and commercial properties are located within 1,000 feet of the site.
- B. Provide the following information for all tanks removed and any remaining at the site:

Table 1.

Tank #	UST or AST	Capacity (gallons)	Contents (product type)	Year installed	Status*	Condition of Tank
1	UST	4,000	Diesel Fuel	1986	Removed 4-17-02	Good
2	UST	6,000	Gasoline	1986	Removed 4-17-02	Fair; Some pitting
3	UST	6,000	Gasoline	1986	Removed 4-17-02	Fair

^{*}Indicate: removed (date), abandoned in place (date), or currently used Notes:

C. Describe the location and status of the other components of the tank system(s), (i.e., piping and dispensers) for those tanks listed above.

The pump dispensers formerly located at the site were removed on April 17, 2002. The pump dispensers were removed prior to Coteau personnel arriving at the site. Reportedly, the pump dispensers were in good condition at the time of removal.

D. Identify and describe the source or suspected source(s) of the release and how the release was discovered.

The suspected source(s) of the release is/are the former gasoline AST(s) at the site.

Excavation Report Worksheet for Petroleum Release Sites Page 3 April 2000 E. What was the volume of the release? (if known): Unknown gallons F. When did the release occur? (if known): Unknown G. Describe source of on-site drinking water. Municipal water is available at the site. PART IV: EXCAVATION INFORMATION A. Dimensions of UST excavation(s): Length 16' Width 12' Depth 9' Length 20' Width 16' Depth 10' Length 23' Width 15' Depth 10' B. Original tank backfill material (sand, gravel, etc.): Sand, silt C. Native soil type (clay, sand, etc.): Sand, silt, clay D. Quantity of contaminated soil removed for treatment (cubic yards): None [Note: If the volume removed is more than allowed in Fact Sheet 3.6 Excavation of Petroleum Contaminated Soil During Tank Removal, please document MPCA staff approval. E. Were new tanks and/or piping and dispensers installed? Tyes X no) If yes, what volume of contaminated soil was excavated to accommodate the installation of the new tanks and piping? F. If contaminated soil was removed to accommodate the installation of new tanks and/or piping, show your calculations for the amount of soil removal allowed using Table 6.2 in Fact Sheet 3.6 Excavation of Petroleum Contaminated Soil During Tank Removal. N/A

- G. Was ground water encountered or a suspected perched water layer or was there evidence of a seasonally high ground water table (i.e. mottling)? X yes no At what depth? Approximately nine (9) feet below grade.
- H. If ground water was not encountered during the excavation, what is the expected depth of ground water? N/A
- I. Additional investigation is necessary at sites that have visual or other evidence of contamination remaining in the suspected source area, with sandy or silty sand soil [Unified Soil Classification System/American Society for Testing Materials] and where the water table is within 25 feet of the ground surface. See fact sheet #3.6 Excavation of Petroleum Contaminated Soil, Part VI Additional Investigation. If a soil boring is necessary, describe the soil screening and analytical results. Attach the boring logs and laboratory results to this report.
- J. If no soil boring was performed, explain.

 Soil borings will be completed during Limited Site Investigation (LSI) activities at the site.

K. If ground water was encountered or if a soil boring was conducted, was there evidence of ground water contamination? (yes/no) Describe this evidence of contamination, e.g., free product (specify thickness), product sheen, ground water in contact with petroleum contaminated soil, water analytical results, etc. Note: If you observe free product, contact MPCA staff immediately, as outlined in fact sheet 3.3 Free Product: Evaluation and Recovery.

A petroleum product sheen was observed on ground water which seeped into the UST excavation where the gasoline UST's were formerly located. A ground water sample was collected for laboratory analysis during excavation activities on April 17, 2002. Laboratory analysis of the ground water sample identified petroleum impacts in the form of benzene, toluene, ethyl benzene and xylenes (BTEX) and total petroleum hydrocarbons (TPH) using Gasoline Range Organics (GRO) methodology.

L.	Was bedrock encountered in the excavation? yes X no At what depth?
M.	Were other unique conditions associated with this site? yes X no) If so, explain.

PART V: SAMPLING INFORMATION

A. Briefly describe the field screening methods used to distinguish contaminated from uncontaminated soil:

A photoionization detector (PID) was utilized to screen soil samples from the excavation areas for organic vapors. In addition, petroleum odor and visible staining were used to identify petroleum-impacted soil.

B. List soil vapor headspace analysis results collected during excavation of tanks, lines and dispensers. Indicate all sampling locations using sample codes (with sampling depths in parentheses), e.g. R-1 (2 feet), R-2 (10 feet), etc. "R" stands for "removed." Samples collected at different depths at the same location should be labeled R-1A (2 feet), R-1B (4 feet), R-1C (6 feet), etc. Similarly, if the sample was collected from the sidewall or bottom after excavation was complete, label it S-1 (for sidewall) or B-1 (for "bottom"). Indicate the depth of sample collection. Be sure the sample codes correspond with the site map in part VI, below.

Sample	Soil	Reading	Sample	Soil	Reading
Code	Type	ppm	Code	Type	ppm
S-1(3-4')	Sand	3.8	S-6(5-6')	Silt/Sand	789.0
S-2(3-4')	Sand	6.4	B-3(9-10')	Sand	110.0
S-3(3-4')	Sand	10.0	B-4(9-10')	Sand	264.0
S-4(3-4')	Sand	5.4	S-7(10-11')	Sand	795.0
B-1(8-9')	Sand	0.1	S-8(5-6')	Silt/Sand	122.0
B-2(8-9')	Sand	2.0	B-5(2-3')	Silt/Sand	0.6
S-5(0-2')	Silt/Sand	511.0	B-6(2-3')	Silt/Sand	1.3

- C. Was the "removed soil" placed back into the excavation basin? X yes no If no, please complete Part VIII: Soil Treatment Information section. If yes, a Limited Site Investigation is necessary (see fact sheet 3.19, Soil and Ground Water Investigations Performed During Remedial Investigations).
- D. Briefly describe the soil analytical sampling and handling procedures used:

Soil samples collected from beneath the gasoline UST's and gasoline pump dispensers were laboratory analyzed for benzene, toluene, ethyl benzene and xylenes (BTEX), methyl tertiary butyl ether (MTBE) and total petroleum hydrocarbons (TPH) using Gasoline Range Organics (GRO) methodology. The soil samples collected from beneath the diesel fuel UST and the diesel fuel pump dispensers were laboratory analyzed for BTEX and TPH as Diesel Range Organics (DRO). The soil samples were transferred into clean laboratory containers and preserved in the field and during transportation to the laboratory. The samples, accompanied by a chain-of-custody, were submitted to Northeast Technical Services, Inc. of Virginia, Minnesota for laboratory analysis.

E. List below all soil sample analytical results from bottom and side wall samples collected after excavation of tanks, lines and dispensers (i.e., soils left in place when excavation is complete). Code the samples with sampling depths in parentheses as follows: sidewall samples S-1 (8 feet), S-2 (4 feet), etc.; bottom samples B-1 (13 feet), B-2 (14 feet), stockpile samples SP-1, etc. Be sure the sample codes correspond to the site map required in part VI. Do not include analyses from the stockpiled soil.

Sample Code	GRO/ DRO	Benzene mg/kg	Ethyl- benzene	Toluene mg/kg	Xylene mg/kg	MTBE mg/kg	Lead mg/kg
			mg/kg	-0.050	-0.000	NIA	NT A
B-1(8-9')	NA/<10	< 0.050	< 0.050	< 0.050	< 0.060	· NA	NA
B-2(8-9')	NA/<10	< 0.050	< 0.050	< 0.050	< 0.060	NA	NA
S-1(10-11')	16,000/NA	17.000	340.000	880.000	1,400.000	200.000	NA
B-3(9-10')	<4/NA	< 0.050	< 0.050	< 0.050	< 0.060	< 0.050	NA
B-4(9-10')	140/NA	2.600	4.600	15.000	21.000	0.960	NA
B-5(2-3')	5.4/NA	< 0.050	< 0.050	0.230	< 0.060	< 0.050	NA
B-6(2-3')	11/NA	< 0.050	< 0.050	< 0.050	< 0.060	< 0.050	NA

Note: Attach copies of laboratory reports and chain of custody forms.

PART VI: FIGURES

Attach the following figures to this report:

- 1. Site location map.
- 2. Site map(s) drawn to scale illustrating the following:
 - a. Location (or former location) of all present and former tanks, piping, and dispensers;
 - b. Location of other structures (buildings, canopies, etc.);
 - c. Adjacent city, township, or county roadways;
 - d. Final extent and depth of excavation;
 - e. Location of soil screening samples (e.g. R-1), soil analytical samples (e.g., S-1 or B-1), and any soil borings (e.g., SB-1). Also, attach all boring logs.
 - f. North arrow, bar scale and map legend.
 - g. Provide location of any on-site water wells. If on-site water wells exist, please provide well logs and/or construction diagrams.
 - h. Locations of new tanks, piping and dispensers, if installed.

PART VII: SUMMARY

Briefly summarize evidence indicating whether additional investigation is necessary at the site, as discussed in parts VI and VII of fact sheet 3.6 Excavation of Petroleum Contaminated Soil During Tank Removal. If no further action is necessary, the MPCA staff will review this report following notification of soil treatment.

Based on field screening of soil samples collected during excavation activities at the site on April 17, 2002, petroleum impacts are present. In addition, laboratory analysis identified petroleum impacts in the ground water sample collected from the excavation basin beneath the former gasoline UST's located at the site. Petroleum impacted soil is in contact with ground water at the site. Therefore, Coteau recommends that a Limited Site Investigation (LSI) br completed at the site.

PART VIII: SOIL TREATMENT INFORMATION

- A. Soil treatment method used (thermal, land application, composting, other). If you choose "other" specify treatment method: N/A
- B. Location of treatment site/facility: N/A
- C. Date MPCA approved soil treatment (if thermal treatment was used after May 1, 1991, indicate date that the MPCA permitted thermal treatment facility agreed to accept soil):
- D. Identify the location of stockpiled contaminated soil: N/A

Excavation Report Worksheet for Petroleum Release Sites Page 7 April 2000

CONSULTANT (OR OTHER) PREPARING THIS REPORT PART IX:

By signing this document, I/we acknowledge that we are submitting this document on behalf of and as agents of the responsible person or volunteer for this leak site. I/we acknowledge that if information in this document is inaccurate or incomplete, it will delay the completion of remediation and may harm the environment and may result in reduction of reimbursement awards. In addition, I/we acknowledge on behalf of the responsible person or volunteer for this leak site that if this document is determined to contain a false material statement, representation, or certification, or if it omits material information, the responsible person or volunteer may be found to be in violation of Minn. Stat. § 115.075 (1994) or Minn. 7000.0300 (Duty of Candor), and that the responsible person or volunteer may be liable for civil penalties.

Name and Title:

Date signed:

Andrew M. Schmidt, EIT Environmental Engineer

Cinter my Schmilt

8-19-03

Company and mailing address: Coteau Environmental

728 Janes Circle Drive SW Alexandria, Minnesota 56308

Telephone: (320) 846-4668

Fax: (320) 846-4668

If additional investigation is not necessary, please mail this form and all necessary attachments to the MPCA project manager. If additional investigation is necessary, include this form as an appendix to Fact Sheet 3.24 Investigation Report Form. MPCA staff will not review excavation reports indicating a limited site investigation is necessary unless the limited site investigation has been completed.

Web pages and phone numbers

MPCA staff MPCA toll free LUST web page MPCA Infor. Request MPCA VPIC program PetroFund Web Page PetroFund Phone

State Duty Officer


http://data.pca.state.mn.us/pca/emplsearch.html 1-800-657-3864.


http://www.pca.state.mn.us/programs/lustap.hunl http://www.pca.state.mn.us/about/inforequest.html http://www.pca.state.mn.us/programs/vpic p.l.iml http://www.commerce.state.mn.us/mainpf.htm


651-297-11119, or 1-800-638-0418 651-649-5451 or 1-800-422-0798


Upon request, this document can be made available in other formats, including Braille, large print and audio tape. TTY users call 651/282-5332 or 1-800-657-3864 (voice/TTY).

Printed on recycled paper containing at least 10 percent fibers from paper recycled by consumers.









<

APPENDIX B LABORATORY ANALYTICAL REPORTS



MDH Laboratory # 027-137-157

Sample ID: | S021681347 | Project #: | 5828.05

Client: Coteau Environmental

Study: Consultant
Descript: KC Kwik Stop
Location: B-1 (9-12)

Sampler: Client Status: Normal Type: Grab Matrix: Soil

NTS COC No: 19246 Sampled: 6/13/2002 Completed: 07/01/2002

Notes:

Analyte	Analysis Date	Result	Units	RL.	Method
GRO, Soil	6/28/2002	4600	mg/Kg	4	WI Method
Benzene, Soil	6/28/2002	19000	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	6/28/2002	140000	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	6/28/2002	94000	ug/Kg	50	SW 846 8021B
Moisture	6/18/2002	18	%	0.1	EPA 160.3
Toluene, Soil	6/28/2002	300000	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	6/28/2002	610000	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.

Northeast Technical Services, Inc. makes no warranty except that the analysis has been made upon the samples received in accordance with generally accepted testing laboratory principles and practices. The results of the analysis may not be characteristi of the whole from which the sample was taken. This warranty is in lieu of all other warranties either expressed or implied.

Friday, July 05, 2002

NTS Laboratory Data Base System

Page 1 of 5



MDH Laboratory # 027-137-157

Sample ID: | S021681355 | Project #: | 5828.05

Client: Coteau Environmental

Study: Consultant
Descript: KC Kwik Stop
Location: B-2 (10-12')

Sampler: Client

Type: Grab Matrix: Soil

Status: Normal NTS COC No: 19246

Sampled: 6/13/2002 Completed: 07/01/2002

Notes:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	6/28/2002	4	mg/Kg	4	WI Method
Benzene, Soil	6/28/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	6/28/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	6/28/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	6/18/2002	13	%	0.1	EPA 160.3
Toluene, Soil	6/28/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	6/28/2002	380	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.

Northeast Technical Services, Inc. makes no warranty except that the analysis has been made upon the samples received in accordance with generally accepted testing laboratory principles and practices. The results of the analysis may not be characteristi of the whole from which the sample was taken. This warranty is in lieu of all other warranties either expressed or implied.

Friday, July 05, 2002

NTS Laboratory Data Base System

Page 2 of 5



MDH Laboratory # 027-137-157

Sample ID: S021681356 Project #: 5828.05

Coteau Environmental Client:

Consultant Study: KC Kwik Stop Descript: B-3 (9-12) Location:

Sampler: Client

Status: Normal

Type: Grab Matrix: Soil

NTS COC No: 19246

Sampled: 6/13/2002 Completed: 07/01/2002

Notes:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	6/28/2002	9100	mg/Kg	4	WI Method
Benzene, Soil	6/28/2002	23000	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	6/28/2002	320000	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	6/28/2002	67000	ug/Kg	50	SW 846 8021B
Moisture	6/18/2002	28	%	0.1	EPA 160.3
Toluene, Soil	6/28/2002	660000	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	6/28/2002	2100000	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.

Northeast Technical Services, Inc. makes no warranty except that the analysis has been made upon the samples received in accordance with generally accepted testing laboratory principles and practices. The results of the analysis may not be characteristi of the whole from which the sample was taken. This warranty is in lieu of all other warranties either expressed or implied.

Friday, July 05, 2002

NTS Laboratory Data Base System

Page 3 of 5



MDH Laboratory # 027-137-157

Type: Grab

Matrix: Soil

S021681357 | Project #: | 5828.05 Sample ID:

Consultant

B-3 (15-18)

KC Kwik Stop

Coteau Environmental

Sampler: Client Status: Normal NTS COC No: 19246

Sampled: 6/13/2002 Completed: 07/05/2002

Notes:

Client:

Study:

Descript:

Location:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	6/30/2002	490	mg/Kg	4	WI Method
Benzene, Soil	6/30/2002	< 1000	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	6/30/2002	13000	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	6/30/2002	8000	ug/Kg	50	SW 846 8021B
Moisture	6/18/2002	14	%	0.1	EPA 160.3
Toluene, Soil	6/30/2002	21000	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	6/30/2002	65000	ug/Kg	60	SW 846 8021B

Approved By: Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

Type: Grab

Matrix: Soil

S02168135A | Project #: | 5828.05 Sample ID:

Coteau Environmental

Consultant Study: KC Kwik Stop Descript:

B-4 (9-11) Location:

Sampler: Client Status: Normal

NTS COC No: 19246 Sampled: 6/13/2002 Completed: 07/01/2002

Notes:	
--------	--

Client:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	6/28/2002	5900	mg/Kg	4	WI Method
Benzene, Soil	6/28/2002	29000	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	6/28/2002	180000	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	6/28/2002	150000	ug/Kg	50	SW 846 8021B
Moisture	6/18/2002	17	%	0.1	EPA 160.3
Toluene, Soil	6/28/2002	590000	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	6/28/2002	800000	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.

Sample Name: S02168135A Cotea Data File D:\HPCHEM\4\DATA\062702\041F4201.D 42 6/28/02 1:56:25 PM Seq. Injection Date 41 Vial: : S02168135A Cotea Sample Name 1 Inj: : dcd Acq. Operator Inj Volume : Manually : C:\HPCHEM\1\METHODS\!GC4ACQ.M Acq. Method : 4/25/01 1:43:18 PM by dcd Last changed Analysis Method : D:\HPCHEM\4\METHODS\05242SLB.M : 6/28/02 10:58:34 AM by dcd Last changed : 6/28 FID1 A, (062702\041F4201.D) 100:1 counts 400000 300000 200000 100000 12 14 16 6 10) 2 FID2 B, (062702\041F4201.D) counts 1 7000000 6000000 5000000 4000000 3000000 2000000 1000000 0 16 12 8 10

Sample Name: S021681356 Cotea Data File D:\HPCHEM\4\DATA\062702\039F4001.D : 6/28/02 12:33:06 PM Injection Date 39 Vial : S021681356 Cotea Sample Name Inj: 1 : dcd Acq. Operator Inj Volume : Manually : C:\HPCHEM\1\METHODS\!GC4ACQ.M Acq. Method : 4/25/01 1:43:18 PM by dcd Last changed Analysis Method : D:\HPCHEM\4\METHODS\05242SLB.M : 6/28/02 10:58:34 AM by dcd Last changed FID1 A, (062702\039F4001.D) 1:001 counts] 6 375 -800000 -700000 -600000 500000 -400000 300000 200000 100000 14 16 10 8 6 FID2 B, (062702\039F4001.D) counts -10000000 8000000 6000000 4000000 157 - BrFi Benzene Sun Ħ 2000000 0 16 6

Sample Name: S0216 Data File D:\HPCHEM\4\DATA\062702\035F3501.D 35 Injection Date 6/28/02 9:21:40 AM : S021681355 Cotea Vial 35 Sample Name Inj 1 Acq. Operator : dcd Inj Volume : Manu Acq. Method C:\HPCHEM\1\METHODS\!GC4ACQ.M : 4/25/01 1:43:18 PM by dcd Last changed Analysis Method : D:\HPCHEM\4\METHODS\05242SLB.M 5 100ml 6/28/02 10:58:34 AM by dcd FID1 A, (062702\035F3501.D) counts 120000 100000 80000 60000 40000 20000 -) 2 FID2 B, (062702\035F3501.D) 10 16 _mhi counts 1000000 800000 600000 400000 200000 6 8 10 12 16 milif

ta File D:\HPCHEM\4\DATA\062702\036F3601.D Maple Mine: S0216 Injection Date 36 : S021681357 Cotea Sample Name 36 Acq. Operator : dcd 1 Manua C:\HPCHEM\1\METHODS\!GC4ACQ.N Acq. Method : 4/25/01 1:43:18 PM by dcd Last changed Analysis Method : D:\HPCHEM\4\METHODS\05242SLB. - 100ml : 6/28/02 10:58:34 AM by dcd Last changed counts 3500000 -3000000 -2500000 -2000000 -1500000 1000000 500000 8 6) 2 FID2 B, (062702\036F3601.D) counts 25000000 20000000 Ethyl Benzene 15000000 10000000 5000000 8 Ó

Northeast Technical Services, Inc. 315 Chesnut Street
P.O. Box 1142
Virginia, MN 55792
Phone: 218-741-4290
Fax: 218-741-4291

it Information

Chain of Custody Record

٥

Date Due:

coc# 19346 Page_

enha/	Colau Enrivenmental	ntal			\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	
Ct Person: Nate Hunke	3930 Sunnybrook Drive NW	rive NW		Y 5.	<i> </i>	
VE NW	Alexandria, MN Sb308	6308		W 738	<i></i>	
(320) 846-4668	Invoice to: Address:	ntel		SP. 1/3 PZ LUI		
(405) 882-4152	Same as above			\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	/ / /	
K-C Kuik Shp-Brooten, MN				\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		
Laboratory ID Sample Description		Matrix			Analysis Required	Comments
Ġ	pinbri suni	Solid Other	Grab Comp			
12 (4-12)	-	×		× ×		
1355 8-2 (10-12)		×		×		
1356 B-3 (9-12)		>		+		
1357 8-3 (15-18)		×		··		
135A B-4 (9-11)		×		< ×		
d By: Date 6-13-02 Received By:	Received By:	Date	Received for	Laboratory By:	Date 17.03	NIS Project # S28.0 C
		Time	Ž	大きなり	Time 30	Misc. Lab Information
Ly Chuill Time 4:00 Pm	Received By:	Date Time	Temperature on Arrival	on Arrival	Degrae Celeine	
					CH10140 CA1940	



MDH Laboratory # 027-137-157

S022251617 Project #: | 5828.10 Sample ID:

Coteau Environmental

Consultant Study: KC Kwik Stop Descript:

B-5 (8-10) Location:

Sampler: Client

Type: Grab Matrix: Soil

Status: Normal NTS COC No: 20472

Sampled: 8/6/2002 4:50 PM

Completed: 08/27/2002

Notes:

Client:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	8/15/2002	<4	mg/Kg	4	WI Method
Benzenc, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	8/13/2002	11	%	0.1	EPA 160.3
Toluene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	8/15/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

Sample ID: | S022251627 | Project #: | 5828.10

Coteau Environmental

Client: Coteau Enviror
Study: Consultant
Descript: KC Kwik Stop
Location: B-5(17-19)

Sampler: Client Status: Normal Type: Grab Matrix: Soil

NTS COC No: 20472

Sampled: 8/6/2002 5:45 PM

Completed: 08/27/2002

Notes:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	8/15/2002	17	mg/Kg	4	WI Method
Benzene, Soil	8/15/2002	260	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	8/15/2002	410	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	8/15/2002	300	ug/Kg	50	SW 846 8021B
Moisture	8/13/2002	16	%	0.1	EPA 160.3
Toluene, Soil	8/15/2002	110	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	8/15/2002	2100	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

S022251630 Sample ID:

Project #: 5828.10

Sampler: Client

Type: Grab

Client:

Coteau Environmental

Study:

Matrix: Soil

Consultant

Status: Normal NTS COC No: 20472

Descript:

KC Kwik Stop

Sampled: 8/6/2002 9:45 AM

B-6(2-4)Location:

Completed: 08/27/2002

Notes:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	8/15/2002	<4	mg/Kg	4	WI Method
Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	8/13/2002	11	%	0.1	EPA 160.3
Toluene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	8/15/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

Sample ID: S022251631 Project #: 5828.10

Client: Coteau Environmental

Study: Consultant
Descript: KC Kwik Stop

Location: B-6(8-10)

Sampler: Client

Type: Grab

Status: Normal

Matrix: Soil

NTS COC No: 20472

Sampled: 8/6/2002 9:45 AM

Completed: 08/27/2002

Notes:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	8/15/2002	<4	mg/Kg	4	WI Method
Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	8/13/2002	13	%	0.1	EPA 160.3
Toluene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	8/15/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

Sample ID: S022251632 Project #: 5828.10

Coteau Environmental

Study: Consultant
Descript: KC Kwik Stop

Location: B-7(8-10)

Sampler: Client

Type: Grab Matrix: Soil

Status: Normal NTS COC No: 20472

Sampled: 8/6/2002 12:10 PM

Completed: 08/27/2002

Notes:

Client:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	8/15/2002	<4	mg/Kg	4	WI Method
Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846'8021B
Methyl tert-butyl ether	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	8/13/2002	14	%	0.1	EPA 160.3
Toluene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	8/15/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By:

 \mathcal{Y}

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

Sample ID: S022251633 Project #: 5828.10

Client: Coteau Environmental

Study: Consultant
Descript: KC Kwik Stop

Location: B-7(12-14)

Sampler: Client

Type: Grab Matrix: Soil

Status: Normal NTS COC No: 20472

Sampled: 8/6/2002 12:45 PM

Completed: 08/27/2002

Notes:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	8/15/2002	<4	mg/Kg	4	WI Method
Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	8/13/2002	16	%	0.1	EPA 160.3
Toluene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	8/15/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

S022251634 Project #: 5828.10 Sample ID:

Coteau Environmental

Consultant Study: KC Kwik Stop **Descript:**

Location: B-8(8-10) Sampler: Client

Type: Grab Matrix: Soil Status: Normal

NTS COC No: 20472

Sampled: 8/6/2002 2:50 PM

Completed: 08/27/2002

Notes:

Client:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	8/15/2002	<4	mg/Kg	4	WI Method
Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	8/15/2002	90	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	8/13/2002	7.3	%	0.1	EPA 160.3
Toluene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	8/15/2002	270	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

Sample ID: S022251636 Project #: 5828.10

Coteau Environmental

Client: Coteau Environme Study: Consultant Descript: KC Kwik Stop

Location: B-8(13-15)

Sampler: Client

Type: Grab Matrix: Soil

Status: Normal NTS COC No: 20472

Sampled: 8/6/2002 3:45 PM

Completed: 08/27/2002

Notes:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	8/15/2002	<4	mg/Kg	4	WI Method
Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	8/13/2002	18	%	0.1	EPA 160.3
Toluene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	8/15/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



Notes:

"Solutions for Technical Concerns"

MDH Laboratory # 027-137-157

S02225163A Project #: 5828.10 Sample ID:

Coteau Environmental Client:

Consultant Study: KC Kwik Stop Descript:

B-9(8-10) Location:

Sampler: Client

Type: Grab Status: Normal Matrix: Soil

NTS COC No: 20472

Sampled: 8/6/2002 5:45 PM

Completed: 08/27/2002

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	8/15/2002	<4	mg/Kg	4	WI Method
Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	8/13/2002	18	%	0.1	EPA 160.3
Toluene, Soil	8/15/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	8/15/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.

Northeast Technical Services, Inc. makes no warranty except that the analysis has been made upon the samples received in accordance with generally accepted testing laboratory principles and practices The results of the analysis may not be characteristi of the whole from which the sample was taken. This warranty is in lieu of all other warranties either expressed or implied

Tuneday August 27 2002

Page 9 of 9

Northeast Technical Services, Inc. 315 Chesnut Street
P.O. Box 1142
Virginia, MN 55792
Phone: 218-741-4290
Fax: 218-741-4291

Chain of Custody Record

COC# 20472_ Page_

Date Due:

ation		Report to:									-	1			
steau E	Teau Environmental	Address:	COTEAU ENVIOUNEMAI	# Ent	יועה וו	Jalia!						<u></u>			
NATE	,, \	,	STSC SUNNYSISOKULIK	0000	00/0/	バラン	3			<u></u>	<u></u>	<u></u>	<u></u>	_	
1930 SW.	1930 Summy Snow Dr. N.W		-ce candia, """ 56308	ار نهر	,	56308				C (3)3	\ \ \	\ \ \		
12 xandri	Yexardria, MN 56308	Invoice to:		7					< \	//-// PS/	\ `;``e	<u></u>	_		
30-346-4668		Address:							(3)	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		<u></u>	<u></u>		
7517-888-50	-4152								[5]	る対グ	1		_		
1110n: 15C'S	KC'S KWIK STOD							,		/ / /	_				
In Tatory ID	Sample Description		Collection	tion	N. S. bung. I	Matrix Solid Other	Type	Filtered		Analy sis Required	equired			Comments	
-////	12-5/2-10 010-97	ر ر	27.7.2	5	-				7	7					
19167		2	3.000	320	-				7	,		- -			
1627	0-565-019/61-8175-8	36.0	Sht1 20-9-8	Shti					1	7				•	
1630	1630 B-6(2-4) PID- 61,0		8-7-02 10945	2460					7	+					
1631	8-6 (3-10) AR-\$30.0	3.0	S+50 20-E-8	5460					7,	1					
1632	3-7 (8-10) P13- 3.7	Ļ	6-7-02 1213	012					7	7					
1633	6.63 - GIRCHI-11) f-8 85.31		5-21 22-6-8	5421					/	7					
1634	8-8 (8-10) 913-11,0	0.11	3-7-4-5 HES	CS hi					7	1					
1636	1636 8-8 (13-15) 813-814	78.	3-7-04 1545	ShSi					1.	1-1-1					
1634	1634 8-9(8-10) 2113-4.0		SHE1 20- E-8	1745					7	1					
C		Received By:	By:		Date	ite	Receiv	ed for La	Received for Laboratory By:	١	\\ \frac{1}{2}	12. Ju	NFS Project	VIS Project # 59 28. 1	b
7	Time 1730	,			ļĒ.	Time		A A	N. J.	25 X	IX.	3	Misc. Lab Information	ormation	
) ::	Date	Received By:	By:		Date	116	Lemp	remperature on Arri	Arri Ai	, ,	,				
	Fime				: <u>:</u>	l ime		On Icc	***************************************	7,7		1. Juces 1. 103			



MDH Laboratory # 027-137-157

Sample ID: Project #: 5828.10 S021121045

Sampler: Client

Type: Grab

Client:

Status: Normal

Matrix: Solid

Coteau Environmental

Study:

Consultant

NTS COC No: 17760

Descript: Location: KC Kwik Stop

Sampled: 4/17/2002 11:00 AM

Completed: 05/06/2002

Notes:

DRO Extraction Date: 04/25/02

B-1 (8-9')

Analyte	Analysis Date	Result	Units	RL	Method
DRO, Soil	5/1/2002	< 10	mg/Kg	10	WI Method
Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	8.6	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By: Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

Sample ID: | S021121051 | Project #: | 5828.10

Coteau Environmental

Study: Consultant
Descript: KC Kwik Stop

Location: N. Sidewall (10-11)

Sampler: Client

Type: Grab Matrix: Solid

Status: Normal NTS COC No: 17760

Sampled: 4/17/2002 12:00 PM

Completed: 05/06/2002

Notes:

Client:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	5/3/2002	16000	mg/Kg	4	WI Method
Benzene, Soil	5/3/2002	17000	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	340000	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	5/3/2002	200000	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	16	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	880000	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	1400000	ug/Kg	60	SW 846 8021B

Approved By:

Project Mánager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

Sample ID: Project #: 5828.10 S021121055

Sampler: Client

Type: Grab

Client:

Coteau Environmental

Status: Normal

Matrix: Solid

Study:

Consultant

NTS COC No: 17760

Descript: Location: KC Kwik Stop B-3 (9-10')

Sampled: 4/17/2002 1:00 PM

Completed: 05/06/2002

Notes:

Closing QC %recovery for BTEX ranged from 68-80%.

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	5/3/2002	< 4	mg/Kg	4	WI Method
Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	16	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By: Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

Project #: 5828.10 Sample ID: S021121056

Coteau Environmental

Consultant Study: Descript: KC Kwik Stop

B-4 (9-10') Location:

Sampler: Client

Type: Grab Matrix: Solid

Status: Normal NTS COC No: 17760

Sampled: 4/17/2002 2:15 PM

Completed: 05/06/2002

N	o	te	2	•

Client:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	5/3/2002	140	mg/Kg	4	WI Method
Benzene, Soil	5/3/2002	2600	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	4600	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	5/3/2002	960	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	16	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	15000	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	21000	ug/Kg	60	SW 846 8021B

Approved By: Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

S021121057 | Project #: | 5828.10 Sample ID:

Coteau Environmental

Study: Descript: KC Kwik Stop Location:

Consultant West P.I. (2-3') Sampler: Client Status: Normal

Type: Grab Matrix: Solid

NTS COC No: 17760

Sampled: 4/17/2002 2:45 PM

Completed: 05/06/2002

Notes:

Client:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	5/3/2002	5.4	mg/Kg	4	WI Method
Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	19	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	230	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

S02112105A Project #: 5828.10 Sample ID:

Sampler: Client

Type: Grab

Client:

Coteau Environmental

Study:

Consultant

Status: Normal NTS COC No: 17760

Matrix: Solid

Descript:

KC Kwik Stop

Sampled: 4/17/2002 2:30 PM

Location:

East P.I. (2-3')

Completed: 05/06/2002

Notes:

Higher hydrocarbons present.

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	5/3/2002	11	mg/Kg	4	WI Method
Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	15	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By: Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.



MDH Laboratory # 027-137-157

S02112105B | Project #: | 5828.10 Sample ID:

Sampler: Client Status: Normal Type: Grab

Coteau Environmental Client:

Matrix: Solid

Study:

Consultant KC Kwik Stop NTS COC No: 17760

Descript: Location:

B-2 (8-9')

Sampled: 4/17/2002 3:00 PM

Completed: 05/06/2002

Notes:

DRO Extraction Date: 04/25/02

Analyte	Analysis Date	Result	Units	RL	Method
DRO, Soil	5/3/2002	< 10	mg/Kg	10	WI Method
Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	4.3	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By: Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.


Sample Name: S02112105/

Seq. Line 5/3/02 11:46:35 AM 49 Vial:

Injection Date : S021121057 1 Inj : Sample Name

Inj Volume : Manually : dcd Acq. Operator

: C:\HPCHEM\1\METHODS\!GC4ACQ.M Acq. Method



Sample Name: SUZIIZIUDO


Seq. Line 5/3/02 9:34:29 AM 45 Vial

Injection Date : S021121056 1 Inj : Sample Name : dcd

Inj Volume : Manually Acq. Operator

: C:\HPCHEM\1\METHODS\!GC4ACQ.M Acq. Method : 4/25/01 1:43:18 PM by dcd

Analysis Method : D:\HPCHEM\4\METHODS\050102SL.M Last changed



Northeast Technical Services, Inc. 315 Chesmu Street
P.O. Box 1142
Virginia, MN 55792
Phone: 218-741-4290
Fax: 218-741-4291

Chain of Custody Record

Page

of

Date Due: 100 # 5828.10

Client Information Rep	Report to:			
	Cotean Environmental			
VIronmental	Address: 3930 SUNNYBrook Dr. NO			
Whook Dr. NW	Hexandria MN 2028			
	Invoice to:		/ / / / / / / / / / / / / / / / / / /	
	Address: - Same as alaye		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
Fax: 605 882-4152				
Project Information: K. 1.1 Sto 2		7		
Lab Use Only	Collection	Type Filtered	Analysis Required Comments	
Laboratory ID Sample Description	Date Time Liquid Solld Other	Grab Comp		
(18-6, 1-8) B-1 (8-6,)	4-17 (20/1 X		X X X	
	X 0001 F1-4		×	
	4-17 13co X		× ×	
	X SIHI E1-4		× ×	
	4-17 1430 X		×	
	N-17 1415 X		× ×	
1058 13-2 (8-7')	4-17 1500 X		X	
Sampled By: Date Re	Received By: Date	Received for Laboratory By:	iboratory By: D22-49-03 NTS Project #	
TIme	Time Time	1 (ACC)	Misc. Lab Information	

Degrees Celsius

On Ice

Time

Time 1500



April 23, 2002

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

4/17/02

Date Received:

4/19/02

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

Liquid

Method:

Units:

8021

ug/L

Analyst:

MS

Detection Limit:

See Below

Date of Analysis:

See Below

Lab Sample ID:

021593-01

l

Client Sample ID.

Basin

Detection Limit (ug/L)

2.5

Date Analyzed:

4/20/02

Benzene Toluene

110.0 479.0

Ethylbenzene

185.0

Total Xylene

842.0

% Surrogate Recovery

130.0

Laboratory Manager: Bassam Yousset

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489

Email: summitenvironmental@msn.com





April 23, 2002

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW Alexandria, MN 56308

Date Collected:

4/17/02

Date Received:

4/19/02

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

Liquid

Method:

WI Mod.

Units:

ug/l

Analyst:

Detection Limit:

MS See Below

Date of Analysis:

See Below

Lab Sample ID.

021593-01

Client Sample ID:

Basin

Detection Limit (ug/l)

100.0

Date Analyzed:

4/20/02

TPH-GRO

6707.0

% Surrogate Recovery

130.0

Laboratory Manager. Bassam Youssef

SUMMIT ENVIRONMENTAL TECHNOLOGIES, INC. 595 EAST TALLMADGE AVENUE AKRON, OHIO 44310

CHAIN OF CUSTODY A2LA CERTIFICATION #: 0724-01



TEL: 330/253-8211; FAX: 330/253-4489

56308 Alexandrica N -- PHONE # 310 846-4668 FAX # 605 882 4153 AMPLED BY:---CLIENT NAME: Cotequ EnvironMerral ADDRESS 3930 SUNIMPROOK Dr. -- PROJECT LOCATION -- Brooten PROJECT NAME: K-C KWIK STOP CONTACT PERSON: KUZE

[Τ	Τ	Τ	1	Τ	Τ	Τ	Τ	Τ	Т	Γ	Γ	1	T-	T-	<u> </u>	ļ	<u> </u>	Γ	Γ	<u> </u>
OTHERS	-																				
TCLP PEST/HERB																					
TCLP																					
TCLP										;	5										
TCLP										7	75.0										
TPH 418.1					-	٠.				1	1										
DRO 8015M										1											
GRO 8015M	7																				
BTEX 8020	7																				
DATE	4-13																				
TIME																					
MEDIA	Water 1300																				
SAMPLE ID# MEDIA TIME DATE	We Risin	>																			
#																					

š.
45
י ס
=
-
t)
\simeq
\sim
~
20
22
Z
_
_
7
۹,
5
\mathcal{O}
ы
E.
$\overline{\mathcal{L}}$
•,

RELINQUISHED BY: | | |

RECEIVED BY:

Or 15 DATE: 4-19-02

3Y:

DATE



Solutions for Technical Concerns"

MDH Laboratory # 027-137-157

Sample ID: | S021121045 | Project #: | 5828.10

Sampler: Client

Type: Grab

Client:

Coteau Environmental

Status: Normal

Study:

NTS COC No: 17760

Matrix: Solid

Consultant Descript: KC Kwik Stop

B-1 (8-9') Location:

Sampled: 4/17/2002 11:00 AM

Completed: 05/06/2002

Notes:

DRO Extraction Date: 04/25/02

Analyte	Analysis Date	Result	Units	RL	Method
DRO, Soil	5/1/2002	< 10	mg/Kg	10	WI Method
Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	8.6	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By: Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.

Northeast Technical Services, inc. makes no warranty except that the analysis has been made upon the samples received in accordance with generally accepted testing laboratory principles and practices. The results of the analysis may not be characteristi of the whole from which the sample was taken. This warranty is in lieu of all other warranties either expressed or implied.



'Solutions for Technical Concerns"

MDH Laboratory # 027-137-157

Sample ID:

S021121051 Project #: 5828.10

Sampler: Client

Type: Grab

Client:

Coteau Environmental

Matrix: Solid

Study:

Consultant

Status: Normal NTS COC No: 17760

Descript:

KC Kwik Stop

Sampled: 4/17/2002 12:00 PM

N. Sidewall (10-11) Location:

Completed: 05/06/2002

Notes:


Analyte	Analysis Date	Result	Units	RL	Method
	5/3/2002	16000	mg/Kg	4	WI Method
GRO, Soil Benzene, Soil	5/3/2002	17000	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	340000	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	5/3/2002	200000	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	16	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	880000	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	1400000	ug/Kg	60	SW 846 8021B

Approved By:

Project Mánager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health

Northeast Technical Services, inc. makes no warranty except that the analysis has been made upon the samples received in accordance with generally accepted testing laboratory principles and practices. The results of the analysis may not be characteristi of the whole from which the sample was taken. This warranty is in lieu of all other warranties either expressed or implied.



,		
	•	



'Solutions for Technical Concerns"

MDH Laboratory # 027-137-157

S021121055 | Project #: 5828.10 Sample ID:

Sampler: Client

Type: Grab

Client:

Coteau Environmental

Status: Normal

Matrix: Solid

Study:

Consultant

NTS COC No: 17760

Descript: Location:

KC Kwik Stop B-3 (9-10')

Sampled: 4/17/2002 1:00 PM

Completed: 05/06/2002

Notes:

Closing QC %recovery for BTEX ranged from 68-80%.

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	5/3/2002	< 4	mg/Kg	4	WI Method
Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	16	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	< 60	ug/Kg	60	SW 846 8021B

	ua, au caigna cas na sao ait ao agus na denne e dha dhubhan, a ear deann ann dearn s saon ann an dheann agus a	
Approved By:	817	
	Project Manager:	

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.

Northeast Technical Services, Inc. makes no warranty except that the analysis has been made upon the samples received in accordance with generally accepted testing laboratory principles and practices. The results of the analysis may not be characteristi of the whole from which the sample was taken. This warranty is in lieu of all other warranties either expressed or implied.

Monday, May 06, 2002

NTS Laboratory Data Base System

Page 3 of 7



"Solutions for Technical Concerns"

MDH Laboratory # 027-137-157

Sample ID: | S021121056 | Project #: 5828.10

Coteau Environmental

Study: Consultant
Descript: KC Kwik Stop

Location: B-4 (9-10')

Sampler: Client

Type: Grab Matrix: Solid

Status: Normal NTS COC No: 17760

Sampled: 4/17/2002 2:15 PM

Completed: 05/06/2002

Notes:

Client:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	5/3/2002	140	mg/Kg	4	WI Method
Benzene, Soil	5/3/2002	2600	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	4600	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	5/3/2002	960	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	16	%	0.1	EPA 160.3
Foluene, Soil	5/3/2002	15000	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	21000	ug/Kg	60	SW 846 8021B

Approved By:	<u> </u>
	Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.

Northeast Technical Services, Inc. makes no warranty except that the analysis has been made upon the samples received in accordance with generally accepted testing laboratory principles and practices. The results of the analysis may not be characteristi of the whole from which the sample was taken. This warranty is in lieu of all other warranties either expressed or implied.



Solutions for Technical Concerns"

MDH Laboratory # 027-137-157

S021121057 Project #: 5828.10 Sample ID:

Sampler: Client

Type: Grab

Client:

Coteau Environmental

Status: Normal

Matrix: Solid

Study:

Consultant KC Kwik Stop NTS COC No: 17760 Sampled: 4/17/2002 2:45 PM

Descript: West P.I. (2-3') Location:

Completed: 05/06/2002

Notes:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	5/3/2002	5.4	mg/Kg	4	WI Method
Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	19	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	230	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	< 60	ug/Kg	60	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.

Northeast Technical Services, Inc. makes no warranty except that the analysis has been made upon the samples received in accordance with generally accepted testing laboratory principles and practices. The results of the analysis may not be characteristi of the whole from which the sample was taken. This warranty is in lieu of all other warranties either expressed or implied.



"Solutions for Technical Concerns"

MDH Laboratory # 027-137-157

Project #: 5828.10 Sample ID: S02112105A

Sampler: Client

Type: Grab

Client:

Coteau Environmental

Status: Normal

Matrix: Solid

Study:

Consultant

NTS COC No: 17760

Descript: Location:

KC Kwik Stop East P.I. (2-3') Sampled: 4/17/2002 2:30 PM

Completed: 05/06/2002

Notes:

Higher hydrocarbons present.

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	5/3/2002	11	mg/Kg	4	WI Method
Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Methyl tert-butyl ether	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	15	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	< 60	ug/Kg	60	SW 846 8021B

	P.45 M 2 1021 M 2014 AT AT AT AT AT A ATT A ATT AND ATTACK OF A ATT AND ATTACK	 	
Approved By:	817		
	Project Manager:		

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.

Northeast Technical Services, Inc. makes no warranty except that the analysis has been made upon the samples received in accordance with generally accepted testing laboratory principles and practices. The results of the analysis may not be characteristi of the whole from which the sample was taken. This warranty is in lieu of all other warranties either expressed or implied.



"Solutions for Technical Concerns"

MDH Laboratory # 027-137-157

Sample ID: S02112105B | Project #: | 5828.10

Client: Coteau Environmental

Study: Consultant KC Kwik Stop Descript: B-2 (8-9') Location:

Sampler: Client

Type: Grab Matrix: Solid

Status: Normal NTS COC No: 17760

Sampled: 4/17/2002 3:00 PM Completed: 05/06/2002

Notes:

DRO Extraction Date: 04/25/02

Analyte	Analysis Date	Result	Units	RL	Method
DRO, Soil	5/3/2002	< 10	mg/Kg	10	WI Method
Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Ethyl Benzene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Moisture	4/25/2002	4.3	%	0.1	EPA 160.3
Toluene, Soil	5/3/2002	< 50	ug/Kg	50	SW 846 8021B
Total Xylenes, Soil	5/3/2002	< 60	ug/Kg	60	SW 846 8021B

STATE PARTIES W. S. PARTIE PARTIES PARTIES AND STATE OF THE PARTIES OF THE PARTIE		
P12	The final of the first the delimination when a contract delimination continued to the property of a day to the	* * * * * * * * * * * * * * * * * * * *
ect Manager:		
	<u> </u>	ect Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.

Northeast Technical Services, Inc. makes no warranty except that the analysis has been made upon the samples received in accordance with generally accepted testing laboratory principles and practices. The results of the analysis may not be characteristi of the whole from which the sample was taken. This warranty is in lieu of all other warranties either expressed or implied.

315 Chesinut Street
315 Chesinut Street
P.O. Box 1142
Virginia, MN 55792
Phone: 218-741-4290
Fax. 218-741-4291

Chain of Custody Record

Ş	山
	H
	#20°
	•

7

Page

ne:			Comments									NTS Project #	Misc. Lab Information	:	
Date Due:	1 / 1 / 1 / 1 / 1 / 1 / 1 / 1 / 1 / 1 /	TO WINDS	Analysis Required										M 00:72 M	Degrees Celsius	-
707	Disture	W PISS	Pflured Analysis	* × ×	X	×	×	×	×	X X X		Received for Laboratory By:	phapely		
	J. 110	808	Type											Тефре	
	Reportio: Coteau Environmental Address: 3930 Sunnybrook Pr. Na	Alexandria MU36308 ". Same as abave			1,200 Y	1300	4-17 IHIS X	7 1430 X	H-17 IMB X	7 1500 X		Date	Time	Date Time	
	Report to: Cofeau Address: 3930	Invoke te		nton Drie	t1-# (11-91)			-3) 4-17		1) 4-17		Received By:	- doll	1 1	1
P.O. Box 1142 Virginia, MN 55792 Phone: 218-741-4290 Fax. 218-741-4291	vironmental	3930 Sunybook Dr. N. Herandria MN 56308 320 846-4668 605 882-4152	570,2	3-1 (8-9')	1 Sidewall (10-11)	13-3 (9-10)	B-4 (6-16')	East P.I (2-3)	1057 West P.[(2-3)	13-2 (8-7)		Date	Time	1 Date 4 - 18	7
	Client: Colaw Environmental Contact Person: U. To	Address 3930 SUNNybrook Dr. NW Hore: 320 846-4668	Project Information: Kuik Stop	SPUNISH S	1501	5501	105(0	6 501	1057	1058		Sampled By:	AS	Relinquished By:	man had



"Solutions for Technical Concerns"

MDH Laboratory # 027-137-157

Sample ID: | S030381114 | Pro

Project #: 5828.10

Sampler: Client

Type: Grab

Client:

Coteau Environmental

Status: Normal NTS COC No: 23562

Matrix: Soil

Study: (Descript: I

Consultant KC Kwik Stop TS COC No: 23562 Sampled: 2/4/2003 05:30 PM

Maurix. Sur

Location: B-10 (10-12)

Completed: 02/13/2003

Notes:

Analyte	Analysis Date	Result	Units	RL	Method
GRO, Soil	2/12/2003	<4	mg/Kg	4	WI Method
Benzene, Soil	2/12/2003	< 100	ug/Kg	100	SW 846 8021B
Ethyl Benzene, Soil	2/12/2003	< 70	ug/Kg	70	SW 846 8021B
Methyl tert-butyl ether	2/12/2003	< 120	ug/Kg	120	SW846 8021
Moisture	2/9/2003	· 16	%	0.1	EPA 160.3
Toluene, Soil	2/12/2003	< 100	ug/Kg	100	SW 846 8021B
Total Xylenes, Soil	2/12/2003	< 200	ug/Kg	200	SW 846 8021B

Approved By:

Project Manager:

Analyses were performed by methods approved by the U.S. Environmental Protection Agency and the Minnesota Department of Health.

Northeast Technical Services, Inc. makes no warranty except that the analysis has been made upon the samples received in accordance with generally accepted testing laboratory principles and practices. The results of the analysis may not be characteristic of the whole from which the sample was taken. This warranty is in lieu of all other warranties either expressed or implied.

Northeast Technical Services, Inc. 315 Chesmu Street
P.O. Box 1142
Virginia, MN 55792
Phone: 218-741-4290
Fax: 218-741-4291

Chain of Custody Record

of coc# 235 (p. Page_

Date Due:

	Comments						NTS Project # 58,28 · 10 Mise. Lab Information
THE THE THE	Analysis Required	X X					50-0-3rad C100
Octeau Environmental 3930 Sunnybrack Dr. Un Mexandria MN56308 ice to: - Sauve as abave -	Collection Matrix Type Filtered	> ×					Date Received for Laboratory By:
Reparation Addition A	ription	7.0 2.5 9					Dalg -4-03 Received By:
Client Information Client Contact Person. Contact Person. Address: Addre	Lab Use Only	S333X 1114			-		Sampled By:

Si G Degrees Celsius

On Ice

Time Date

Date 2-5-03 (ime 2 ; 30)



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-1 10.2'

Laboratory ID #: 022478-01

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 6/17/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

l

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
1,1,1,2-Tetrachloroethane	3.0	BDL
1,1,1-Trichloroethane	2.5	BDL
1,1,2,2-Tetrachloroethane	. 3.0	BDL
1,1,2-Trichloroethane	2.5	BDL
1,1-Dichloroethane	2.5	BDL
1,1-Dichloroethene	15.0	BDL
1,1-Dichloropropene	2.5	BDL
1,2,3-Trichlorobenzene	2.0	BDL
1,2,3-Trichloropropane	4.0	BDL
1,2,4-Trichlorobenzene	1.5	BDL
1,2,4-Trimethylbenzene	1.0	725.0
1,2-Dibromo-3-chloropropane	3.5	BDL
1,2-Dibromoethane	25.0	BDL
1,2-Dichlorobenzene	1.0	BDL
1,2-Dichloroethane	3.0	BDL
1,2-Dichloropropane	3.0	BDL
1,3,5-Trimethylbenzene	1.0	BDL
1,3-Dichlorobenzene	1.0	BDL
1,3-Dichloropropane	2.5	BDL

Laboratory Manager. Bassam Yous fef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-1 10.2'

Laboratory ID #: 022478-01

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 6/17/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter Parame	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	4.0	BDL
2,2-Dichloropropane	5.0	BDL
2-Chlorotoluene	10.0	BDL
4-Chlorotoluene	5.0	BDL
Acetone	100.0	BDL
Allyl Chloride	5.0	BDL
Benzene	0.50	1254.0
Bromobenzene	1.0	BDL
Bromochloromethane	5.0	BDL
Bromodichloromethane	3.5	BDL
Bromoform	25.0	BDL
Bromomethane	65.0	BDL
Carbon Tetrachloride	3.5	BDL
Chlorobenzene	1.0	BDL
Chloroethane	35.0	BDL
Chloroform	2.5	BDL
Chloromethane	25.0	BDL
cis-1,2-Dichloroethene	1.5	BDL
cis-1,3-Dichloropropene	1.0	BDL
· · · · · · · · · · · · · · · · · · ·	•	

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-1 10.2'

Laboratory ID #: 022478-01

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 6/17/02

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	3.0	BDL
Dibromomethane	30.0	BDL
Dichlorodifluoromethane	20.0	BDL
Dichlorofluoromethane	45.0	BDL
Ethyl Ether	15.0	BDL
Ethylbenzene	0.50	763.0
Hexachlorobutadiene	2.5	BDL
Isopropylbenzene	1.0	BDL
m,p-Xylene	1.0	2455.0
Methyl Ethyl Ketone	100.0	BDL
Methyl Isobutyl Ketone	25.0	BDL
Methyl Tertiary Butyl Ether	20.0	BDL
Methylene Chloride	2.0	BDL
n-Butylbenzene	1.0	BDL
n-Propylbenzene	1.0	BDL
Naphthalene	3.5	1265.0
o-Xylene	1.0	1229.0
p-Isopropyltoluene	1.0	BDL
sec-Butylbenzene	1.5	BDL

Laboratory Manager Bassam Yousset

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com



4

June 19, 2002

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-1 10.2'

Laboratory ID #: 022478-01

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 6/17/02 Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

	Detection Limit (ug/l)	Results (ug/l)
<u>Parameter</u>	10.0	BDL
Styrene	1.0	BDL
tert-Butylbenzene	1.5	BDL
Tetrachloroethene		BDL
Tetrahydrofuran	60.0	4798.0
Toluene	0.50	
trans-1, 3-Dichloropropene	0.50	BDL
trans-1,2-Dichloroethene	1.5	BDL
	1.0	BDL
Trichloroethene	25.0	BDL
Trichlorofluoromethane	5.0	BDL
Trichlorotrifluoroethane	5.0	BDL
Vinyl Chloride	J	125.0
%Dibromofluoromethane Recovery		102.0
%Toluene-d8 Recovery		99.0
%4-Bromofluorobenzene Recovery		99.0

Laboratory Manager. Bassam Youssel



Client: Coteau Environmental Address: 3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected: 6/13/02 Date Received: 6/17/02

Project #: K-C Kwik Stop

Client ID #: B-2 9.7' Laboratory ID #: 022478-02

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 6/19/02
Analyst: MS

VOC Analysis (Method Mn DEH 465F)

Bayamatar	Detection Limit (ug/l)	Results (ug/l)
Parameter	0.060	BDL
1,1,1,2-Tetrachloroethane	0.050	BDL
1,1,1-Trichloroethane	0,060	BDL
1,1,2,2-Tetrachloroethane	0.050	BDL
1,1,2-Trichloroethane		BDL
1,1-Dichloroethane	0.050	
1,1-Dichloroethene	0.30	BDL
1,1-Dichloropropene	0.050	BDL
1,2,3-Trichlorobenzene	0.040	BDL
1,2,3-Trichloropropane	0.080	BDL
	0.030	BDL
1,2,4-Trichlorobenzene	0,020	336.0
1,2,4-Trimethylbenzene	0.070	BDL
1,2-Dibromo-3-chloropropane	0.50	BDL
1,2-Dibromoethane		BDL
1,2-Dichlorobenzene	0.020	
1,2-Dichloroethane	0.060	BDL
1,2-Dichloropropane	0.060	BDL
1,3,5-Trimethylbenzene	0.020	100.0
1,3-Dichlorobenzene	0.020	BDL
	0.050	BDL
1.3-Dichloropropane		

Laboratory Manager Bassam Youssel





Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-2 9.7'

Laboratory ID #:

022478-02

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 6/19/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	0.080	BDL
2,2-Dichloropropane	0.10	BDL
2-Chlorotoluene	0.20	BDL
4-Chlorotoluene	0.10	BDL
Acetone	2.0	BDL
Allyl Chloride	0.10	BDL
Benzene	0.010	BDL
Bromobenzene	0.020	BDL
Bromochloromethane	0.10	BDL
Bromodichloromethane	0.070	BDL
	0.50	BDL
Bromoform	1.3	BDL
Bromomethane	0 070	BDL
Carbon Tetrachloride	0.020	BDL
Chlorobenzene		BDL
Chloroethane	0.70	
Chloroform	0.050	BDL
Chloromethane	0.50	BDL
cis-1,2-Dichloroethene	0.030	BDL
cis-1,3-Dichloropropene	0.020	BDL

Laboratory Manager: Bassam Youssef



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-2 9.7'

Laboratory ID #: 022478-02

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 6/19/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Paramet <u>er</u>	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	0.060	BDL
Dibromomethane	0,60	BDL
Dichlorodifluoromethane	0.40	BDL
Dichlorofluoromethane	0.90	BDL
Ethyl Ether	0.30	BDL
Ethyl Ethel Ethylbenzene	0.010	66.0
Hexachlorobutadiene	0.050	BDL
	0.020	7.0
Isopropylbenzene	0.020	555.0
m,p-Xylene	2 0	BDL
Methyl Ethyl Ketone	0.50	BDL
Methyl Isobutyl Ketone	0.40	BDL
Methyl Tertiary Butyl Ether		BDL
Methylene Chloride	0.040	BDL
n-Butylbenzene	0.020	
n-Propylbenzene	0 020	11.0
Naphthalene	0.070	75.0
o-Xylene	0.020	206.0
p-Isopropyltoluene	0.020	BDL
sec-Butylbenzene	0.030	BDL

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-2 9.7'

Laboratory ID #: 022478-02

Analysis: Matrix:

VOC Analysis (Method Mn DEH 465F)

Date of Analysis: 6/19/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter	Detection Limit (ug/l)	Results (ug/l)
Styrene	0.20	BDL
tert-Butylbenzene	0.020	BDL
Tetrachloroethene	0.030	BDL
Tetrahydrofuran	1.2	BDL
Toluene	0.010	98.0
	0.010	BDL
trans-1, 3-Dichloropropene	0.030	BDL
trans-1,2-Dichloroethene	0.020	BDL
Trichloroethene	0.50	BDL
Trichlorofluoromethane		BDL
Trichlorotrifluoroethane	0.10	
Vinyl Chloride	0.10	BDL
%Dibromofluoromethane Recovery		94.0
%Toluene-d8 Recovery		100.0
%4-Bromofluorobenzene Recovery		103.0

Laboratory Manager. Bassam Youssef



9

June 19, 2002

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-3 12.85'

Laboratory ID #: 022478-03

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 6/18/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
1,1,1,2-Tetrachloroethane	0.30	BDL
1,1,1-Trichloroethane	0.25	BDL
1,1,2,2-Tetrachloroethane	0.30	BDL
1,1,2-Trichloroethane	0.25	BDL
1,1-Dichloroethane	0.25	BDL
1,1-Dichloroethene	1.5	BDL
1,1-Dichloropropene	0.25	BDL
1,2,3-Trichlorobenzene	0.20	BDL
1,2,3-Trichloropropane	0.40	BDL
1,2,4-Trichlorobenzene	0.15	BDL
1,2,4-Trimethylbenzene	0.10	2338.0
1,2-Dibromo-3-chloropropane	0.35	BDL
1,2-Dibromoethane	2.5	BDL
1,2-Dichlorobenzene	0.10	BDL
1,2-Dichloroethane	0.30	BDL
1,2-Dichloropropane	0.30	BDL
1,3,5-Trimethylbenzene	0.10	1008.0
1,3-Dichlorobenzene	0.10	BDL
1.3-Dichloropropane	0.25	BDL

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received: Project #:

6/17/02

K-C Kwik Stop

Client ID #:

B-3 12.85'

Laboratory ID #: 022478-03

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 6/18/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter Parame	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	0.40	BDL
2,2-Dichloropropane	0.50	BDL
2-Chlorotoluene	1.0	BDL
4-Chlorotoluene	0.50	BDL
Acetone	10.0	BDL
Allyl Chloride	0,50	BDL
Benzene	0.050	101.0
Bromobenzene	0.10	BDL
Bromochloromethane	0.50	BDL
Bromodichloromethane	0.35	BDL
Bromoform	2.5	BDL
Bromomethane	6.5	BDL
Carbon Tetrachloride	0.35	BDL
Chlorobenzene	0.10	BDL
Chloroethane	3.5	BDL
Chloroform	0.25	BDL
Chloromethane	2.5	BDL
cis-1,2-Dichloroethene	0.15	BDL
cis-1,3-Dichloropropene	0 10	BDL

Laboratory Manager: Bassam Coussef



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-3 12.85'

Analysis:

Laboratory ID #: 022478-03 VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 6/18/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	0,30	BDL
Dibromomethane	3.0	BDL
Dichlorodifluoromethane	2.0	BDL
Dichlorofluoromethane	4.5	BDL
Ethyl Ether	1.5	BDL
Ethylbenzene	0.050	1259.0
Hexachlorobutadiene	0.25	BDL
Isopropylbenzene	0.10	144.0
m,p-Xylene	0.10	4825.0
Methyl Ethyl Ketone	10.0	BDL
Methyl Isobutyl Ketone	2.5	BDL
Methyl Tertiary Butyl Ether	2.0	BDL
Methylene Chloride	0.20	BDL
n-Butylbenzene	0.10	BDL
n-Propylbenzene	0.10	488.0
Naphthalene	0.35	825.0
o-Xylene	0.10	2232.0
p-Isopropyltoluene	0.10	BDL
sec-Butylbenzene	0.15	BDL

Laboratory Manager Bassam Yoursef



12

June 19, 2002

Coteau Environmental Client: 3930 Sunnybrook Dr. NW Address: Alexandria, MN 56308

6/13/02 Date Collected: 6/17/02 Date Received: K-C Kwik Stop Project #: Client ID #: B-3 12.85'

Laboratory ID #: 022478-03 VOC Analysis (Method Mn DEH 465F) Analysis:

Liquid Matrix: Date of Analysis: 6/18/02 MS Analyst:

VOC Analysis (Method Mn DEH 465F)

Parameter	Detection Limit (ug/l)	Results (ug/l)
Styrene	1.0	BDL
tert-Butylbenzene	0.10	BDL
Tetrachloroethene	0.15	BDL
Tetrahydrofuran	6.0	BDL
Toluene	0.050	4696.0
trans-1, 3-Dichloropropene	0.050	BDL
,	0.15	BDL
trans-1,2-Dichloroethene	0.10	BDL
Trichloroethene	2.5	BDL
Trichlorofluoromethane	0,50	BDL
Trichlorotrifluoroethane		-
Vinyl Chloride	0.50	BDL
%Dibromofluoromethane Recovery		93.0
%Toluene-d8 Recovery		94.0
%4-Bromofluorobenzene Recovery		111.0

Laboratory Manager Bassam Youşsef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000 595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489

Email: cummitanuunnmantal@msn.com



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-4 10.21

Laboratory ID #: 022478-04

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 6/18/02

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
1,1,1,2-Tetrachloroethane	1.5	BDL
1,1,1-Trichloroethane	1.3	BDL
1,1,2,2-Tetrachloroethane	1.5	BDL
1,1,2-Trichloroethane	1.3	BDL
1,1-Dichloroethane	1.3	BDL
1,1-Dichloroethene	7 5	BDL
1,1-Dichloropropene	1.3	BDL
1,2,3-Trichlorobenzene	1.0	BDL
1,2,3-Trichloropropane	2.0	BDL
1,2,4-Trichlorobenzene	0.75	BDL
1,2,4-Trimethylbenzene	0.50	6246.0
1,2-Dibromo-3-chloropropane	1.8	BDL
1,2-Dibromoethane	12.5	BDL
1,2-Dichlorobenzene	0.50	BDL
1,2-Dichloroethane	1.5	BDL
1,2-Dichloropropane	1.5	BDL
1,3,5-Trimethylbenzene	0.50	1960,0
1,3-Dichlorobenzene	0.50	BDL
1,3-Dichloropropane	1.3	BDL

Laboratory Manager. Bassam Youssef



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-4 10.21

Laboratory ID #:

022478-04

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 6/18/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter Parame		Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene		2.0	BDL
,		2.5	BDL
2,2-Dichloropropane		5.0	BDL
2-Chlorotoluene		2.5	BDL
4-Chlorotoluene			BDL
Acetone		50.0	_
Allyl Chloride		2.5	BDL
Benzene		0.25	209.0
Bromobenzene		0.50	BDL
Bromochloromethane		2.5	BDL
		1.8	BDL
Bromodichloromethane		12.5	BDL
Bromoform		32.5	BDL
Bromomethane			BDL
Carbon Tetrachloride		1.8	
Chlorobenzene		0.50	BDL
Chloroethane		17.5	BDL
Chloroform		1.3	BDL
Chloromethane		12.5	BDL
		0.75	BDL
cis-1,2-Dichloroethene		0,50	BDL
cis-1,3-Dichloropropene	_	1 1	

Laboratory Manager: Bassam (oussef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000 595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489

Email: summitenvironmental@msn.com



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-4 10.2'

Laboratory ID #:

022478-04

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 6/18/02 Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	1.5	BDL
Dibromomethane	15.0	BDL
Dichlorodifluoromethane	10.0	BDL
Dichlorofluoromethane	22.5	BDL
Ethyl Ether	7.5	BDL
Ethylbenzene	0.25	2686.0
Hexachlorobutadiene	1.3	BDL
Isopropylbenzene	0.50	227.0
m,p-Xylene	0.50	11513.0
Methyl Ethyl Ketone	50.0	BDL
Methyl Isobutyl Ketone	12.5	BDL
Methyl Tertiary Butyl Ether	10.0	BDL
Methylene Chloride	1.0	BDL
n-Butylbenzene	0.50	BDL
n-Propylbenzene	0.50	915.0
Naphthalene	1.8	2940.0
o-Xylene	0.50	4515.0
p-lsopropyltoluene	0.50	BDL
sec-Butylbenzene	0.75	BDL

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

B-4 10 2'

Laboratory ID #

022478-04

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis Liquid 6/18/02

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter_	Detection Limit (ug/l)	Results (ug/l)
Styrene	5.0	BDL
tert-Butylbenzene	0.50	BDL
Tetrachloroethene	0.75	BDL
Tetrahydrofuran	30 0	BDL
Toluene	0.25	9054.0
trans-1, 3-Dichloropropene	0.25	BDL
trans-1,2-Dichloroethene	0.75	BDL
Trichloroethene	0.50	BDL
Trichlorofluoromethane	12 5	BDL
Trichlorotrifluoroethane	2.5	BDL
	2 5	BDL
Vinyl Chloride	- 1	84.0
%Dibromofluoromethane Recovery		90,0
%Toluene-d8 Recovery		105.0
%4-Bromofluorobenzene Recovery		105.0

Laboratory Manager. Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summittenvironmental@msn.com





Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

6/13/02

Date Received:

6/17/02

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

Liquid

Method:

WI Mod.

Units:

ug/l

Analyst:

MS

Detection Limit:

See Below

Date of Analysis:

See Below

Lab Sample ID:	022478-01	022478-02	022478-03	022478-04
Client Sample ID:	B-1 10.2'	B-2 9.7'	B-3 12.85'	B-4 10.21
Detection Limit (ug/l)	100.0	100.0	100.0	100.0
Date Analyzed:	6/17/02	6/17/02	6/18/02	6/17/02
TPH-GRO	44993.0	4211.0	350157.0	338583.0
% Surrogate Recovery	82.0	140.0	92.0	96.0

Laboratory Manager: Bassark Youssef

SUMMIT ENVIRONMENTAL TECHNOLOGIES, INC. 595 EAST TALLMADGE AVENUE

AKRON, OHIO 44310 TEL: 330/253-8211; FAX: 330/253-4489

CHAIN OF CUSTODY

A2LA CERTIFICATION 4: 0724-01



CLIENT NAME CARLU ENVIRONMENTAL ADDRESS 3930 SURAY BRIVE NW; ALEXANDER SOB -- PO#. K-C KWIK STOP CONTACT PERSON NATE HUNKE PHONE # (320) 876-1668 FAX # (405) 882-4122 SAMPLED BY (124) Brooten, Mx PROJECT NAME: K-C. KWIK Stof --- PROJECT LOCATION-

-1 Walky 6-13-02 V VOC'S -1 Walky 6-13-02 V V -3	SAMPLE ID#	MEDIA	TIME	DATE	BTEX 8020	GRO 8015M	DRO 8015M	解冷	TCLP	TCLP	TCLP BNAS	TCLP PEST/HERB	OTHERS
6-13-02 6-13-02 6-13-02 6-13-02 6-13-02 6-13-02 6-13-02 6-13-02 6-13-02 6-13-02	3	19/2		_		7		+					V0C's -
3. 3 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	1												- Use MDH465F-MC
7.	1			20-61-9				1					
7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7								,					
057438				6-13-02		1		7					
7 7 7 8 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7													
7.82.	_	>		b-13-02		7		7					
74.38	_												
7.138.	-												
74.38	_												
2478.	_												
34 J8.						-							
	_				5	7	701			•			
					7	1	74/		0.1				
	-												
	_												
	1												
	-												

	DATE:	9:15	
	RECEIVED BY:	DATE: 6/17/2	
	DATE: 6-14-02		
110000	L'AL DATE	04 12:0	
SPECIAL INSTRUCTIONS.	REI INOUISHED BY:	RECEIVED AT THE LAB BY:	



August 20, 2002

Client: Coteau Environmental
Address: 3930 Sunnybrook Dr. NW
Alexandria, MN 56308

Date Collected: 8/12/02 Date Received: 8/16/02

Project #: K-C Kwik Stop

Client ID #: MW-01 Laboratory ID #: 023416-01

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 8/16/02
Analyst: MS

VOC Analysis (Method Mn DEH 465F)

Parameter_	Detection Limit (ug/l)	Results (ug/l)
1,1,1,2-Tetrachloroethane	0.060	BDL
1,1,1-Trichloroethane	0.050	BDL
1,1,2,2-Tetrachloroethane	0.060	BDL
1,1,2-Trichloroethane	0.050	BDL
1,1-Dichloroethane	0.050	BDL
1,1-Dichloroethene	0,30	BDL
,	0.050	BDL
1,1-Dichloropropene	0.040	BDL
1,2,3-Trichlorobenzene	0.080	BDL
1,2,3-Trichloropropane	0.030	BDL
1,2,4-Trichlorobenzene	0,020	BDL
1,2,4-Trimethylbenzene	0.020	BDL
1,2-Dibromo-3-chloropropane	0.50	BDL
1,2-Dibromoethane		BDL
1,2-Dichlorobenzene	0.020	
1,2-Dichloroethane	0.060	BDL
1,2-Dichloropropane	0.060	BDL
1,3,5-Trimethylbenzene	0.020	BDL
1,3-Dichlorobenzene	0.020	BDL
1,3-Dichloropropane	0,050	BDL

Laboratory Manager Bassam Youssel

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com

1



August 20, 2002

Client: Coteau Environmental Address: 3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected 8/12/02 Date Received: 8/16/02

Project #: K-C Kwik Stop

Client ID #: MW-01 Laboratory ID #: 023416-01

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 8/16/02
Analyst: MS

VOC Analysis (Method Mn DEH 465F)

Parameter	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	0.080	BDL
2,2-Dichloropropane	0 10	BDL
2-Chlorotoluene	0.20	BDL
4-Chlorotoluene	0.10	BDL
Acetone	2.0	BDL
Allyl Chloride	0.10	BDL
Benzene	0.010	BDL
Bromobenzene	0.020	BDL
Bromochloromethane	0.10	BDL
Bromodichloromethane	0.070	BDL
Bromoform	0.50	BDL
Bromomethane	1.3	BDL
Carbon Tetrachloride	0.070	BDL
Chlorobenzene	0.020	BDL
Chloroethane	0.70	BDL
Chloroform	0.050	BDL
Chloromethane	0.50	BDL
cis-1,2-Dichloroethene	0.030	BDL
cis-1,3-Dichloropropene	0.020	BDL

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com



August 20, 2002

Client: Coteau Environmental
Address: 3930 Sunnybrook Dr. NW
Alexandria, MN 56308

Date Collected: 8/12/02
Date Received: 8/16/02
Project #: K-C Kwik Stop

Client ID #: MW-01 Laboratory ID #: 023416-01

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 8/16/02
Analyst: MS

VOC Analysis (Method Mn DEH 465F)

Detection Limit (ug/l)	Results (ug/l)
0.060	BDL
0.60	BDL
0.40	BDL
0.90	BDL
0.30	BDL
0.010	BDL
0.050	BDL
0.020	BDL
0.020	BDL
2.0	BDL
0.50	BDL
0.40	BDL
0.040	BDL
0.020	BDL
0.020	BDL
0.070	BDL
0.020	BDL
0.020	BDL
0.030	BDL
	0.060 0.60 0.40 0.90 0.30 0.010 0.050 0.020 0.020 2.0 0.50 0.40 0.040 0.040 0.020 0.020 0.020 0.020

Laboratory Manager: Bassam(Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summittenvironmental@msn.com



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

8/12/02

Date Received:

8/16/02

Project #:

K-C Kwik Stop

Client ID #:

MW-01

Laboratory ID #:

Analysis:

023416-01 VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 8/16/02

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter	Detection Limit (ug/l)	Results (ug/l)
	0.20	BDL
Styrene	0.020	BDL
tert-Butylbenzene		BDL
Tetrachloroethene	0.030	
Tetrahydrofuran	1.2	BDL
Toluene	0.010	BDL
	0.010	BDL
trans-1, 3-Dichloropropene	0.030	BDL
trans-1,2-Dichloroethene		BDL
Trichloroethene	0.020	
Trichlorofluoromethane	0.50	BDL
Trichlorotrifluoroethane	0.10	BDL
	0.10	BDL
Vinyl Chloride		96.0
%Dibromofluoromethane Recovery		95.0
%Toluene-d8 Recovery		
%4-Bromofluorobenzene Recovery		89.0

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489

,-	•		~	
				1
				•••
				_
				_
				_
				-
				i
				_
				_
				-
				•
			1	
				_
				_
				_
				_
				_
				_



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

8/12/02

Date Received:

8/16/02

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

Liquid

Method:

WI Mod.

Units:

ug/l

Analyst:

MS

Detection Limit:

See Below

Date of Analysis:

See Below

Lab Sample ID:

023416-01

Client Sample 1D:

MW-01

Detection Limit (ug/l)

100.0

Date Analyzed:

8/16/02

TPH-GRO

<100.0

% Surrogate Recovery

102.0

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489





Client:

Coteau Environmental

Address.

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

8/12/02

Date Received:

8/16/02

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #: Matrix:

See Below

Liquid

Method:

Units:

8021

ug/L

Analyst:

MS

Detection Limit:

See Below

Date of Analysis:

See Below

Lab Sample ID:

Date Analyzed:

023416-02

Client Sample ID:

MW-06

Detection Limit (ug/L)

1.0

Benzene

8/16/02 <1.0

Toluene

<1.0

Ethylbenzene

<1.0

Total Xylene

<1.0

% Surrogate Recovery

100.0

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489





Client:

9

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

8/12/02

Date Received:

8/16/02

Project #:

K-C Kwik Stop

Client ID #:

MW-02

Laboratory ID #:

023416-03

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 8/16/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter	Detection Limit (ug/l)	Results (ug/l)
1,1,2-Tetrachloroethane	0.060	BDL
1,1,1-Trichloroethane	0.050	BDL
1,1,2,2-Tetrachloroethane	0.060	BDL
1,1,2-Trichloroethane	0.050	BDL
1,1-Dichloroethane	0.050	BDL
1,1-Dichloroethene	0.30	BDL
1,1-Dichloropropene	0.050	BDL
1,2,3-Trichlorobenzene	0.040	BDL
1,2,3-Trichloropropane	0.080	BDL
1,2,4-Trichlorobenzene	0.030	BDL
1,2,4-Trimethylbenzene	0.020	BDL
1,2-Dibromo-3-chloropropane	0.070	BDL
1,2-Dibromoethane	0.50	BDL
1,2-Dichlorobenzene	0.020	BDL
1,2-Dichloroethane	0.060	BDL
1,2-Dichloropropane	0.060	BDL
1,3,5-Trimethylbenzene	0.020	BDL
1,3-Dichlorobenzene	0.020	BDL
1,3-Dichloropropane	0.050	BDL
1,5 2 IIII O P P P P		

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

8/12/02

Date Received:

8/16/02

Project #:

K-C Kwik Stop

Client ID #:

MW-02

Laboratory ID #:

023416-03

Analysis: Matrix: VOC Analysis (Method Mn DEH 465F)

Date of Analysis: 8/16/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	080.0	BDL
2,2-Dichloropropane	0.10	BDL
2-Chlorotoluene	0.20	BDL
4-Chlorotoluene	0.10	BDL
Acetone	2.0	BDL
Allyl Chloride	0.10	BDL
Benzene	0.010	BDL
Bromobenzene	0.020	BDL
Bromochloromethane	0.10	BDL
Bromodichloromethane	0.070	BDL
Bromoform	0.50	BDL
Bromomethane	1.3	BDL
Carbon Tetrachloride	0.070	BDL
Chlorobenzene	0.020	BDL
Chloroethane	0.70	BDL
Chloroform	0.050	BDL
Chloromethane	0.50	BDL
cis-1,2-Dichloroethene	0.030	BDL
cis-1,3-Dichloropropene	0.020	BDL

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com



9

August 20, 2002

Client: Coteau Environmental Address: 3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected: 8/12/02 Date Received: 8/16/02

Project #: K-C Kwik Stop

Client ID #: MW-02 Laboratory ID #: 023416-03

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 8/16/02
Analyst: MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	0.060	BDL
Dibromomethane	0.60	BDL
Dichlorodifluoromethane	0.40	BDL
Dichlorofluoromethane	0.90	BDL
Ethyl Ether	0.30	BDL
Ethylbenzene	0.010	BDL
Hexachlorobutadiene	0.050	BDL
Isopropylbenzene	0 020	BDL
m,p-Xylene	0.020	BDL
Methyl Ethyl Ketone	2.0	BDL
Methyl Isobutyl Ketone	0.50	BDL
Methyl Tertiary Butyl Ether	0.40	BDL
Methylene Chloride	0.040	BDL
n-Butylbenzene	0.020	BDL
n-Propylbenzene	0.020	BDL
Naphthalene	0.070	BDL
o-Xylene	0.020	BDL
p-Isopropyltoluene	0.020	BDL
sec-Butylbenzene	0.030	BDL

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summittenvironmental@msn.com



Client: Coteau Environmental Address: 3930 Sunnybrook Dr. NW Alexandria, MN 56308

Date Collected: 8/12/02 Date Received: 8/16/02

Project #: K-C Kwik Stop

Client ID #: MW-02 Laboratory ID #: 023416-03

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 8/16/02
Analyst: MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Styrene	0.20	BDL
tert-Butylbenzene	0.020	BDL
Tetrachloroethene	0.030	BDL
Tetrahydrofuran	1.2	BDL
Toluene	0.010	BDL
trans-1, 3-Dichloropropene	0.010	BDL
trans-1,2-Dichloroethene	0.030	BDL
Trichloroethene	0.020	BDL
Trichlorofluoromethane	0.50	BDL
Trichlorotrifluoroethane	0.10	BDL
Vinyl Chloride	0.10	BDL
%Dibromofluoromethane Recovery		103.0
%Toluene-d8 Recovery		94.0
%4-Bromofluorobenzene Recovery		93.0

Laboratory Manager: Bassam Youssef





Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

8/12/02

Date Received:

8/16/02

Project #:

K-C Kwik Stop

Client ID #: Laboratory ID #:

MW-03

Analysis:

023416-04 VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 8/19/02 Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
1,1,1,2-Tetrachloroethane	0.060	BDL
1,1,1-Trichloroethane	0.050	BDL
1,1,2,2-Tetrachloroethane	0.060	BDL
1,1,2-Trichloroethane	0.050	BDL
1,1-Dichloroethane	0.050	BDL
1,1-Dichloroethene	0.30	BDL
1,1-Dichloropropene	0.050	BDL
1,2,3-Trichlorobenzene	0.040	BDL
1,2,3-Trichloropropane	0.080	BDL
1,2,4-Trichlorobenzene	0.030	BDL
1,2,4-Trimethylbenzene	0.020	BDL
1,2-Dibromo-3-chloropropane	0.070	BDL
1,2-Dibromoethane	0.50	BDL
1,2-Dichlorobenzene	0.020	BDL
1,2-Dichloroethane	0.060	BDL
1,2-Dichloropropane	0.060	BDL
1,3,5-Trimethylbenzene	0.020	BDL
1,3-Dichlorobenzene	0.020	BDL
1,3-Dichloropropane	0.050	BDL

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

8/12/02

Date Received:

8/16/02

Project #:

K-C Kwik Stop

Client ID #:

MW-03

Laboratory ID #:

023416-04

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 8/19/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Paramete <u>r</u>	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	0.080	BDL
2,2-Dichloropropane	0.10	BDL
2-Chlorotoluene	0.20	BDL
4-Chlorotoluene	0.10	BDL
Acetone	2.0	BDL
Allyl Chloride	0.10	BDL
Benzene	0.010	BDL
Bromobenzene	0.020	BDL
Bromochloromethane	0.10	BDL
Bromodichloromethane	0.070	BDL
Bromoform	0.50	BDL
	1.3	BDL
Bromomethane	0.070	BDL
Carbon Tetrachloride	0.020	BDL
Chlorobenzene	0.70	BDL
Chloroethane	0.050	BDL
Chloroform	0.50	BDL
Chloromethane		BDL
cis-1,2-Dichloroethene	0.030	BDL
cis-1,3-Dichloropropene	0.020	DDL

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

8/12/02

Date Received:

8/16/02

Project #:

K-C Kwik Stop

Client ID #:

MW-03

Laboratory ID #:

023416-04

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 8/19/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	0.060	BDL
Dibromomethane	0.60	BDL
Dichlorodifluoromethane	0.40	BDL
Dichlorofluoromethane	0.90	BDL
Ethyl Ether	0.30	BDL
Ethylbenzene	0.010	BDL
Hexachlorobutadiene	0.050	BDL
Isopropylbenzene	0.020	BDL
m,p-Xylene	0.020	BDL
Methyl Ethyl Ketone	2.0	BDL
Methyl Isobutyl Ketone	0.50	BDL
Methyl Tertiary Butyl Ether	0.40	BDL
Methylene Chloride	0.040	BDL
n-Butylbenzene	0.020	BDL
n-Propylbenzene	0.020	BDL
Naphthalene	0.070	BDL
o-Xylene	0.020	BDL
p-Isopropyltoluene	0.020	BDL
sec-Butylbenzene	0.030	BDL

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com



Client.

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected.

8/12/02

Date Received:

8/16/02

Project #:

K-C Kwik Stop

Client ID #:

MW-03

Laboratory ID #: 023416-04

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 8/19/02 Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter	Detection Limit (ug/l)	Results (ug/l)
Styrene	0.20	BDL
tert-Butylbenzene	0.020	BDL
Tetrachloroethene	0.030	BDL
Tetrahydrofuran	1.2	BDL
Toluene	0.010	BDL
trans-1, 3-Dichloropropene	0.010	BDL
trans-1,2-Dichloroethene	0.030	BDL
Trichloroethene	0.020	BDL
Trichlorofluoromethane	0.50	BDL
Trichlorotrifluoroethane	0.10	BDL
Vinyl Chloride	0.10	BDL
%Dibromofluoromethane Recovery		110.0
%Toluene-d8 Recovery		85.0
%4-Bromofluorobenzene Recovery		97.0

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489



Client: Coteau Environmental Address: 3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected: 8/12/02 Date Received: 8/16/02

Project #: K-C Kwik Stop

Client ID #: MW-04 Laboratory ID #: 023416-05

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 8/16/02
Analyst: MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
1,1,1,2-Tetrachloroethane	0.060	BDL
1,1,1-Trichloroethane	0.050	BDL
1,1,2,2-Tetrachloroethane	0.060	BDL
1,1,2-Trichloroethane	0.050	BDL
1,1-Dichloroethane	0.050	BDL
1,1-Dichloroethene	0.30	BDL
1,1-Dichloropropene	0.050	BDL
1,2,3-Trichlorobenzene	0.040	BDL
1,2,3-Trichloropropane	0.080	BDL
1,2,4-Trichlorobenzene	0.030	BDL
1,2,4-Trimethylbenzene	0.020	BDL
1,2-Dibromo-3-chloropropane	0.070	BDL
1,2-Dibromoethane	0.50	BDL
1,2-Dichlorobenzene	0.020	BDL
1,2-Dichloroethane	0.060	BDL
1,2-Dichloropropane	0.060	BDL
1,3,5-Trimethylbenzene	0.020	BDL
1,3-Dichlorobenzene	0.020	BDL
1,3-Dichloropropane	0,050	BDL
7		

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000





Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

8/12/02

Date Received:

8/16/02

Project #:

K-C Kwik Stop

Client ID #:

MW-04

Laboratory ID #:

023416-05

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 8/16/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	0.080	BDL
2,2-Dichloropropane	0.10	BDL
2-Chlorotoluene	0.20	BDL
4-Chlorotoluene	0.10	BDL
Acetone	2.0	BDL
Allyl Chloride	0.10	BDL
Benzene	0.010	BDL
Bromobenzene	0.020	BDL
Bromochloromethane	0.10	BDL
Bromodichloromethane	0.070	BDL
Bromoform	0.50	BDL
Bromomethane	1.3	BDL
Carbon Tetrachloride	0.070	BDL
Chlorobenzene	0.020	BDL
Chloroethane	0.70	BDL
Chloroform	0.050	BDL
Chloromethane	0.50	BDL
cis-1,2-Dichloroethene	0.030	BDL
cis-1,3-Dichloropropene	0.020	BDL

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected: Date Received: 8/12/02 8/16/02

Project #:

K-C Kwik Stop

Client ID #:

MW-04

Laboratory ID #: 023416-05 VOC Analysis (Method Mn DEH 465F)

Analysis: Matrix:

Liquid

Date of Analysis: 8/16/02 Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

	Detection Limit (ug/l)	Results (ug/l)
<u>Parameter</u>	0.060	BDL
Dibromochloromethane	0.60	BDL
Dibromomethane	0.40	BDL
Dichlorodifluoromethane	0.90	BDL
Dichlorofluoromethane	0.30	BDL
Ethyl Ether	0,010	BDL
Ethylbenzene	0.050	BDL
Hexachlorobutadiene	0,020	BDL
Isopropylbenzene	0.020	BDL
m,p-Xylene	2.0	BDL
Methyl Ethyl Ketone	0.50	BDL
Methyl Isobutyl Ketone	0.40	BDL
Methyl Tertiary Butyl Ether	0.040	BDL
Methylene Chloride	0.020	BDL
n-Butylbenzene	0.020	BDL
n-Propylbenzene	0.070	BDL
Naphthalene	0.020	BDL
o-Xylene	0.020	BDL
p-Isopropyltoluene	0.030	BDL
sec-Butylbenzene	,)	

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000 595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com



Coteau Environmental Client: 3930 Sunnybrook Dr. NW Address: Alexandria, MN 56308

8/12/02 Date Collected: 8/16/02 Date Received:

K-C Kwik Stop Project #:

Client ID #: MW-04 Laboratory ID #: 023416-05

VOC Analysis (Method Mn DEH 465F) Analysis:

Liquid Matrix: Date of Analysis: 8/16/02 MS Analyst:

VOC Analysis (Method Mn DEH 465F)

Parameter Parame	Detection Limit (ug/l)	Results (ug/l)
Styrene	0.20	BDL
tert-Butylbenzene	0.020	BDL
Tetrachloroethene	0.030	BDL
Tetrahydrofuran	1.2	BDL
Toluene	0.010	BDL
trans-1, 3-Dichloropropene	0.010	BDL
trans-1,2-Dichloroethene	0.030	BDL
Trichloroethene	0.020	BDL
Trichlorofluoromethane	0.50	BDL
Trichlorotrifluoroethane	0.10	BDL
	0.10	BDL
Vinyl Chloride		99.0
%Dibromofluoromethane Recovery		93.0
%Toluene-d8 Recovery		98.0
%4-Bromofluorobenzene Recovery		2 2.0

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected: Date Received:

8/12/02

Project #:

8/16/02 K-C Kwik Stop

MW-05

Client ID #:

Laboratory ID #:

023416-06

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 8/16/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter_	Detection Limit (ug/l)	<u>Results (ug/l)</u>
1,1,1,2-Tetrachloroethane	0,60	BDL
1,1,1-Trichloroethane	0.50	BDL
• •	0.60	BDL
1,1,2,2-Tetrachloroethane	0,50	BDL
1,1,2-Trichloroethane	0.50	BDL
1,1-Dichloroethane	3.0	BDL
1,1-Dichloroethenc		BDL
1,1-Dichloropropene	0.50	BDL
1,2,3-Trichlorobenzene	0.40	
1,2,3-Trichloropropane	0.80	BDL
1,2,4-Trichlorobenzene	0.30	BDL
1,2,4-Trimethylbenzene	0.20	373.0
1,2-Dibromo-3-chloropropane	0.70	BDL
1,2-Dibromoethane	5.0	BDL
'	0.20	BDL
1,2-Dichlorobenzene	0.60	BDL
1,2-Dichloroethane	0.60	BDL
1,2-Dichloropropane	0.20	107.0
1,3,5-Trimethylbenzene	0.20	BDL
1,3-Dichlorobenzene		BDL
1,3-Dichloropropane	0.50	DDL

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email summitenvironmental@msn.com



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

8/12/02

Date Received:

8/16/02 K-C Kwik Stop

Project #: Client ID #:

MW-05

Laboratory ID #: 023416-06

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid 8/16/02

Date of Analysis: Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

P	Detection Limit (ug/l)	Results (ug/l)
<u>Parameter</u>	0.80	BDL
1,4-Dichlorobenzene	1.0	BDL
2,2-Dichloropropane	2.0	BDL
2-Chlorotoluene		BDL
4-Chlorotoluene	1.0	
Acetone	20.0	910.0
Allyl Chloride	1.0	BDL
Benzene	0.10	503.0
	0.20	BDL
Bromobenzene	1.0	BDL
Bromochloromethane	0.70	BDL
Bromodichloromethane	5.0	BDL
Bromoform		BDL
Bromomethane	13.0	
Carbon Tetrachloride	0.70	BDL
Chlorobenzene	0.20	BDL
Chloroethane	7.0	BDL
	0.50	BDL
Chloroform	5.0	BDL
Chloromethane	0.30	BDL
cis-1,2-Dichloroethene	0.20	BDL
cis-1,3-Dichloropropene	V.20	222

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com



Client: Coteau Environmental

Address: 3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected: 8/12/02 Date Received: 8/16/02

Project #: K-C Kwik Stop

Client ID #: MW-05 Laboratory ID #: 023416-06

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 8/16/02
Analyst: MS

VOC Analysis (Method Mn DEH 465F)

Dayamatar	Detection Limit (ug/l)	Results (ug/l)
Parameter Dibromochloromethane	0.60	BDL
	6.0	BDL
Dibromomethane	4.0	BDL
Dichlorodifluoromethane	9.0	BDL
Dichlorofluoromethane	3.0	BDL
Ethyl Ether		347.0
Ethylbenzene	0.10	BDL
Hexachlorobutadiene	0.50	
Isopropylbenzene	0.20	BDL
m,p-Xylene	0.20	1154.0
Methyl Ethyl Ketone	20.0	BDL
Methyl Isobutyl Ketone	5.0	BDL
Methyl Tertiary Butyl Ether	4.0	BDL
•	0.40	BDL
Methylene Chloride	0.20	BDL
n-Butylbenzene	0.20	BDL
n-Propylbenzene	0.70	281.0
Naphthalene		709.0
o-Xylene	0.20	BDL
p-Isopropyltoluene	0.20	BDL
sec-Butylbenzene	0.30	DDL

Laboratory Manager Bassam (oussef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000 595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com



Coteau Environmental Client: 3930 Sunnybrook Dr. NW Address: Alexandria, MN 56308

Date Collected: 8/12/02 8/16/02 Date Received: K-C Kwik Stop Project #: MW-05 Client ID #: 023416-06 Laboratory ID #:

VOC Analysis (Method Mn DEH 465F) Analysis:

Liquid Matrix: Date of Analysis: 8/16/02 MS Analyst:

VOC Analysis (Method Mn DEH 465F)

P	Detection Limit (ug/l)	Results (ug/l)
<u>Parameter</u>	2.0	BDL
Styrene	0.20	BDL
tert-Butylbenzene	0.30	BDL
Tetrachloroethene		BDL
Tetrahydrofuran	12.0	
Toluene	0.10	1187.0
trans-1, 3-Dichloropropene	0.10	BDL
	0.30	BDL
trans-1,2-Dichloroethene	0.20	BDL
Trichloroethene	5.0	BDL
Trichlorofluoromethane	1.0	BDL
Trichlorotrifluoroethane		BDL
Vinyl Chloride	1.0	107.0
%Dibromofluoromethane Recovery		
%Toluene-d8 Recovery		95.0
%4-Bromofluorobenzene Recovery		94.0

Laboratory Manager. Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000

595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489 Email: summitenvironmental@msn.com



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected: Date Received:

8/12/02 8/16/02

Project #:

K-C Kwik Stop

Client ID #: Laboratory ID #: See Below

Matrix:

See Below

Method:

Liquid

Units:

WI Mod.

Analyst:

ug/l MS

Detection Limit:

See Below

Date of Analysis:

See Below

Lab Sample ID:	023416-03	023416-04	023416-05	023416-06
Client Sample ID:	MW-02	MW-03	MW-04	MW-05
Detection Limit (ug/l)	100.0	100.0	100.0	100.0
Date Analyzed:	8/16/02	8/16/02	8/16/02	8/16/02
TPH-GRO	<100.0	<100.0	288.0	13919.0
TITI GICO		100.0	126.0	108.0
% Surrogate Recovery	104.0	108.0	120.0	100.0

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000 595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489



Coteau Environmental Client: 3930 Sunnybrook Dr. NW Address: Alexandria, MN 56308

8/12/02 Date Collected: 8/16/02 Date Received:

K-C Kwik Stop Project #: See Below Client ID #: Laboratory ID #: See Below Liquid Matrix: 8021 Method: ug/L Units: MS Analyst: See Below **Detection Limit:** See Below Date of Analysis:

	Lab Sample ID: Client Sample ID: Detection Limit (ug/L) Date Analyzed:	023416-07 Trip Blank 1.0 8/16/02	
Benzene		<1.0	
Toluene		<1.0	
Ethylbenzene		<1.0	
Total Xylene		<1.0	
% Surrogate Re	covery	100.0	

Laboratory Manager: Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000 595 East Tallmadge Avenue • Akron, Ohio 44310 • Phone: 330-253-8211 • Fax: 330-253-4489

Summit Environmental Technologies, Inc. 595 East Tallmadge Avenue
Akron, Ohio 44310 Tel: 330.253.8211 Fax: 330.253.44

Tel: 330.253.8211 Fax: 330.253.4489

Analysis Request/Chain of Custody For Summit Environmental Technologies, Inc. use only

SET No. 0234/6.01.04.

								7	5716.	JLS7/6.01.07	4
Client Name	Project Name		-		_	Analytic	Analytical Parameters and Methods	neters	and M	[ethod:	S
COTCAS ENVIRGITMENTAL	KCS KWIK STOP										
Client Address	Project Address		,					/	/		
3 1	JAKA JAKA		I!O		·	_	_	_	_	_	_
Chent Phone No.	Report to		=0 '			_	_			_	_
320-	COLEAN ENVIRONMENTAL	アピアショ	bin	•		_	_	_	_	_	_
Client Fax No. Please Fax Results /	PO#		bjr		S.	_	_		_	_	_
605 882-4152]=]		ıəuļ	_	_	_	_	_	_
Contact Person	Quote No.		I,b		ntai	_		_	_	_	_
NATA HUNKE		-	ilo2		Col	_	<u>ح</u> رد	_	_	_	_
Sampled by S ≥ ✓	Check if Ohio VAP samples ~		osite x: S= udge	vitevt	SEK OL	_	ار الا - ر	_			
Sample Identification	Date Collected	Time E	Coml TIRM,			<u> </u>			/		
0,35	18/12/02	1537				\	\				
		1,77,31			\		:				
2 MD - Ce		1345 /			1						
3 20-02		1624 /				>	.,				
1 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3		1719 /				>	`				
S - 0.4		1818				7	`				
50-34	(ઉઝલ્સ્સ)	1907				7	\ \ <u>\</u>				
TRIP BLANK SAME FOR BOTH S	OC TRIP 13074 SITER				, ,						Ì
Relinquished by: Date Time	A Received by:	9	Time	Notes/Comments:	nts:						
1634 Sichar 8/13/2 1630	fre tecpus	विष्य १६	8								
	Rush Requested:	Days									
M That thelia 10 00	White and yellow pages should accompany samples to the laboratory	any samples to the		l' The client retains the pink page	pink page						



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

11/6/02

Date Received

11/11/02

Project #:

K-C Kwik Stop

Client ID #

See Below

Laboratory ID #:

See Below

Matrix:

Liquid

Method:

Wl Mod

Units:

ug/l

Analyst:

MS

Detection Limit

See Below

Date of Analysis.

See Below

Lab Sample ID: Client Sample ID: Detection Limit (ug/l) Date Analyzed	024927-01 MW-01 100.0 11/12/02	024927-02 MW-06 100.0 11/12/02	024927-03 MW-02 100.0 11/12/02	
TPH-GRO	<100.0	<100 0	<1()(),()	
% Surrogate Recovery	110.0	116.0	114 0	

1

Laboratory Manager: Bassam Youssef





Client Coteau Environmental
Address. 3930 Sunnybrook Dr. NW
Alexandria, MN 56308

Date Collected: 11/6/02
Date Received: 11/11/02
Project #: K-C Kwik Stop
Client ID #: MW-01

Client ID #: MW-01 Laboratory ID #: 024927-01

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 11/12/02
Analyst: MS

Laboratory Manager. Bassam Youssef

VOC Analysis (Method Mn DEH 465F)

Param <u>eter</u>	Detection Limit (ug/l)	Results (ug/l)
1.1.1,2-Tetrachloroethane	0.060	BDL
1,1,1-Trichloroethane	0.050	BDL
1,1,2,2-Tetrachloroethane	0.060	BDL
1,1,2-Trichloroethane	0.050	BDL
1,1-Dichloroethane	0.050	BDL
1,1-Dichloroethene	0.30	BDL
1,1-Dichloropropene	0.050	BDL
1,2,3-Trichlorobenzene	0.040	BDL
1,2,3-Trichloropropane	0.080	BDL
1,2,4-Trichlorobenzene	0.030	BDL
1,2,4-Trimethylbenzene	0.020	BDL
1,2-Dibromo-3-chloropropane	0.070	BDL
1,2-Dibromoethane	0.50	BDL
1,2-Dichlorobenzene	0.020	BDL
1,2-Dichloroethane	0.060	BDL
1,2-Dichloropropane	0,060	BDL
1,3,5-Trimethylbenzene	0,020	BDL
1,3-Dichlorobenzene	0.020	BDL
1,3-Dichloropropane	0.050	BDL
1,3-Dictioropropane		



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

11/6/02

Date Received:

11/11/02

Project #:

K-C Kwik Stop

Client ID #:

MW-01

Laboratory ID #:

024927-01

Analysis¹

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 11/12/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter_	Detection Limit (ug/l)	Results (ug/l)
1.4-Dichlorobenzene	0.080	5.0
2.2-Dichloropropane	0.10	BDL
2-Chlorotoluene	0.20	BDL
4-Chlorotoluene	0.10	BDL
Acetone	2.0	BDL
Allyl Chloride	0.10	BDL
Benzene	0.010	BDL
Bromobenzene	0.020	BDL
Bromochloromethane	0.10	BDL
Bromodichloromethane	0.070	BDL
Bromoform	0.50	BDL
Bromomethane	1.3	BDL
Carbon Tetrachloride	0.070	BDL
Chlorobenzene	0.020	BDL
Chloroethane	0.70	BDL
Chloroform	0.050	6.0
	0,50	BDL
Chloromethane	0.030	BDL
cis-1,2-Dichloroethene	0.020	BDL
cis-1,3-Dichloropropene	V.V.2V	

Laboratory Manager: Bassam Youssef





Client: Address: Coteau Environmental 3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected. Date Received:

11/6/02

Project #:

11/11/02

K-C Kwik Stop

Client ID #:

MW-01

Laboratory ID #: 024927-01

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 11/12/02

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Paramete <u>r</u>	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	0,060	· BDL
Dibromomethane	0.60	BDL
Dichlorodifluoromethane	0.40	BDL
Dichlorofluoromethane	0.90	BDL
Ethyl Ether	0.30	BDL
Ethylbenzene	0.010	BDL
Hexachlorobutadiene	0.050	BDL
Isopropylbenzene	0.020	BDL
m.p-Xylene	0.020	BDL
Methyl Ethyl Ketone	2.0	BDL
Methyl Isobutyl Ketone	0.50	BDL
Methyl Tertiary Butyl Ether	0.40	BDL
Methylene Chloride	0.040	BDL
n-Butylbenzene	0.020	BDL
n-Propylbenzene	0.020	BDL
Naphthalene	0.070	BDL
o-Xylene	0.020	BDL
p-Isopropyltoluene	0.020	BDL
sec-Butylbenzene	0.030	BDL
Sec-Daty to chize the		

Laboratory Manager, Bassam Youssef

"Analytical Integrity" • A2LA Accreditation #0724.01 • ISO 9000



Coteau Environmental Client: 3930 Sunnybrook Dr. NW Address: Alexandria, MN 56308

11/6/02 Date Collected 11/11/02 Date Received K-C Kwik Stop Project #: Client ID #: MW-01

Laboratory ID #: 024927-01

VOC Analysis (Method Mn DEH 465F) Analysis:

Matrix: Liquid Date of Analysis: 11/12/02 Analyst MS

VOC Analysis (Method Mn DEH 465F)

Parameter	Detection Limit (ug/l)	Results (ug/l)
Styrene	0.20	BDL
tert-Butylbenzene	0.020	BDL
Tetrachloroethene	0.030	BDL
Tetrahydrofuran	1.2	BDL
Toluene	0.010	BDL
trans-1, 3-Dichloropropene	0.010	BDL
trans-1,2-Dichloroethene	0.030	BDL
Trichloroethene	0.020	BDL
Trichlorofluoromethane	0.50	BDL
Trichlorottifluoroethane	0.10	BDL
Vinyl Chloride	0.10	BDL
%Dibromofluoromethane Recovery		96 0
%Toluene-d8 Recovery		100.0
%4-Bromofluorobenzene Recovery		99.0

Laboratory Manager Bassam Youssef



Chent:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected

11/6/02

Date Received:

11/11/02

Project #:

K-C Kwik Stop

Chent ID #:

See Below

Laboratory ID #.

See Below

Matrix:

Liquid

Method:

8021

Units:

ug/L

Analyst:

MS

Detection Limit: Date of Analysis: See Below See Below

024927-02

Client Sample ID:

Lab Sample ID:

Date Analyzed:

MW-06

Detection Limit (ug/L)

1.0

11/12/02 <1.()

Benzene Toluene

<1.()

Ethylbenzene

<1.()

Total Xylene

<1.0

% Surrogate Recovery

116.0

Laboratory Manager Bassam Youssef





Client: Coteau Environmental Address: 3930 Sunnybrook Dr. NW Alexandria, MN 56308

Date Collected: 11/6/02
Date Received: 11/11/02
Project # K-C Kwik Stop

Client ID #: MW-02 Laboratory ID #: 024927-03

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 11/12/02
Analyst: MS

VOC Analysis (Method Mn DEH 465F)

Parameter_	Detection Limit (ug/l)	Results (ug/l)
1,1,2-Tetrachloroethane	0 060	BDL
1,1,1-Trichloroethane	0.050	BDL
1,1,2,2-Tetrachloroethane	0,060	BDL
1.1.2-Trichloroethane	0.050	BDL
1,1-Dichloroethane	0.050	BDL
1,1-Dichloroethene	0.30	BDL
1,1-Dichloropropene	0.050	BDL
1,2,3-Trichlorobenzene	0.040	BDL
1,2,3-Trichloropropane	0.080	BDL
1,2,4-Trichlorobenzene	0.030	BDL
1,2,4-Trimethylbenzene	0.020	BDL
1,2-Dibromo-3-chloropropane	0.070	BDL
1,2-Dibromoethane	0.50	BDL
1,2-Dichlorobenzene	0.020	BDL
1,2-Dichloroethane	0 060	BDL
1.2-Dichloropropane	0,060	BDL
1,3,5-Trimethylbenzene	0 020	BDL
1,3-Dichlorobenzene	0.020	BDL
1,3-Dichloropropane	0.050	BDL
1,3-Dichiotopropane		

Laboratory Manager: Bassam Youssef



Client:

Coteau Environmental

Address.

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

11/6/02

Date Received:

11/11/02

Project #:

K-C Kwik Stop

MW-02

Client ID #:

Laboratory ID #: 024927-03

Analysis.

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 11/12/02

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	0.080	BDL
2,2-Dichloropropane	0.10	BDL
2-Chlorotoluene	0.20	BDL
4-Chlorotoluene	0.10	BDL
Acetone	2.0	BDL
Allyl Chloride	0 10	BDL
Benzene	0.010	BDL
Bromobenzene	0.020	BDL
Bromochloromethane	0.10	BDL
Bromodichloromethane	0,070	BDL
Bromoform	0.50	BDL
Bromomethane	1.3	BDL
Carbon Tetrachloride	0.070	BDL
Chlorobenzene	0.020	BDL
Chloroethane	0.70	BDL
Chloroform	0.050	BDL
Chloromethane	0.50	BDL
cis-1,2-Dichloroethene	0.030	BDL
cis-1,3-Dichloropropene	0.020	BDL

Laboratory Manager. Bassam Youssef





Client. Coteau Environmental Address 3930 Sunnybrook Dr. NW Alexandria, MN 56308

Date Collected 11/6/02
Date Received: 11/11/02
Project #: K-C Kwik Stop

Client ID #: MW-02 Laboratory ID #: 024927-03

Analysis. VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 11/12/02
Analyst: MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	0 060	BDL
Dibromomethane	0.60	BDL
Dichlorodifluoromethane	0.40	BDL
Dichlorofluoromethane	0.90	BDL
Ethyl Ether	0.30	BDL
Ethylbenzene	0.010	BDL
Hexachlorobutadiene	0.050	BDL
Isopropylbenzene	0.020	BDL
m,p-Xylene	0.020	BDL
Methyl Ethyl Ketone	2.0	BDL
Methyl Isobutyl Ketone	0.50	BDL
Methyl Tertiary Butyl Ether	0.40	BDL
Methylene Chloride	0.040	BDL
n-Butylbenzene	0.020	BDL
n-Propylbenzene	0.020	BDL
Naphthalene	0.070	BDL
o-Xylene	0.020	BDL
p-Isopropyltoluene	0.020	BDL
sec-Butylbenzene	0.030	BDL

Laboratory Manager Bassam Youssef



Client:

Coteau Environmental

Address.

3930 Sunnybrook Dr NW

Alexandria, MN 56308

Date Collected.

11/6/02

Date Received:

11/11/02

Project #:

K-C Kwik Stop

Client ID #:

MW-02

Laboratory ID #: 024927-03

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 11/12/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Param <u>eter</u>	Detection Limit (ug/l)	Results (ug/l)
Styrene	0.20	BDL
tert-Butylbenzene	0.020	BDL
Tetrachloroethene	0.030	BDL
Tetrahydrofuran	1.2	BDL
Toluene	0.010	BDL
trans-1, 3-Dichloropropene	0.010	BDL
trans-1,2-Dichloroethene	0.030	BDL
Trichloroethene	0.020	BDL
	0,50	BDL
Trichlorofluoromethane	0.10	BDL
Trichlorotrifluoroethane	0.10	BDL
Vinyl Chloride	0.10	100 0
%Dibromofluoromethane Recovery		98.0
%Toluene-d8 Recovery		
%4-Bromofluorobenzene Recovery		100 0



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected

11/6/02

Date Received:

11/11/02

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

Liquid

Method:

WI Mod.

Units:

ug/l

Analyst:

MS

Detection Limit:

See Below

Date of Analysis:

See Below

Lab Sample ID. Client Sample ID Detection Limit (ug/l) Date Analyzed:	MW-03 100.0 11/12/02	024927-05 MW-04 100.0 11/12/02	024927-06 MW-05 100.0 11/12/02	
TPH-GRO	18550.0	186.0	-	
% Surrogate Recovery	122.0	132.0	132.0	

Laboratory Manager Bassam Youssef



Client: Address: Coteau Environmental 3930 Sunnybrook Dr NW

Alexandria, MN 56308

Date Collected

11/6/02

Date Received

11/11/02

Project #:

K-C Kwik Stop

Client ID #:

MW-03

Laboratory ID #: 024927-04

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 11/14/02

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter_	Detection Limit (ug/l)	Results (ug/l)
1,1,1,2-Tetrachloroethane	6.0	BDL
1,1,1-Trichloroethane	5 0	BDL
1.1.2.2-Tetrachloroethane	6.0	BDL
1,1,2-Trichloroethane	5.0	BDL
1,1-Dichloroethane	5.0	BDL
1,1-Dichloroethene	30.0	BDL
1,1-Dichloropropene	5.0	BDL
1,2,3-Trichlorobenzene	4.0	BDL
1,2,3-Trichloropropane	8.0	BDL
1,2,4-Trichlorobenzene	3.0	BDL
1,2,4-Trimethylbenzene	2.0	1011.0
1,2-Dibromo-3-chloropropane	7.0	BDL
•	50.0	BDL
1,2-Dibromoethane	2.0	BDL
1,2-Dichlorobenzene	6.0	BDL
1,2-Dichloroethane	6.0	BDL
1,2-Dichloropropane	2.0	BDL
1,3,5-Trimethylbenzene	2.0	BDL
1,3-Dichlorobenzene	5.0	BDL
1,3-Dichloropropane	J.V	200
A November Passer Volumes		

Laboratory Manager, Bassam Youssef



Client:

Coteau Environmental

Address.

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected

11/6/02

Date Received.

11/11/02

Project #:

K-C Kwik Stop

Client ID #:

MW-03

Laboratory ID #: 024927-04

VOC Analysis (Method Mn DEH 465F)

Analysis: Matrix:

Liquid

Date of Analysis 11/14/02

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

Parameter Parame	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	0.8	BDL
2,2-Dichloropropane	10.0	BDL
2-Chlorotoluene	20 0	BDL
4-Chlorotoluene	10 0	BDL
Acetone	200.0	BDL
Allyl Chloride	10 0	BDL
Benzene	1.0	728 ()
Bromobenzene	2.0	BDL
Bromochloromethane	10.0	BDL
Bromodichloromethane	7.0	BDL
Bromoform	50.0	BDL
Bromomethane	130 0	BDL
Carbon Tetrachloride	7 ()	BDL
Chlorobenzene	2.0	BDL
Chloroethane	70 0	BDL
Chloroform	5.0	BDL
Chloromethane	50.0	BDL
cis-1,2-Dichloroethene	3.0	BDL
cis-1,3-Dichloropropene	2.0	BDL

Laboratory Manager: Bassam Youssef



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

11/6/02

Date Received:

11/11/02

Project #:

K-C Kwik Stop

Client ID #:

MW-03

Laboratory ID #: 024927-04

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 11/14/02

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	6.0	BDL
Dibromomethane	60 0	BDL
Dichlorodifluoromethane	40.0	BDL
Dichlorofluoromethane	90.0	BDL
Ethyl Ether	30.0	BDL
Ethylbenzene	1 0	1011-0
Hexachlorobutadiene	5.0	BDL
Isopropylbenzene	2.0	BDL
m,p-Xylene	2.0	3410.0
Methyl Ethyl Ketone	200.0	BDL
Methyl Isobutyl Ketone	50 0	BDL
Methyl Tertiary Butyl Ether	40.0	BDL
Methylene Chloride	4.0	BDL
n-Butylbenzene	2.0	BDL
n-Propylbenzene	2.0	BDL
**	7.0	917.0
Naphthalene	2 0	1257.0
o-Xylene	2.0	BDL
p-Isopropyltoluene	3 0	BDL
sec-Butylbenzene	<i>5</i>	

Laboratory Manager: Bassam Youssef



Coteau Environmental Client: Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

11/6/02 Date Collected. 11/11/02 Date Received:

K-C Kwik Stop Project #:

Client ID #: MW-03 Laboratory ID #: 024927-04

VOC Analysis (Method Mn DEH 465F) Analysis:

Liquid Matrix: Date of Analysis: 11/14/02 MS Analyst:

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Styrene	20.0	BDL
tert-Butylbenzene	2.0	BDL
Tetrachloroethene	3.0	BDL
Tetrahydrofuran	120.0	BDL
Toluene	1.0	3111.0
trans-1, 3-Dichloropropene	1.0	BDL
trans-1,2-Dichloroethene	3 0	BDL
Trichloroethene	2.0	BDL
Trichlorofluoromethane	50 0	BDL
Trichlorotrifluoroethane	10,0	BDL
Vinyl Chloride	10.0	BDL
%Dibromofluoromethane Recovery		99,0
%Toluene-d8 Recovery		92 0
%4-Bromofluorobenzene Recovery		97.0

Laboratory Manager. Bassam Youssef



Client: Coteau Environmental

Address: 3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected. 11/6/02
Date Received: 11/11/02
Project #: K-C Kwik Stop

Client ID #: MW-04 Laboratory ID # 024927-05

Analysis. VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 11/12/02
Analyst: MS

Parameter	Detection Limit (ug/l)	Results (ug/l)
1.1.1.2-Tetrachloroethane	0.060	BDL
1.1,1-Trichloroethane	0.050	BDL
1,1,2,2-Tetrachloroethane	0.060	BDL
	0.050	BDL
1,1,2-Trichloroethane	0.050	BDL
1,1-Dichloroethane	0.30	BDL
1,1-Dichloroethene	0,050	BDL
1.1-Dichloropropene	0.040	BDL
1,2,3-Trichlorobenzene	0.080	BDL
1,2,3-Trichloropropane	0.030	BDL
1,2,4-Trichlorobenzene		BDL
1,2,4-Trimethylbenzene	0.020	BDL
1,2-Dibromo-3-chloropropane	0.070	BDL
1,2-Dibromoethane	0 50	
1,2-Dichlorobenzene	0.020	BDL
1,2-Dichloroethane	0,060	BDL
1,2-Dichloropropane	0.060	BDL
1,3,5-Trimethylbenzene	0.020	BDL
1,3-Dichlorobenzene	0.020	BDL
1,3-Dichloropropane	0.050	BDL
i,5 Biomotopospi		
Laboratory Manager: Bassam Youssef	pr-	- -



Client: Coteau Environmental Address. 3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected: 11/6/02
Date Received. 11/11/02
Project #: K-C Kwik Stop

Cleant ID # MW 04

Client ID #. MW-04 Laboratory ID #: 024927-05

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 11/12/02
Analyst: MS

VOC Analysis (Method Mn DEH 465F)

Parameter Parame	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	0.080	BDL
2,2-Dichloropropane	0.10	BDL
2-Chlorotoluene	0.20	BDL
4-Chlorotoluene	0.10	BDL
Acetone	2.0	BDL
Allyl Chloride	0.10	BDL
Benzene	0.010	BDL
Bromobenzene	0,020	BDL
Bromochloromethane	0.10	BDL
Bromodichloromethane	0 070	BDL
Bromoform	0.50	BDL
Bromomethane	1.3	BDL
Carbon Tetrachloride	0.070	BDL
Chlorobenzene	0,020	BDL
Chloroethane	0.70	BDL
Chloroform	0.050	BDL
Chloromethane	0.50	BDL
cis-1,2-Dichloroethene	0.030	BDL
cis-1,3-Dichloropropene	0.020	BDL
ois 1,5 Diamoroproperio		
Laboratory Manager, Bassam Youssel		

Laboratory Manager. Bassam Youssef



Chent:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

11/6/02

Date Received:

11/11/02

Project #.

K-C Kwik Stop

Client ID #.

MW-04

Laboratory ID #: 024927-05

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 11/12/02 Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	0.060	BDL
Dibromomethane	0.60	BDL
Dichlorodifluoromethane	0.40	BDL
Dichlorofluoromethane	0.90	BDL
Ethyl Ether	0.30	BDL
Ethylbenzene	0.010	BDL
Hexachlorobutadiene	0.050	BDL
Isopropylbenzene	0.020	BDL
m,p-Xylene	0.020	BDL
Methyl Ethyl Ketone	2.0	BDL
Methyl Isobutyl Ketone	0.50	BDL
Methyl Tertiary Butyl Ether	0.40	BDL
Methylene Chloride	0.040	BDL
n-Butylbenzene	0.020	BDL
n-Propylbenzene	0.020	BDL
Naphthalene	0.070	BDL
o-Xylene	0.020	BDL
p-Isopropyltoluene	0.020	BDL
sec-Butylbenzene	0.030	BDL

Laboratory Manager: Bassam Youssef



Client Coteau Environmental Address. 3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected: 11/6/02
Date Received: 11/11/02
Project #: K-C Kwik Stop

Client ID #: MW-04 Laboratory ID #. 024927-05

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 11/12/02
Analyst: MS

VOC Analysis (Method Mn DEH 465F)

Parameter	Detection Limit (ug/l)	Results (ug/l)
Styrene	0.20	BDL
tert-Butylbenzene	0.020	BDL
Tetrachloroethene	0.030	BDL
Tetrahydrofuran	1 2	BDL
Toluene	0.010	BDL
trans-1, 3-Dichloropropene	0.010	BDL
trans-1,2-Dichloroethene	0.030	BDL
Trichloroethene	0.020	BDL
Trichlorofluoromethane	0.50	BDL
Trichlorotrifluoroethane	0.10	BDL
Vinyl Chloride	0.10	BDL
%Dibromofluoromethane Recovery		98.0
%Toluene-d8 Recovery		100 0
%4-Bromofluorobenzene Recovery		103.0

Laboratory Manager. Bassam Youssef





Client:

Coteau Environmental

Address.

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

11/6/02

Date Received:

11/11/02

Project #:

K-C Kwik Stop

Client ID #:

MW-05

Laboratory ID #: 024927-06

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis

Liquid 11/14/02

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
1,1,1,2-Tetrachloroethane	0.60	BDL
1,1,1-Trichloroethane	0.50	BDL
1,1,2,2-Tetrachloroethane	0.60	BDL
1,1,2-Trichloroethane	0.50	BDL
I,1-Dichloroethane	0.50	BDL
1,1-Dichloroethene	3.0	BDL
1.1-Dichloropropene	0.50	BDL
1,2,3-Trichlorobenzene	0.40	BDL
1,2,3-Trichloropropane	0.80	BDL
1,2,4-Trichlorobenzene	0.30	BDL
1,2,4-Trimethylbenzene	0.20	866 0
1,2-Dibromo-3-chloropropane	0.70	BDL
1,2-Dibromoethane	5.0	BDL
1,2-Dichlorobenzene	0.20	BDL
1,2-Dichloroethane	0.60	BDL
1,2-Dichloropropane	0.60	BDL
1,3,5-Trimethylbenzene	0.20	254.0
1,3-Dichlorobenzene	0.20	BDL
1,3-Dichloropropane	0.50	BDL
/		

Laboratory Manager Bassam Youssef



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected.

11/6/02

Date Received:

11/11/02 K-C Kwik Stop

Project #:

MW-05

Client ID #: Laboratory ID #: 024927-06

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis. 11/14/02

Analyst

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
1.4-Dichlorobenzene	0.80	BDL
2.2-Dichloropropane	1.0	BDL
2-Chlorotoluene	2.0	BDL
4-Chlorotoluene	1.0	BDL
Acetone	20 0	BDL
Allyl Chloride	1.0	BDL
Benzene	0.10	1167 0
Bromobenzene	0.20	BDL
Bromochloromethane	1.0	BDL
Bromodichloromethane	0.70	BDL
Bromoform	5.0	BDL
Bromomethane	13.0	BDL
Carbon Tetrachloride	0.70	BDL
Chlorobenzene	0.20	BDL
Chloroethane	7.0	BDL
Chloroform	0.50	BDL
Chloromethane	5.0	BDL
cis-1,2-Dichloroethene	0.30	BDL
cis-1,3-Dichloropropene	0.20	BDL
Laboratony Manager, Bassam Vousself		

Laboratory Manager. Bassam Youssef





Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected

11/6/02

Date Received:

11/11/02

Project #:

K-C Kwik Stop

Client ID #:

MW-05

Laboratory ID #: 024927-06 Analysis.

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 11/14/02

Analyst

MS

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	0.60	BDL
Dibromomethane	6 0	BDL
Dichlorodifluoromethane	4 ()	BDL
Dichlorofluoromethane	9 ()	BDL
Ethyl Ether	3.0	BDL
Ethylbenzene	0.10	647.0
Hexachlorobutadiene	0.50	BDL
Isopropylbenzene	0.20	BDL
m.p-Xylene	0.20	2423 ()
Methyl Ethyl Ketone	20,0	BDL
Methyl Isobutyl Ketone	5,0	BDL
Methyl Tertiary Butyl Ether	4.0	BDL
Methylene Chloride	0.40	BDL
n-Butylbenzene	0.20	BDL
n-Propylbenzene	0.20	110 0
Naphthalene	0.70	269 0
o-Xylenc	0.20	1125 0
p-lsopropyltoluene	0.20	BDL
sec-Butylbenzene	0.30	BDL
Laboratory Manager Bassam Youssef		





Client

Coteau Environmental

Address.

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

11/6/02

Date Received:

11/11/02

Project #:

K-C Kwik Stop

Client ID #: Laboratory ID #: 024927-06

MW-05

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis. 11/14/02

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Styrene	2.0	BDL
tert-Butylbenzene	0.20	BDL
Tetrachloroethene	0.30	BDL
Tetrahydrofuran	12 ()	BDL
Toluene	0.10	5320 0
trans-1, 3-Dichloropropene	0.10	BDL
trans-1,2-Dichloroethene	0.30	BDL
Trichloroethene	0.20	BDL
Trichlorofluoromethane	5.0	BDL
Trichlorotrifluoroethane	1.0	BDL
Vinyl Chloride	1.0	BDL
%Dibromofluoromethane Recovery		106 0
%Toluene-d8 Recovery		99.0
%4-Bromofluorobenzene Recovery		98 0

Laboratory Manager: Bassam Youssef



Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected

11/6/02

Date Received

11/11/02

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

Liquid

Method:

Digina

....

8021

Units:

ug/L

Analyst.

MS

Detection Limit

See Below

Date of Analysis.

See Below

Lab Sample ID:

Date Analyzed

024927-07

Client Sample ID:

Trip Blank

Detection Limit (ug/L)

1.0

11/12/02 <1.0

Benzene Toluene

<1.()

Ethylbenzene

<1.0

Total Xylene

< 1 ()

% Surrogate Recovery

96 0

Laboratory Manager. Bassam Youssef

Email: summitenvironmental@msn.com

ENVIRONMENTAL TECHNOLOGIES, INC.

TALLMADGE AVENUE)HIO 44310

:53-8211; FAX: 330/253-4489

CHAIN OF CUSTODY

A2LA CERTIFICATION 4: 0724-01



- PO# KC KWIE STOP	XANDIA 1011) SESOB
PROJECT LOCATION BRODE M. M.	DDRESS 3930 SWANY BROOK DR NW AL
ME KC KWIK STOP	IE. COTEAUENICKONMCLIENT ADDRESS-39

ERSON: NATE HUN KE ___ PHONE #320-246-468-FAX#: 582-4152 SAMPLED BY ___ SD+

_	r	_	, -		1	1	T.		r ·	1			.		,			·		 	 1
	OTHERS	1																			
	TCLP PEST/HERB													7							
	TCLP BNAS													1							
	TCLP														<						
	TCLP								1		1		-			1		7			
	1.PH 418.1				,					6		1					D				
7,207	d Mila	7		>	>	>	>		•		5		7	•	 						
-Hal-		>	>	>	7	/	7			•											
	BTEX 8020		7					>		(1	X								
	DATE	11/6/02	_				-			(
	TIME											4									
	MEDIA	W 4778R			T [→							·						
	WPLE ID#	10-0		70	0.3	60	ጸ	318 BLANK													

BY: See Man 1/02.
THE LAB BY:

DATE

9130

RECEIVED BY:

DATE:



March 10, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

2/27/03

Date Received:

2/28/03

Project #

K-C Kwik Stop

Client ID #:

MW-06

Laboratory ID #: 031026-03

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 3/3/03

Liquid

Analyst:

MS

Parameter	Detection Limit (ug/l)	Results (ug/l)
1,1,1,2-Tetrachloroethane	0.060	BDL
1,1,1-Trichloroethane	0.050	BDL
1,1,2,2-Tetrachloroethane	0.060	BDL
1,1,2-Trichloroethane	0.050	BDL
1,1-Dichloroethane	0.050	BDL
1,1-Dichloroethene	0.30	BDL
1,1-Dichloropropene	0.050	BDL
1,2,3-Trichlorobenzene	0.040	BDL
1,2,3-Trichloropropane	0.080	BDL
1,2,4-Trichlorobenzene	0 030	BDL
1,2.4-Trimethylbenzene	0.020	BDL
1,2-Dibromo-3-chloropropane	0.070	BDL
1,2-Dibromoethane	0.50	BDL
1,2-Dichlorobenzene	0.020	BDL
1,2-Dichloroethane	0.060	BDL
1,2-Dichloropropane	0,060	BDL
1,3,5-Trimethylbenzene	0.020	BDL
1,3-Dichlorobenzene	0.020	BDL
1,3-Dichloropropane	0.050	BDL
		223



March 10, 2003

Client: Coteau Environmental
Address: 3930 Sunnybrook Dr. NW
Alexandria, MN 56308

Date Collected: 2/27/03 Date Received: 2/28/03

Project #: K-C Kwik Stop Client ID #: MW-06 Laboratory ID #: 031026-03

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 3/3/03
Analyst: MS

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	0.080	BDL
2.2-Dichloropropane	0.10	BDL
2-Chlorotoluene	0.20	BDL
4-Chlorotoluene	0.10	BDL
Acetone	2 0	BDL
Allyl Chloride	0.10	BDL
Benzene	0.010	BDL
Bromobenzene	0.020	BDL
Bromochloromethane	0.10	BDL
Bromodichloromethane	0.070	BDL
Bromoform	0,50	BDL
Bromomethane	1.3	BDL
Carbon Tetrachloride	0.070	BDL
Chlorobenzene	0.020	BDL
Chloroethane	0.70	
Chloroform	0.70	BDL
Chloromethane	0,50	BDL
cis-1,2-Dichloroethene	0.030	BDL
cis-1,3-Dichloropropene		BDL
1 F	0.020	BDL



March 10, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

2/27/03

Date Received:

2/28/03

Project #:

K-C Kwik Stop

Client ID #:

MW-06

Laboratory ID #: 031026-03 Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 3/3/03 Analyst:

MS

<u>Parameter</u>		
	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	0,060	BDL
Dibromomethane	0.60	BDL
Dichlorodifluoromethane	0.40	BDL
Dichlorofluoromethane	0.90	BDL
Ethyl Ether	0,30	BDL
Ethylbenzene	0.010	BDL
Hexachlorobutadiene	0.050	BDL
Isopropylbenzene	0.020	BDL
m.p-Xylene	0.020	BDL
Methyl Ethyl Ketone	2.0	BDL
Methyl Isobutyl Ketone	0.50	BDL
Methyl Tertiary Butyl Ether	0.40	BDL
Methylene Chloride	0.040	BDL
n-Butylbenzene	0.020	BDL
n-Propylbenzene	0.020	BDL
Naphthalene	0.070	BDL
o-Xylene	0.020	
p-Isopropyltoluene		BDL
	0.020	BDL
sec-Butylbenzene	0.030	BDL



March 10, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

2/27/03

Date Received:

2/28/03

Project #:

K-C Kwik Stop

Client ID #:

MW-06

Laboratory ID #:

031026-03

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix Date of Analysis: 3/3/03

Liquid

MS

Analyst:

Parameter	· Detection Limit (ug/l)	Results (ug/l)
Styrene	0.20	BDL
tert-Butylbenzene	0.020	BDL
Tetrachloroethene	0.030	BDL
Tetrahydrofuran	1.2	BDL
Toluene	0.010	BDL
trans-1, 3-Dichloropropene	0.010	BDL
trans-1,2-Dichloroethene	0.030	BDL
Trichloroethene	0.020	BDL
Trichlorofluoromethane	0.50	BDL
Trichlorotrifluoroethane	0.10	BDL
Vinyl Chloride	0.10	BDL
%Dibromofluoromethane Recovery		128.0
%Toluene-d8 Recovery		101.0
%4-Bromofluorobenzene Recovery		102.0



March 10, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

2/27/03

Date Received:

2/28/03

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

Liquid

Method:

8021

Units:

ug/L

Analyst:
Detection Limit:

MS

Date of Analysis:

See Below See Below

	Lab Sample ID:	031026-01	031026-02	031026-04	
	Client Sample ID:	MW-01	MW-02	MW-04	
	Detection Limit (ug/L)	1.0	1.0	1.0	
	Date Analyzed:	3/3/03	3/3/03	3/4/03	
Benzene		<1.0	<1.0	9.4	
Toluene		<1.()	<1.0	<1.0	
Ethylbenzene		<1.0	<1.0	<1.0	
Total Xylene		<1.0	<1.0	<1.0	
% Surrogate Rec	covery	88.0	86.0	118.0	



March 10, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

2/27/03

Date Received:

2/28/03

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

Method:

Liquid WI Mod.

Units:

ug/l

Analyst:

MS

Detection Limit:

Sec Below

Date of Analysis:

Lab Sample ID: Client Sample ID: Detection Limit (ug/l) Date Analyzed:	031026-01 MW-01 100.0 3/3/03	031026-02 MW-02 100.0 3/3/03	031026-03 MW-06 100.0 3/3/03	031026-04 MW-04 100.0 3/4/03
TPH-GRO	<100.0	<100.0	<100.0	206.0
% Surrogate Recovery	88.0	86.0	90.0	118.0



March 10, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

2/27/03

Date Received:

2/28/03

Project #:

K-C Kwik Stop

Client ID #: Laboratory ID #: See Below

Matrix:

See Below

Liquid

Method:

8021

Units:

ug/L

Analyst:

MS

Detection Limit

See Below

Date of Analysis:

Lab Samp	ole ID: 031026-0	031026-06	6 031026-07	031026-08
Client Samp	ole ID: MW-08	3 MW-03	MW-05	Trip Blank
Detection Limit	(ug/L) 1.0	5.0	100.0	1.0
Date Ana	lyzed: 3/4/03	3/4/03	3/8/03	3/4/03
Benzene	9.0	349.0	4888.0	<1.0
Toluene	<1.0	307.0	13065.0	<1.0
Ethylbenzene	<1.0	655.0	1165.0	<1.0
Total Xylene	<1.0	1790.0	9325.0	<1.0
% Surrogate Recovery	118 0	106 0	116.0	84.0



March 10, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

2/27/03

Date Received:

2/28/03

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

Liquid

Method:

WI Mod.

Units:

ug/l

Analyst:
Detection Limit:

MS See Below

Date of Analysis:

Lab Sample ID:	031026-06	031026-07
Client Sample ID:	MW-03	MW-05
Detection Limit (ug/l)	100.0	100.0
Date Analyzed:	3/4/03	3/8/03
TPH-GRO	7101.0	54146.0
% Surrogate Recovery	106.0	116.0

Enmine Invited memory Termologies, Inc.

595 East Tallmadge Avenue Akron, Ohio 44310

Tel: 330.253.8211 Fax: 330.253.4489

Analysis Request/Chain of Custody
For Summit Environmental Technologies, Inc. use only
Page of

secoSET No.	Analytical Parameters and Methods)	SLS		2 \ 2 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	18		7 / 7	7 7 2		. , , , , , , , , , , , , , , , , , , ,	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	7 7	7 / 2	7 / 7	2 3		The state of the s	ments:
•	•		ンと	30	piup	יוים=	d, L= Air	 S=S:x dgbu	Matri SE_SI	- -	465							<u></u> →		-	Notes/Comments:	
	+	7	-						Grab Comp	+	7	7	7	7				7			Time	
	< ·		\	>				> 3	Time	Concrete	. SHLO	7280	0413	1003	10101	5	1043	1120			Date	-
	محدد عاد		Jun's	7				VAP sample	Date Collected	-	2/27/03							>			d by:	
	KC KUK	Project Address	BROOTEN, W	Report to	FO#		Quote No.	Check if Ohio VAP samples ✓							,						Received by:	
ame	STEAL ENDIRORMENTAL	30 SULVING BROOK DR ME	EXAMBILIA, MN 56308	:one No (320) 846-4668	No. Please Fax Results /	(00) 886-4152	crson	» SD4	Sample Identification	3 - 1 - 3	10-80	02	8	60	80	03		CS	TRIP TEM: 32A1K	I	quished by: Date Time	

White and yellow pages should accompany samples to the laboratory. The client retains the punk page.

Days

Rush Requested:

Must be approved by lab manager

Time

Date



.

May 09, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

5/1/2003

Date Received:

5/5/2003

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

Liquid

Method:

8021

Units:

ug/L

Analyst:

MS See Below

Detection Limit: Date of Analysis:

	Lab Sample ID:	032392-01	032392-02	032392-04	032392-05
	Client Sample ID:	MW-01	MW-02	MW-07	MW-04
	Detection Limit (ug/L)	1.0	1.0	1.0	1.0
	Date Analyzed:	5/6/2003	5/6/2003	5/6/2003	5/6/2003
Benzene		<1.0	<1.0	<1.0	5.0
Toluene		<1.0	<1.0	<1.0	<1.0
Ethylbenzene		<1.0	<1.0	<1.0	<1.0
Total Xylene		<1.0	<1.0	<1.0	<1.0
% Surrogate Rec	covery	90.0	88.0	88.0	102.0



May 09, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

5/1/2003

Date Received:

5/5/2003

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

:-..:..

Manix.

Liquid

Method:

8021

Units:

ug/L

Analyst:

MS

Detection Limit:

See Below

Date of Analysis:

	Lab Sample ID:	032392-06	032392-07	032392-08
	Client Sample ID:	MW-03	MW-05	Trip Blank
	Detection Limit (ug/L)	5.0	100.0	1.0
	Date Analyzed:	5/7/2003	5/8/2003	5/6/2003
Benzene		201.0	2566.0	<1.0
Toluene		424.0	12436.0	<1.0
Ethylbenzene		493.0	1089.0	<1.0
Total Xylene		1522.0	5809.0	<1.0
% Surrogate Re	covery	90.0	82.0	82.0



May 09, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

5/1/2003

Date Received:

5/5/2003

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

Liquid

Method:

WI Mod

Units:

ug/l

Analyst:

MS

Detection Limit:

See Below

Date of Analysis:

Lab Sample ID:	032392-01	032392-02	032392-03	032392-04
Client Sample ID:	MW-01	MW-02	MW-06	MW-07
Detection Limit (ug/l)	100.0	100.0	100.0	100.0
Date Analyzed:	5/6/2003	5/6/2003	5/6/2003	5/6/2003
TPH-GRO	<100.0	<100.0	<100.0	<100.0
% Surrogate Recovery	90.0	88.0	88.0	88.0



May 09, 2003

Client: Address:

Coteau Environmental 3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

5/1/2003 5/5/2003

Date Received:

5/5/2003

Project #:

K-C Kwik Stop

Client ID #:

See Below

Laboratory ID #:

See Below

Matrix:

ee belov

Method:

Liquid

Method

WI Mod

Units:

ug/l

Analyst:

MS See Below

Detection Limit: Date of Analysis:

Lab Sample ID: Client Sample ID: Detection Limit (ug/l) Date Analyzed:	032392-05 MW-04 100.0 5/6/2003 <100.0	032392-06 MW-03 100.0 5/7/2003 5827.0	032392-07 MW-05 100.0 5/8/2003 34537.0
% Surrogate Recovery	102.0	90.0	82.0



May 09, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

5/1/2003

Date Received:

5/5/2003

Project #:

K-C Kwik Stop

Client ID #:

Laboratory ID #: 032392-03

MW-06

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 5/6/2003

Analyst:

MS

Parameter_	Detection Limit (ug/l)	Results (ug/l)
	0.060	BDL
1,1,1,2-Tetrachloroethane		
1,1,1-Trichloroethane	0.050	BDL
1,1,2,2-Tetrachloroethane	0.060	BDL
1,1,2-Trichloroethane	0.050	BDL
1,1-Dichloroethane	0.050	BDL
1,1-Dichloroethene	0.30	BDL
1,1-Dichloropropene	0.050	BDL
1,2,3-Trichlorobenzene	0.040	BDL
1,2,3-Trichloropropane	0.080	BDL
1,2,4-Trichlorobenzene	0.030	BDL
1,2,4-Trimethylbenzene	0.020	BDL
1,2-Dibromo-3-chloropropane	0.070	BDL
1,2-Dibromoethane	0.50	BDL
1,2-Dichlorobenzene	0.020	BDL
1,2-Dichloroethane	0.060	BDL
1,2-Dichloropropane	0.060	BDL
1,3,5-Trimethylbenzene	0.020	BDL
1,3-Dichlorobenzene	0.020	BDL
1,3-Dichloropropane	0.050	BDL



May 09, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

5/1/2003

Date Received:

5/5/2003

Project #:

K-C Kwik Stop

Client ID #:

MW-06

Laboratory ID #: Analysis:

032392-03

Matrix:

VOC Analysis (Method Mn DEH 465F)

Date of Analysis: 5/6/2003

Liquid

Analyst:

MS

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	0.080	BDL
2,2-Dichloropropane	0.10	BDL
2-Chlorotoluene	0.20	BDL
4-Chlorotoluene	0.10	BDL
Acetone	2.0	BDL
Allyl Chloride	0.10	BDL
Benzene	0.010	BDL
Bromobenzene	0.020	BDL
Bromochloromethane	0.10	BDL
Bromodichloromethane	0.070	BDL
Bromoform	0.50	BDL
Bromomethane	1.3	BDL
Carbon Tetrachloride	0.070	BDL
Chlorobenzene	0.020	BDL
Chloroethane	0.70	BDL
Chloroform	0.050	BDL
Chloromethane	0.50	BDL
cis-1,2-Dichloroethene	0.030	BDL
cis-1,3-Dichloropropene	0.020	BDL
Cis-1,5 Diemoropene		



May 09, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

5/1/2003

Date Received:

5/5/2003

Project #:

K-C Kwik Stop

Client ID #:

MW-06

Laboratory ID #: 032392-03

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 5/6/2003

Liquid

Analyst:

MS

VOC Analysis (Method Mn DEH 465F)

10

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	0.060	BDL
Dibromomethane	0.60	BDL
Dichlorodifluoromethane	0.40	BDL
Dichlorofluoromethane	0.90	BDL
Ethyl Ether	0.30	BDL
Ethylbenzene	0.010	BDL
Hexachlorobutadiene	0.050	BDL
Isopropylbenzene	0.020	BDL
m,p-Xylene	0.020	BDL
Methyl Ethyl Ketone	2.0	BDL
Methyl Isobutyl Ketone	0.50	BDL
Methyl Tertiary Butyl Ether	0.40	BDL
Methylene Chloride	0.040	BDL
n-Butylbenzene	0.020	BDL
n-Propylbenzene	0.020	BDL
Naphthalene	0.070	BDL
o-Xylene	0.020	BDL
p-Isopropyltoluene	0.020	BDL
sec-Butylbenzene	0.030	BDL



May 09, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

5/1/2003

Date Received:

5/5/2003

Project #:

K-C Kwik Stop

Client ID#:

MW-06

Laboratory ID #:

032392-03

Analysis: Matrix:

VOC Analysis (Method Mn DEH 465F)

Date of Analysis: 5/6/2003

Liquid

Analyst:

MS

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Styrene	0.20	BDL
tert-Butylbenzene	0.020	BDL
Tetrachloroethene	0.030	BDL
Tetrahydrofuran	1.2	BDL
Toluene	0.010	BDL
trans-1, 3-Dichloropropene	0.010	BDL
trans-1,2-Dichloroethene	0.030	BDL
Trichloroethene	0.020	BDL
Trichlorofluoromethane	0.50	BDL
Trichlorotrifluoroethane	0.10	BDL
Vinyl Chloride	0.10	BDL
%Dibromofluoromethane Recovery		103.0
%Toluene-d8 Recovery		97.0
%4-Bromofluorobenzene Recovery	•	96.0



May 09, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

5/1/2003

Date Received:

5/5/2003

Project #:

K-C Kwik Stop

Client ID #:

Laboratory ID #: 032392-09

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix: Date of Analysis: 5/6/2003

Liquid

Analyst:

MS

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
1,1,1,2-Tetrachloroethane	0.060	BDL
1,1,1-Trichloroethane	0.050	BDL
1,1,2,2-Tetrachloroethane	0.060	BDL
1,1,2-Trichloroethane	0.050	BDL
1,1-Dichloroethane	0.050	BDL
1,1-Dichloroethene	0.30	BDL
1,1-Dichloropropene	0.050	BDL
1,2,3-Trichlorobenzene	0.040	BDL
1,2,3-Trichloropropane	0.080	BDL
1,2,4-Trichlorobenzene	0.030	BDL
1,2,4-Trimethylbenzene	0.020	BDL
1,2-Dibromo-3-chloropropane	0.070	BDL
1,2-Dibromoethane	0.50	BDL
1,2-Dichlorobenzene	0.020	BDL
1,2-Dichloroethane	0.060	BDL
1,2-Dichloropropane	0.060	BDL
1,3,5-Trimethylbenzene	0.020	BDL
1,3-Dichlorobenzene	0.020	BDL
1,3-Dichloropropane	0.050	BDL



· ·

May 09, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

5/1/2003

Date Received:

5/5/2003

Project #:

K-C Kwik Stop

Client ID #:

Laboratory ID #: 032392-09

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Date of Analysis: 5/6/2003

Analyst:

MS

Paramete <u>r</u>	Detection Limit (ug/l)	Results (ug/l)
1,4-Dichlorobenzene	0.080	BDL
2,2-Dichloropropane	0.10	BDL
2-Chlorotoluene	0.20	BDL
4-Chlorotoluene	0.10	BDL
Acetone	2.0	BDL
Allyl Chloride	0.10	BDL
Benzene	0.010	BDL
Bromobenzene	0.020	BDL
Bromochloromethane	0.10	BDL
Bromodichloromethane	0.070	BDL
Bromoform	0.50	BDL
Bromomethane	1.3	BDL
Carbon Tetrachloride	0.070	BDL
Chlorobenzene	0.020	BDL
Chloroethane	0.70	BDL
Chloroform	0.050	BDL
Chloromethane	0.50	BDL
cis-1,2-Dichloroethene	0.030	BDL
cis-1,3-Dichloropropene	0.020	BDL



May 09, 2003

Client:

Coteau Environmental

Address:

3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected:

5/1/2003

Date Received:

5/5/2003

Project #:

K-C Kwik Stop

Client ID #:

Laboratory ID #: 032392-09

Analysis:

VOC Analysis (Method Mn DEH 465F)

Matrix:

Liquid

Date of Analysis: 5/6/2003 Analyst:

MS

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Dibromochloromethane	0.060	BDL
Dibromomethane	0.60	BDL
Dichlorodifluoromethane	0.40	BDL
Dichlorofluoromethane	0.90	BDL
Ethyl Ether	0.30	BDL
Ethylbenzene	0.010	BDL
Hexachlorobutadiene .	0.050	BDL
Isopropylbenzene	0.020	BDL
m,p-Xylene	0.020	BDL
Methyl Ethyl Ketone	2.0	BDL
Methyl Isobutyl Ketone	0.50	BDL
Methyl Tertiary Butyl Ether	0.40	BDL
Methylene Chloride	0.040	BDL
n-Butylbenzene	0.020	BDL
n-Propylbenzene	0.020	BDL
Naphthalene	0.070	BDL
o-Xylene	0.020	BDL
p-Isopropyltoluene	0.020	BDL
sec-Butylbenzene	0.030	BDL



15 🔮

May 09, 2003

Client: Coteau Environmental Address: 3930 Sunnybrook Dr. NW

Alexandria, MN 56308

Date Collected: 5/1/2003
Date Received: 5/5/2003
Project #: K-C Kwik Stop

Client ID #:

Laboratory ID #: 032392-09

Analysis: VOC Analysis (Method Mn DEH 465F)

Matrix: Liquid
Date of Analysis: 5/6/2003
Analyst: MS

<u>Parameter</u>	Detection Limit (ug/l)	Results (ug/l)
Styrene	0.20	BDL
tert-Butylbenzene	0.020	BDL
Tetrachloroethene	0.030	BDL
Tetrahydrofuran	1.2	BDL
Toluene	0.010	BDL
trans-1, 3-Dichloropropene	0.010	BDL
trans-1,2-Dichloroethene	0.030	BDL
Trichloroethene	0.020	BDL
Trichlorofluoromethane	0.50	BDL
Trichlorotrifluoroethane	0.10	BDL
Vinyl Chloride	0.10	BDL
%Dibromofluoromethane Recovery		103.0
%Toluene-d8 Recovery		97.0
%4-Bromofluorobenzene Recovery		96.0

Summit Engenomental Lochnologies, Las 595 East Tallmadge Avenue

Tel 330.253.8211 Fax: 330.253.4489

Akron, Ohio 44310

For Summit Environmental Technologies, Inc. use only

matris tradical/Chainer Castot

SET No of

Analytical Parameters and Methods દુ 5,00A 1 7 > Notes/Comments: Number of Containers \sim 2 N 2 \sim Preservative SL=Sludge, A=Air Matrix: S=Solid, L=Liquid, O=Oil Composite Time Grab Days Collected 0360 Must be approved by lab manager 2040 Date Time 2853 1027 盤 5011 145 Check if Ohio VAP samples ~ Collected 5/1/03 Rush Requested: BECOTEL MK 520 Date Received by: KC KJK Report to Project Address Project Name Quote No PO# Sample Identification Time Time 020 Please Fax Results / WIN SIG SUDJEBENIANS CESS ジメンニといれるとといるし ALEXA1/0,21M, MX1 56308 , 0 N N Date 5/2/03 Date 20 ٥ 0 7 04 1.5 03 ふっちん 0125 Client Phone No. 320 - 846-466 8 BLitak 2511-288-509 Received in lab by: Relinquished by: 1000 XATE 405 012 COITHER Client Address Contact Person Chent Fax No. Client Name Sampled by e * \mathcal{I} $\mathcal{F}^{\mathcal{V}}$

White and yellow pages should accompany samples to the laboratory. The client retains the pink page.

APPENDIX C
METHODOLOGIES AND PROCEDURES

METHODOLOGIES

Soil Borings

Soil borings will be advanced using a drilling rig and hollow-stem augers. Soil samples will be collected during drilling utilizing a 2-foot long split-barrel sampler at approximately 2-foot depth intervals. Prior to each use, the augers will be steam cleaned and the split spoon sampler will be cleaned with a detergent solution and distilled water rinse.

Soil samples collected with the split-barrel sampler will be classified in the field to characterize the lithology, depth, and vertical extent of the soil at the site. The soil samples will be classified in the field. Geologic logs of the borings indicating the depth and identification of the various soil units, water-level information, information regarding the method of maintaining and advancing the drill hole, and all other relevant information will be prepared during the drilling program. The split-spoon samples will be collected, stored and screened in accordance with the Minnesota Pollution Control Agency (MPCA).

The split-barrel sampler will be cleaned with a detergent solution and distilled water between each use and the hollow-stem augers will be steam cleaned prior to advancement of each boring. Test borings will be abandoned following completion utilizing procedures approved by the Minnesota Department of Health (MDH). Cement grout will be used to seal the borings to minimize the potential for contaminant migration along the borehole. In cases where neither ground water nor soil impacts were encountered, the borings will be abandoned utilizing drill cuttings only.

Soil Borings

The soil borings will be advanced using hydraulically driven, direct-push drilling technology. Prior to the start of drilling, all borings locations will be cleared for utilities.

Soil samples will be collected using a 1-inch diameter by 24-inch long soil sampler. Soil samples will be collected at 2.5 foot depth intervals. Prior to drilling each soil boring, all down-hole equipment will be decontaminated to prevent cross contamination. In addition, the sampler will be decontaminated during soil boring advancement to prevent cross contamination between sample intervals.

Soil samples collected with the sampler will be classified in the field to characterize the lithology, depth, and vertical extent of the soil at the site. Geologic logs of the borings indicating the

depth and identification of the various soil units, water-level information, information regarding the method of maintaining and advancing the drill hole, and all other relevant information will be prepared during the drilling program. The soil samples will be collected, stored and screened in accordance with the Minnesota Pollution Control Agency (MPCA) requirements.

Soil borings will be abandoned following completion utilizing procedures approved by the Minnesota Department of Health (MDH). If required, cement grout will be used to seal the borings to minimize the potential for contaminant migration along the borehole. In cases where neither ground water nor soil impacts were encountered, the borings will be abandoned utilizing drill cuttings only.

Ground Water Sample Collection

Ground water samples will be collected from the soil borings using a temporary well consisting of a 0.50-inch diameter, flush-threaded, PVC, Schedule 40 casing and 0.50-inch diameter, flush-threaded, PVC, Schedule 40, 10 slot screen. The PVC screen and casing are wrapped in plastic by the manufacturer, prior to shipment. New PVC casing and screen are utilized for collection of the ground water samples from each boring, or are steam cleaned prior to use, to prevent cross-contamination. The PVC casing and screen are lowered into the direct-push bore hole and the PVC screen is centered on the approximate depth of the water table. The ground water sample is collected from the temporary well by lowering a 0.25-inch I.D. tygon tubing fitted with a bottom check valve into ground water that infiltrates into the temporary well. In relatively low-permeability formations, the temporary well is left in the direct-push borehole overnight to allow for infiltration of ground water into the well for subsequent collection with the 0.25-inch I.D. tygon tubing fitted with a bottom check valve.

Monitor Well Installation

Monitor wells will be designed, constructed, maintained, and sealed in compliance with the MDH. The monitor wells will be completed by a drilling contractor licensed in the State of Minnesota.

All monitor wells will be installed using 2-inch PVC screens with appropriate slot sizes and 2-inch PVC casings. All materials used to complete the monitor wells will be sterilized and wrapped

in a protective coating by the manufacturer or will be steam cleaned at the site prior to installation. Water-table wells will be constructed with 10-foot screens placed with approximately 60% of the screen below and 40% above the water table. Monitor wells constructed with the screen entirely below the water table will be completed with 5 feet of screen. Appropriately-sized filter pack will be placed around the screen from approximately 1 foot below the base of the screen to 2 feet above the screened interval. Each monitor well will be sealed with approximately 2 feet of bentonite above the filter pack and the remaining annular space will be filled with neat cement or approved equivalent to grade. Wells completed flush with grade will be constructed with a locking, packer-type well lid, gasketed manhole cover, and cement apron that slopes away from the well. Above-grade well completions will be constructed with a locking, protective steel casing. Protective guard posts will be placed around the well where necessary in areas of heavy vehicular traffic to protect the above-grade portion of the well casing. The well casing will terminate approximately 2 feet above grade.

Monitor well construction diagrams will be completed in the field during monitor well installation. Well construction details will be submitted to the MDH after installation of the monitor wells.

All monitor wells will be surveyed following installation. The top-of-casing (TOC) elevation will be surveyed to the nearest 0.01 foot. Ground elevations will also be surveyed, to the nearest 0.1 foot. A local benchmark will be used to determine the monitor well TOC and ground elevations. The test borings and monitor wells will be given an "MW" designation, numbered in the order that they are drilled.

Monitor Well Development

Following installation, the monitor wells will be developed using a dedicated bailer, hand-operated pump or an electric submersible pump. Ground water in each monitor well will be bailed until most of the sediment is removed from the water in the well and the filter pack.

Fluid Level Monitoring

Fluid-levels in all monitor wells will be monitored using an electronic water-level indicator, steel tape or interface probe. An interface probe or chalk and paste will be used to measure fluid levels when free product exists in the well. The fluid level will be obtained by lowering the measuring

device into the well until the water surface has been encountered and by recording the distance from the top of the inside casing to the measuring device to the nearest 0.01 foot. Prior to each measurement, the fluid-level measuring device will be cleaned with alcohol and distilled water.

Hydraulic Conductivity Testing

Hydraulic-conductivity tests will be performed at monitor wells only when necessary for determination of remedial alternatives and upon approval of the MPCA. Hydraulic-conductivity testing will be conducted to determine the water-transmitting properties of the soils in the immediate vicinity of each monitor well. Hydraulic-conductivity testing will be conducted by removing water from the well using a hand pump or dedicated bailer. The water-level recovery in the monitor well will be recorded using a water level indicator or a data logger. All equipment that comes in contact with the monitor well will be cleaned prior to each test using a detergent solution and distilled water. Wells containing free product will not be tested for hydraulic conductivity.

The Bouwer and Rice, 1976, method will be used to determine the average horizontal hydraulic conductivity at each monitor well tested. This information will be utilized to estimate the average linear velocity of ground-water flow at the site.

Ground Water Sampling

Ground water sampling procedures will be conducted in accordance with the MPCA. Monitor wells will be sampled from the suspected cleanest to the most contaminated. The field protocol for monitor well sampling will consist of fluid level measurement, monitor well development, and sample collection. The fluid level will be measured in the well to the nearest 0.01 foot. Following fluid level measurement, the well volume will be calculated and a minimum of 3 to 5 well casing volumes will be removed from the well prior to sampling using a dedicated stainless-steel or polyethylene bailer. Well stabilization data may be recorded during purging in the form of temperature, pH and electrical conductivity. Following sample collection, the samples will be shipped to a specified laboratory following appropriate documentation, preservation, and chain of custody procedures. Data collected during the sampling procedure will be documented in the field. All equipment utilized during sample collection will be cleaned with alcohol and deionized water.

Free-Phase Product Removal


Free phase product removal is conducted utilizing dedicated polyethylene bailers, passive sorbent bailers, or an active product recovery system. Free-phase product recovery utilizing a polyethylene disposable bailer is performed by lowering the disposable bailer to the product/water interface and bailing the product from the well until only a film or consistent thickness of product remains in the well.

A passive sorbent bailer system is utilized when product thicknesses are insufficient for removal with a disposable bailer. A passive sorbent bailer is suspended at the product/water interface with a vent tube or suspension cord. The sorbent bailer allows for passive collection of free-phase product utilizing a hydrophobic filter buoy. Product accumulates in a canister at the bottom of the bailer and is evacuated periodically utilizing a drain valve located at the base of the canister.

Active free-phase product recovery is utilized when removal of larger volumes of free-phase product is required. Active free-phase product recovery is accomplished with compressed air, vacuum recovery, or electrical submersible product recovery pumps and may involve water table depression, dual phase recovery, or product skimmer systems. Product recovery records will be maintained and reported to the MPCA on a periodic basis.

Laboratory Analysis

Laboratory analysis of the soil and ground water samples will be conducted by a certified laboratory using standard EPA methods. Benzene, toluene, ethylbenzene, xylenes (BTEX), volatile organic compounds (VOC's), total petroleum hydrocarbons (TPH) as gasoline utilizing GRO methodology and TPH as fuel oil using DRO methodology will be conducted in accordance with Wisconsin methodology or equivalent methods approved by the MPCA.



٦,

APPENDIX D

GEOLOGIC LOGS OF SOIL BORINGS AND MONITOR WELL CONSTRUCTION DIAGRAMS

PROJECT: FORMER K-C KWIK STOP				DATE: 6-13-02			BORING: B-1
			INNESOTA	GRADE EL	EVATIO	ON:	(MW-5)
				99.57			SCALE: 1" = 3'
SAMPLE NO.	DEPTH FEET	ASTM D2487	DESCRIPTION		"N"	PID	NOTES
		1	GRAVEL			PPM	ODOR/RECOVERY
	2.0		NO SAMPLEPREVIOUSL EXCAVATED UST BASIN				
	4.0	•					
	6.0						
	8.0		·				
	10.0	SP	SAND, fine to medium, blace Free product. Outwash.	k, saturated.		653.0	Strong odor/ 2.0 ft.
	12.0	SP				308.0	Strong odor/ 3.0 ft.
	14.0		NO SAMPLE				
	16.0	SP	SAND, fine to coarse; some brown; saturated. Outwash.			3.9	Odor/ 2.0 ft. (from water above)
	18.0		NO SAMPLE				
	20.0	SP	SAND, fine to medium; trac brown; saturated. Outwash.			0.2	No.odor/ 2.0 ft.

PROJECT	PROJECT: FORMER K-C KWIK STOP		KWIK STOP	DATE: 6-13-02			BORING: B-1
	BROC	TEN, M	INNESOTA	GRADE EL		ON:	(MW-5)
			99.57			SCALE: 1" = 3'	
SAMPLE NO.	DEPTH FEET	ASTM D2487	DESCRIPTION	N	"N"	PID	NOTES
			GRAVEL			PPM	ODOR/RECOVERY
	22.0		NO SAMPLE				
	24.0						
	26.0	SP	SAND, fine to coarse, brown Outwash.	ı, saturated.		ND	No odor/ 0.5 ft.
	28.0	CL	CLAY; trace medium to coar saturated. Till.	se sand; black;		ND	No odor/ 2.0 ft.
	30.0		REFUSAL AT 30 FEET BG END OF BORING AT				
	32.0		FT. = FEET ND = NONDETEC BG = BELOW G	TABLE			
	34.0			٠			
	36.0						
	38.0						
	40.0						

BROC	TENT M		DATE: 6-13-02		BORING: B-2	
	I EN, M	INNESOTA	GRADE EL	EVATIO	ON:	
						SCALE: 1" = 3'
DEPTH FEET	ASTM D2487	DESCRIPTION		"N"	PID	NOTES
		CONCRETE			PPM	ODOR/RECOVERY
	МН	SILT; trace clay; black; damp	o. Fill.		ND	No odor/ 1.0 ft.
2.0	ML	SILT and fine to coarse sand, damp. Alluvium.	brown/black,		11.5*	No odor/ 2.0 ft.
4.0	SM	SAND, fine to coarse; trace s moist. Outwash.	ilt; brown;		63.1*	No odor/ 2.0 ft.
6.0	SP	SAND, fine to coarse; some for brown; moist. Outwash.	ine gravel;		14.6*	No odor/ 2.0 ft.
8.0	SC	SAND, fine to coarse; trace c black; moist. Outwash.	lay; brown/		25.0	Odor/ 2.0 ft.
10.0	SP	SAND, fine to coarse, gray, s Outwash.	saturated.		198.0	Strong odor/ 2.0 ft.
12.0	SP	SAND, fine to coarse, brown saturated. Outwash.	/gray,		40.1	Odor/ 2.0 ft.
14.0	ÇD.	SAND Grata coores como			2.0	
16.0	31	brown; saturated. Outwash.	me graver;		2.9	No odor/ 2.0 ft.
18.0		NO SAMPLE				
20.0	SP	SAND, fine to coarse, brown Outwash.	, saturated.		3.2	No odor/ 2.0 ft.
	2.0 4.0 6.0 8.0 10.0 14.0 16.0 18.0	FEET D2487 MH 2.0 ML 4.0 SM 6.0 SP 8.0 SC 10.0 SP 14.0 SP 14.0 SP 14.0 SP	CONCRETE MH SILT; trace clay; black; damp 2.0 ML SILT and fine to coarse sand, damp. Alluvium. 4.0 SM SAND, fine to coarse; trace s moist. Outwash. 6.0 SP SAND, fine to coarse; some fibrown; moist. Outwash. 8.0 SC SAND, fine to coarse; trace coblack; moist. Outwash. 10.0 SP SAND, fine to coarse, gray, soutwash. 12.0 SP SAND, fine to coarse, brown saturated. Outwash. 14.0 SP SAND, fine to coarse, brown saturated. Outwash. 16.0 NO SAMPLE 20.0 SP SAND, fine to coarse, brown saturated. Outwash.	CONCRETE MH SILT; trace clay; black; damp. Fill. SILT and fine to coarse sand, brown/black, damp. Alluvium. 4.0 SM SAND, fine to coarse; trace silt; brown; moist. Outwash. 6.0 SP SAND, fine to coarse; some fine gravel; brown; moist. Outwash. 8.0 SC SAND, fine to coarse; trace clay; brown/black; moist. Outwash. 10.0 SP SAND, fine to coarse, gray, saturated. Outwash. 12.0 SP SAND, fine to coarse, brown/gray, saturated. Outwash. 14.0 SP SAND, fine to coarse; some fine gravel; brown; saturated. Outwash. 16.0 NO SAMPLE 20.0 SP SAND, fine to coarse, brown, saturated.	CONCRETE MH SILT; trace clay; black; damp. Fill. SILT and fine to coarse sand, brown/black, damp. Alluvium. SAND, fine to coarse; trace silt; brown; moist. Outwash. SAND, fine to coarse; some fine gravel; brown; moist. Outwash. SAND, fine to coarse; trace clay; brown/black; moist. Outwash. SAND, fine to coarse; trace clay; brown/black; moist. Outwash. SP SAND, fine to coarse, gray, saturated. Outwash. SP SAND, fine to coarse, brown/gray, saturated. Outwash. SP SAND, fine to coarse; some fine gravel; brown; saturated. Outwash. NO SAMPLE SAND, fine to coarse; some fine gravel; brown; saturated. Outwash.	CONCRETE MH SILT; trace clay; black; damp. Fill. ND SILT and fine to coarse sand, brown/black, damp. Alluvium. SILT and fine to coarse; trace silt; brown; moist. Outwash. SAND, fine to coarse; some fine gravel; brown; moist. Outwash. SAND, fine to coarse; trace clay; brown/ black; moist. Outwash. SAND, fine to coarse; trace clay; brown/ black; moist. Outwash. SP SAND, fine to coarse, gray, saturated. Outwash. SP SAND, fine to coarse, brown/gray, saturated. Outwash. SP SAND, fine to coarse; some fine gravel; brown; saturated. Outwash. NO SAMPLE SAND, fine to coarse; some fine gravel; brown; saturated. Outwash. SP SAND, fine to coarse; some fine gravel; brown; saturated. Outwash. SP SAND, fine to coarse; some fine gravel; brown; saturated. Outwash.

PROJECT	ROJECT: FORMER K-C KWIK STOP		KWIK STOP	DATE: 6-13-02	2		BORING: B-2	
	BROC	TEN, M	INNESOTA	GRADE EL	EVATI(ON:	COALE 17 22	
SAMPLE	DEPTH	ASTM	DESCRIPTION	<u> </u>	"N"	PID	SCALE: 1" = 3' NOTES	
NO.	FEET	D2487	DESCRIPTION		11	TID	NOTES	
			CONCRETE			PPM	ODOR/RECOVERY	
	22.0							
		SW	SAND, fine, brown, saturated	d. Outwash.		ND	No odor/ 2.0 ft.	
	24.0							
	26.0		END OF BORING AT FT. = FEET					
	20.0	:	ND = NONDETEC	TABLE				
			BG = BELOW GI	RADE				
	28.0		* PID malfunction suspected					
	30.0							
	30.0				:			
	32.0							
	34.0				!			
	36.0							
	38.0					:		
	40.0					E		
	40.0							
]							

PROJECT			DATE: 6-13-0	2		BORING: B-3	
	BROC	TEN, M	INNESOTA	GRADE EL	EVA	ΓΙΟΝ:	
	v						SCALE: 1" = 3'
SAMPLE NO.	DEPTH FEET	ASTM D2487	DESCRIPTION		N	PID	NOTES
			GRASS			PPM	ODOR/RECOVERY
		ML	SILT; some fine to coarse sar gravel; black; dry to damp.			ND	No odor/ 3.0 ft.
	2.0	ML	SILT; some fine to coarse sai			ND	No odor/ 3.0 ft.
	4.0		gravel; black; dry to damp.	Alluvium.			
	6.0	SC	SAND, fine to coarse; trace silt; trace clay; brown; damp to moist. Outwash.			ND	No odor/ 3.0 ft.
	8.0						
	10.0	SC	SAND, fine to coarse; trace of trace clay; black; saturated. product. Outwash.			881.0	Strong odor/ 3.0 ft.
	12.0	SP	SAND, fine to coarse, black/saturated. Possible free prod			842.0	Strong odor/ 3.0 ft.
	14.0						
	16.0	SP	SAND, fine to coarse, gray, Outwash.	saturated.		1,130.0	Strong odor/ 3.0 ft.
	18.0		NO SAMPLE				
	20.0						

PROJECT	Γ: FORM	MER K-C KWIK STOP DATE: 6-13-02			BORING: B-3		
	BROO	TEN, M	INNESOTA	GRADE EL	EVA	TION:	
							SCALE: 1" = 3'
SAMPLE NO.	DEPTH FEET	ASTM D2487	DESCRIPTION	1	N	PID	NOTES
			GRASS			PPM	ODOR/RECOVERY
	22.0	SP	SAND, fine to coarse; trace f brown; saturated. Outwash.	ine gravel;		1.1	No odor/ 2.0 ft.
	24.0		NO SAMPLE				
	26.0	SP	SAND, fine to coarse; some brown; saturated. Outwash.	fine gravel;		ND	No odor/ 2.0 ft.
	28.0		END OF BORING AT FT. = FEET				
	30.0		ND = NONDETEC BG = BELOW GI				
	32.0	:					
	34.0						
	36.0						
	38.0						
	40.0						

PROJECT	T: FORM	IER K-C	KWIK STOP	DATE: 6-13-02	2		BORING: B-4
	BROC	TEN, M	INNESOTA	GRADE EL	EVA	ΓΙΟΝ:	
			T				SCALE: 1" = 3'
SAMPLE NO.	DEPTH FEET	ASTM D2487	DESCRIPTION	N	N	PID	NOTES
			CONCRETE			PPM	ODOR/RECOVERY
	2.0		NO SAMPLE—PREVIOUSL EXCAVATED PUMP ISLAN ON 4-17-02				
	4.0	ML	SILT; some fine to coarse sar damp. Alluvium.	nd; brown;		4.1	No odor/ 2.0 ft.
	6.0	SM	SAND, fine to coarse; trace s damp to moist. Outwash.	silt; brown;		32.0	Odor/ 2.0 ft.
	8.0	SP	SAND, fine to coarse; trace for brown; moist. Outwash.	ine gravel;		808.2	Odor/ 2.0 ft.
	10.0	SW	SAND, fine, brown, saturate free product. Outwash.	d. Possible		1,363.0	Strong odor/ 1.0 ft.
	12.0		NO SAMPLE				
	12.0	SP	SAND, fine to coarse, brown Outwash.	ı, saturated.		212.2	Odor/ 0.3 ft.
	16.0	SP				21.9	Slight odor/ 2.0 ft. (from water above)
	18.0	į	NO SAMPLE				(**************************************
	20.0						

PROJECT	Γ: FORM	ER K-C	KWIK STOP	DATE: 6-13-02	2		BORING: B-4
	BROC	TEN, M	INNESOTA	GRADE EL	EVAT	TION:	
	r	r · · · · · · · · · · · · · · · · · · ·		γ			SCALE: 1" = 3'
SAMPLE NO.	DEPTH FEET	ASTM D2487	DESCRIPTION	7	N	PID	NOTES
			CONCRETE			PPM	ODOR/RECOVERY
	22.0	SP	SAND, fine to coarse; trace f brown; saturated. Outwash.	ine gravel;		2.4	No odor/ 2.0 ft.
	24.0	SP				ND	No odor/ 2.0 ft.
	26.0		END OF BORING AT :				
	28.0		ND = NONDETEC BG = BELOW GI	TABLE			
	30.0						
	32.0				:		
	34.0	-					
	36.0						
	38.0						
	40.0						

PROJECT	ROJECT: FORMER K-C KWIK STOP DATE: 8-6-02				BORING: B-5		
	BROO	TEN, M	INNESOTA	GRADE EL	EVA	ΓΙΟΝ:	
				99.64	ļ		SCALE: 1" = 3'
SAMPLE	DEPTH	ASTM	DESCRIPTION	N	N	PID	NOTES
NO.	FEET	D2487					
						PPM	ODOR/RECOVERY
			NO SAMPLE				
	2.0	SP	SAND, fine to coarse; trace fi brown; dry. Outwash.	ne gravel;		402.0*	No odor/ 0.5 ft.
	4.0	SM	SAND, fine to coarse; some figravel; trace silt; brown; damp			219.0*	No odor/ 0.5 ft.
	6.0	SM				250.0*	No odor/ 0.5 ft.
	8.0	SP	SAND, fine to coarse; trace fi gravel; brown; saturated. Out			92.0*	No odor/ 0.5 ft.
	10.0	SP	SAND, fine to coarse; trace fi brown; saturated. Outwash.	ne gravel;		ND	No odor/ 0.5 ft.
	12.0	SP	SAND, fine to coarse, brown, Outwash.	saturated.		ND	No odor/ 0.3 ft.
	14.0						
	16.0	SP	SAND, fine to coarse; trace fi brown; saturated. Outwash.	ine gravel;		94.0	Odor/ 1.5 ft.
		SP				526.0	Strong odor/ 1.5 ft.
	18.0						
			REFUSAL AT 19 FEET BG				
			END OF BORING AT	19 FT. BG		1	
	20.0		FT. = FEET				•
			ND = NONDETEC BG = BELOW G				
			* PID malfunction suspected				

PROJECT	PROJECT: FORMER K-C KWIK STOP		KWIK STOP	DATE: 8-6-02			BORING: B-6
	BROC	TEN, M	INNESOTA	GRADE EL	EVA	ΓΙΟΝ:	(MW-1)
				99.88			SCALE: 1" = 3'
SAMPLE NO.	DEPTH FEET	ASTM D2487	DESCRIPTIO	N	N	PID	NOTES
						PPM	ODOR/RECOVERY
			NO SAMPLE				
	2.0	SP	SAND, fine to coarse; some fi brown; moist. Fill.	ine gravel;		61.0*	No odor/ 1.5 ft.
	4.0	SP	SAND, fine to coarse; some fine to moist. Fill.	ine gravel;		60.0*	No odor/ 1.0 ft.
	6.0	SP		SAND, fine to coarse; trace fine to coarse gravel; brown; damp to moist. Fill.		37.0*	No odor/ 1.0 ft.
	8.0	SC	SAND, fine to coarse; some find clay; brown; saturated. Fill.	ine gravel; trace		32.0*	No odor/ 1.5 ft.
	10.0	SP	SAND, fine to coarse and fine saturated. Outwash.	e gravel, brown,		2.0	No odor/ 1.5 ft.
	12.0	SC	SAND, fine to coarse and fine clay; brown; saturated. Outw	_		1.6	No odor/ 1.5 ft.
	14.0					=	
	16.0	SP	SAND, fine to coarse; trace fi brown; saturated. Outwash.	ne gravel;		2.3	Odor/ 0.5 ft.
	18.0	SP	SAND, fine to coarse; trace fi gravel; brown; saturated. Out			ND	No odor/ 0.5 ft.
	20.0		REFUSAL AT 19 FEET BG END OF BORING AT FT. = FEET ND = NONDETEC				
			BG = BELOW GI * PID malfunction suspected				

PROJECT	PROJECT: FORMER K-C KWIK STOP DATE: 8-6-02		DATE: 8-6-02			BORING: B-7	
	BROC	TEN, M	INNESOTA	GRADE EL	EVA?	TION:	(MW-3)
				99.69			SCALE: 1" = 3'
SAMPLE	DEPTH	ASTM	DESCRIPTION		N	PID	NOTES
NO.	FEET	D2487					
						PPM	ODOR/RECOVERY
			NO SAMPLE				
	2.0	SM	SAND, fine to coarse; trace fit	ne to medium		ND	No odor/ 0.3 ft.
į			gravel; trace silt; black; damp.	Alluvium.			
	4.0	SP	SAND, fine to coarse; some fi	ne gravel;		3.0	No odor/ 1.0 ft.
			brown; dry. Outwash.				
							, , , , , , , , , , , , , , , , , , ,
	6.0	SP	SAND, fine to coarse; trace fin	ne to medium		3.4	No odor/ 1.5 ft.
	0,0		gravel; brown; dry. Outwash.				
						1	
	8.0	SP	SAND, fine to coarse; trace fin	na aravati		3.7	No odor/ 1.5 ft.
	8.0) SF	brown; saturated. Outwash.	ne graver,		3.7	140 0d01/ 1.5 ft.
			,				
	100	GD.	CANID Con to the control of the cont	1.		150	C1:-1-4 - 1/
	10.0	SP	SAND, fine to coarse; trace find brown/rust; saturated. Outwas	_		15.0	Slight odor/ 1.5 ft.
			orowing rust, suturated. Outwar	,,, <u>,</u>		Ì	1.5 1.
		-		4.			
	12.0	SP	SAND, fine to coarse; trace fingravel; brown/gray; saturated.			50.0	Odor/ 1.0 ft.
		!	graver, brown gray, saturated.	Outwasii.			
	14.0						
		SP	SAND, fine to coarse, brown,	saturated		10.7*	No odor/ 1.0 ft.
			Outwash.	saturated.		10.7	140 000// 1.0 10.
	16.0				ļ		
		SP				ND	No adam/106
		SP			-	ND	No odor/ 1.0 ft.
	18.0						
			REFUSAL AT 19 FEET BG END OF BORING AT	10 FT DC			
	20.0		FT. = FEET	19 F I , BU			
			ND = NONDETECT	TABLE			
			BG = BELOW GF	RADE			
	L	L	* PID malfunction suspected		1	L	


PROJECT	: FORM	ER K-C KWIK STOP DATE: 8-6-02		· · · · · · · · · · · · · · · · · · ·		BORING: B-8	
		TEN, M	INNESOTA	GRADE EL	EVA?	ΓΙΟΝ:	(MW-4)
				99.99)		SCALE: 1" = 3'
SAMPLE	DEPTH	ASTM	DESCRIPTION	DESCRIPTION		PID	NOTES
NO.	FEET	D2487			•		
					1	PPM	ODOR/RECOVERY
***	<u> </u>		NO SAMPLE				
		27.4	GAND 5			4.0	No odor/ 1.5 ft.
	2.0	SM	SAND, fine to coarse; some si medium gravel; brown; damp.			4.0	NO 0001/ 1.5 1t.
			medium graver, brown, damp.	Topson.			
	4.0	SP	SAND, fine to coarse; trace fi	ne gravel;		13.0*	No odor/ 1.0 ft.
1			brown; dry. Outwash.				
	6.0	SP				13.0*	No odor/ 1.0 ft.
					1		
					İ		
	0.0	CD.	CAND fine to convent trace fi	na araval:		11.0*	No odor/ 1.0 ft.
	8.0	SP	SAND, fine to coarse; trace fi brown; saturated. Outwash.	ne graver,		11.0	No odol/ 1.0 it.
			blown, saturated. Outwasn.				
	10.0		NO SAMPLE-ROCK	,	,		
			•				
	12.0					-	
1							
		SP	SAND, fine to coarse; trace fi			8.6	Odor/ 1.0 ft.
	14.0		gravel; gray; saturated. Outw	asn.			
	14.0						
		SP	SAND, fine to coarse, gray, s	aturated.		2.0	Slight odor/
			Outwash.				1.0 ft.
	16.0						
		SP	SAND, fine to coarse; brown	/grav:		ND	Slight odor/
			saturated. Outwash.	, 6, ,	1		1.0 ft.
	18.0						
			DEDUCAT AM (A PERSON DA				
			REFUSAL AT 19 FEET BG END OF BORING AT			-	
	20.0		FT. = FEET				
	20.0		ND = NONDETEC				
		1	BG = BELOW G				
			* PID malfunction suspected		<u> </u>		


PROJECT	: FORM	IER K-C	KWIK STOP	DATE: 8-7-02		BORING: B-9		
	BROC	TEN, M	INNESOTA	GRADE ELI	EVA:	(MW-2)		
				99.67			SCALE: 1" = 3'	
SAMPLE NO.	DEPTH FEET	ASTM D2487	DESCRIPTIO	Ν	Z	PID	NOTES	
						PPM	ODOR/RECOVERY	
			NO SAMPLE					
	2.0	SM	SAND, fine to coarse; some sorganics; brown; damp. Tops		-	4.3	No odor/ 1.0 ft.	
	4.0	SP	SAND, fine to coarse; trace fi trace organics; brown; damp t Alluvium.			11.5*	No odor/ 1.0 ft.	
	6.0	SP	SAND, fine to coarse; some figravel; brown; damp. Outwas			8.6	No odor/ 0.5 ft.	
	8.0	SP	SAND, fine to coarse; brown; Outwash.	saturated.		4.0	No odor/ 1.5 ft.	
	10.0	SP	SAND, fine to coarse; trace fit brown; saturated. Outwash.	ne gravel;		2.2	No odor/ 1.5 ft.	
	12.0	SP	SAND, fine to coarse, brown, Outwash.	saturated.	ı	2.7	No odor/ 1.5 ft.	
	14.0	•						
	16.0	SP	SAND, fine to coarse; trace fine brown; saturated; Outwash.	ne gravel;		2.8	No odor/ 1.0 ft.	
	18.0	SP	SAND, fine to coarse, brown, Outwash.	saturated.		1.4	No odor/ 1.5 ft.	
	20.0		END OF BORING AT FT. = FEET ND = NONDETECT BG = BELOW GR * PID malfunction suspected	ABLE				

PROJECT: FORMER K-C KWIK STOP				DATE: 2-4-03	BORING: B-10			
	BROC	TEN, M	INNESOTA	GRADE EL	EVA	(MW-6)		
				99.74	SCALE: 1" = 3'			
SAMPLE NO.	DEPTH FEET	ASTM D2487	DESCRIPTION	N	N	PID	NOTES	
						PPM	ODOR/RECOVERY	
			NO SAMPLE					
	2.0							
		SP	SAND, fine to coarse, brown,	dry. Outwash.		ND	No odor/ 2.0 ft.	
	4.0							
	6.0	SP	SAND, fine to coarse; trace fi gravel; brown; damp. Outwas			ND	No odor/ 2.0 ft.	
; ;	0.0	SP				0.5	No odor/ 2.0 ft.	
	8.0							
	10.0	SP	SAND, fine to coarse, brown, Outwash.	saturated.		2.8	No odor/ 2.0 ft.	
	12.0	SP	SAND, fine to medium, brow Outwash.	n, saturated.		0.7	No odor/ 2.0 ft.	
	14.0							
	:	SP	SAND, fine to coarse; trace fi brown; saturated. Outwash.	ne gravel;		0.4	No odor/ 2.0 ft.	
	16.0							
		SP				ND	No odor/ 2.0 ft.	
	18.0							
	20.0		END OF BORING AT FT. = FEET ND = NONDETEC BG = BELOW GI	TABLE				

MONITOR WELL CONSTRUCTION DIAGRAM-MINNESOTA

FORMER K-C KWIK STOP BROOTEN, MINNESOTA






MONITOR WELL CONSTRUCTION DIAGRAM - MINNESOTA

FORMER K-C KWIK STOP BROOTEN, MINNESOTA


ABOVE-GRADE MONITOR WELL MW-2



MONITOR WELL CONSTRUCTION DIAGRAM - MINNESOTA

FORMER K-C KWIK STOP BROOTEN, MINNESOTA


ABOVE-GRADE MONITOR WELL MW-3



MONITOR WELL CONSTRUCTION DIAGRAM - MINNESOTA


FORMER K-C KWIK STOP BROOTEN, MINNESOTA


ABOVE-GRADE MONITOR WELL MW-4



MONITOR WELL CONSTRUCTION DIAGRAM-MINNESOTA


FORMER K-C KWIK STOP BROOTEN, MINNESOTA





MONITOR WELL CONSTRUCTION DIAGRAM-MINNESOTA

FORMER K-C KWIK STOP BROOTEN, MINNESOTA




APPENDIX E

COPIES OF WATER SUPPLY WELL LOGS

	MINNESOTA	DEPARTMENT OF HEALTH				
Unique No. 00458780		D BORING RECORD	Update Date 1993/07/12			
County Name Stearns	1	a Statutes Chapter 1031	Entry Date 1992/11/18			
Township Name Township Range		Well Depth Depth Complete 45 ft. 45 ft.	ed Date Well Completed 1990/06/04			
Well Name BOHMER, JOHN		Drilling Method Non-specified Rote	ary			
Contact's Name BOHMER,			Hydrofractured? Yes No			
Comacis Hame	OT II V	Other From				
BROOTEN MN		Use Other (specify in remarks)				
		Casing Drive Shoe? Yes	N Hole Diameter			
		Jive choo.	0 in. to 45 ft			
GEOLOGICAL MATERIAL COLO	R HARDNESS FROM TO	Casing Diameter Welght(lbs				
	SOFT 0 1	4 in. to 40 ft				
	SOFT 1 45	_				
3	0011 1 40					
		Screen Y Open H	lole From ft. to ft.			
		Make CERTA-LINK	Туре Р			
		Diameter Slot Length Set	Fitting			
	٥	19-11-11-11-11-11-11-11-11-11-11-11-11-1	to 45 ft			
		-				
		Static Water Level 12 ft. from Land st				
		PUMPING LEVEL (below land surface) 15 ft. after hrs. pump				
		Well Head Completion				
		Pitless adapter mfr Casing Protection	Model			
		At-grade(Environmental Wells and B	☐ 12 in. above grade orings ONLY)			
		Grouting Information Well grout	ed? 🗹 Yes 🗌 No			
		Material From To (ft.) Am O 0 8 0	ount(yds/bags)			
		O 0 8 0 G 8 40 0 O 40 45 0				
•		O 40 45 0				
		Nearest Known Source of Contaminat	ion type			
			Yes No			
		Pump Not installed	Date Installed			
		Mfr name Model	HP 0 Volts			
REMARKS, ELEVATION, SOURCE O	E DATA etc	Drop Pipe Length ft.	HP 0 Volts Capacity g.p.m			
1ST & CENTRAL AVE., BROOTEN, N		Туре	or many one of			
LOCATED 600' SW OF HWY. 55 & CO		Any not in use and not sealed well(s) on	property? Yes No			
220 211 21 1117 11 20 4 01	- · · · - · · · ·	Was a variance granted from the MDH fo				
USGS Quad Padua	Elevation 1310					
Aquifer: QWTA	Alt ld:	Well CONTRACTOR CERTIFICATION License Business Name	Lic. Or Reg. No. <u>73413</u>			

		-	MININ	IESOTA D	EPARTMENT OF HEALTH
Unique No. 00102020					BORING RECORD Update Date 1993/07/16
County Name Stearns					Statutes Chapter 1031 Entry Date 1988/04/17
Township Name Township	Range D	ir Section	n Subs	ection	Well Depth Depth Completed Date Well Completed
123	35	W 6	A(CBBBB	180 ft. 166 ft. 1975/08/07
Well Name BROOTEN 2					Drilling Method Non-specified Rotary
Contact's Name BRO	DOTEN 2				Drilling Fluid Well Hydrofractured? ☐ Yes ☐ No
BROOTEN MN 56316					From ft. to . ft.
					Use Community Supply (municipal)
					Casing Drive Shoe?
GEOLOGICAL MATERIAL	COLOR I	HARDNESS	FROM	1 то	Casing Diameter Weight(lbs/ft)
DIRT	BLACK		0	1	10 in. to 141 ft
SAND + ROCKS + CLAY LEN	ı		1	39	
CLAY + SAND SEAMS	BLUE		39	43	
SANDY CLAY	BLUE		43	60	
SAND			60	64	Screen Y Open Hole From ft. to ft.
ROCK			64	66	Make JOHNSON 304 Type L
SANDY CLAY	BLUE		66	70	Diameter Slot Length Set Fitting
ROCK			70	71	10 40 25 141 ft. to 166 ft
SANDY CLAY	BLUE		71	80	Static Water Level 21 ft. from Land surface Date 1975/08/07
ROCKS			80	82	PUMPING LEVEL (below land surface)
SANDY CLAY + SAND LENS	BLUE		82	110	54.25 ft. after hrs. pumping 500 g.p.m.
ROCKS			110	112	Well Head Completion
SANDY CLAY	BLUE		112	130	Pitless adapter mfr Model Casing Protection 12 in, above grade
SAND WITH BLUE CLAY	BLUE		130	140	Casing Protection
SAND			140	141	Grouting Information Well grouted? ✓ Yes No
ROCK			141	142	Material From To (ft.) Amount(yds/bags) G 0 0 0
SAND			142	160	
SAND			160	180	
					Nearest Known Source of Contamination
					ft. direction type
					Well disinfected upon completion? Yes No
					Pump
					Mfr name VERTI-LINE
REMARKS, ELEVATION, SOU	IBCE OF S	ATA etc		······································	Model 8RL HP 20 Volts 230 Drop Pipe Length 102 ft. Capacity 300 g.p.m
NURE NO.602279.	RCE OF D	AIA, etc.			Type T
					Any not in use and not sealed well(s) on property? Yes No
USGS Quad Belgrade	-	levation 130	าด		Was a variance granted from the MDH for this Well? Yes No
Aquifer: QBAA			3092		Well CONTRACTOR CERTIFICATION Lic. Or Reg. No. 12013

Unique No	002151	137					DEPARTMENT				Update [Date 2	2002/02/1	8
County Na	me Stearns	s					BORING Statutes Chap		RD	-	Entry Da		988/04/1	
Township	Name Tow	-	Range D	Pir Section W 31	Subse		Well Depth		Depth C	Completed ft.	d Date	Well Co	ompleted	
Well Name							Drilling Me			11.		/19/24		
Contact's			OTEN 1							ا بيرا		"		
			OILIV.				Drilling Flu	Ia		From	Hydrofract	ured? [ft. to	☐ Yes [∏ No ft.
BROOTEN	MN 56316	<u> </u>					Use Con		· · · · · · · · · · · ·			11. 10		п.
							Casing	nmunity St				.:-!> D		
							Casing	Drive	Shoe?	☐ Yes	□N	Hole D	iameter	
GEOLOGIC	CAL MATER	IAL (COLOR	HARDNESS	FROM	1 то	Casing Dia	neter	W	eight(lbs/	ft)			
DRIFT					0	220	8 in.				,			
									_					
							Screen		 1		- 5			
							Make			Open Ho			t. to	ft.
							IVIANU			1	ype			
							Static Water			Land surf	асе	D	ate	/19/24
							PUMPING LI							
								after		s. pumpin	9 350	g.p.m.		
							Well Head C Pitless adap		1					
							Casing Prot					odel 12 in ah	ove grade	^
							At-grade		ental Wells	s and Bori	ات ings ONL۱	12 III. au ()	ove grau	Э
							Grouting Info			ell grouted			☐ No	
							Nearest Kno	wn Source	e of Contr					
							1,00,000,1000		direction	aliiinauoi		type		
							Well disinfe	cted upon	completio	on? 🔲] No		
							Pump [Not Inst	talled		Date Inst	alled v		
							Mfr name	_			Date	unou 1		
							Model			HP	0	Vo	oits	
							Drop Pipe L		ft.		Cap	acity	g.p.ı	n
							Type S							
							Any not in use					Yes	☐ No	
USGS Quad				evation 1312			Was a variand						☐ No	·
Aquifer:	QBAA		All	t ld: 80-30	92		Well CONTR			TION L	ic. Or Re	g. No. <u> </u>	<u>JSGS</u>	
	R	epo	rt Co	vac			Name of Dri		10					





GRAIN SIZE ANALYSIS AND HYDRAULIC CONDUCTIVITY MEASUREMENTS

B-1

SIEVE#	mm	% Retained	% Passed
		59%	
6	3.3		40%
	•	21%	
16	1.2		19%
		12%	
25	0.675		7%
		7" .	11.00
40	0.375	3 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0%
		0%	

Hydraulic conductivity calculations

 $K=A(d10)^2$

cm/sec

A = 1 d10 = 0.700

K= 0.490 cm/sec equals 1388.98 feet/day

b= 19 feet

T=K*b ft^2/sec

 $T=Kcm/sec * in/2.54 cm * ft/12 in * b ft = ft^2/sec$

T= 0.3054 ft^2/sec

 $T = ft^2/\sec * 60\sec/\min * 60 \min/hr * 24hr/day = ft^2/day$

T= 26387 ft^2/day >50 AQUIFER BLUE <50 NO AQUIFER RED

0.1 KC KWIK STOP, BROOTEN, MN B-1 (16-18 FT) GRAIN SIZE (mm) 2 100% %06 %0 %08 %0/ 20% 10% %09 20% 40% 30% % PASSING

B-2

SIEVE#	mm	% Retained	% Passed
		14%	
6	3.3	1999	87%
	1. 1. M. 1.	18%	
16	1.2		69%
		28%	
25	0.675		41%
	-	29%	
40	0.375		12%
	1:,	12%	
		101%	

Hydraulic conductivity calculations

 $K=A(d10)^2$

cm/sec

A= 1 d10 = 0.290

K= 0.084 cm/sec equals 238.11 feet/day

b= 19 feet

T=K*b ft^2/sec

 $T=Kcm/sec * in/2.54 cm * ft/12 in * b ft = ft^2/sec$

T= 0.0524 ft^2/sec

 $T = ft^2/\sec * 60\sec/\min * 60 \min/hr * 24hr/day = ft^2/day$

T= 4527 ft^2/day >50 AQUIFER BLUE <50 NO AQUIFER RED

0.01 KC KWIK STOP, BROOTEN, MN B-2 (15-17 FT) GRAIN SIZE (mm) %0I 100% 10 %09 30% %0 20% 40% 20% %06 %08 %0/

% byssing

0.001

B-3

SIEVE#	mm	% Retained	% Passed
		25%	14 134 13
6	3.3		74%
		19%	E Bits Occup
16	1.2		55%
		20%	的各種類的
25	0.675		35%
	· 14.	25%	
40	0.375		10%
		10%	Children

Hydraulic conductivity calculations

 $K=A(d10)^2$

cm/sec

A=

d10 = 0.320

K=

0.102 cm/sec

equals 289.13 feet/day

b=

19 feet

T=K*b

ft^2/sec

 $T=Kcm/sec * in/2.54 cm * ft/12 in * b ft = ft^2/sec$

T=

0.0636 ft^2/sec

 $T = ft^2/\sec * 60\sec/\min * 60 \min/hr * 24hr/day = ft^2/day$

T=

5495 ft^2/day

>50

AQUIFER

BLUE

<50

NO AQUIFER

RED

0.001 0.01 KC KWIK STOP, BROOTEN, MN GRAIN SIZE (mm) B-3 (21-23 FT) 0.1 10 %0 20% 40% %06 %08 %09 10% 100% %0/ 30% 20% % byzzinc