3-Copies

GME CONSULTANTS, INC.

CONSULTING ENGINEERS

314 Garfield Avenue (Duluth, MN 55802

(218) 722-4323 / Fax (218) 722-9722



February 25, 1993

CROSSY # SOI-967- PECEIVED

APR 19 1993

Mr. Robert Dittmer Dittmer Oil Company, Inc 600 East Lincoln Avenue Fairfax, Minnesota 55332

MPCA, HAZARDOUS WASTE DIVISION GME Project No. C-2373A

RE: Remedial Investigation status and contract amendment for supplemental Remedial Investigation services at the Dittmer Oil site in Fairfax, Minnesota

Dear Mr. Dittmer:

We are writing regarding the status of the Remedial Investigation (RI) we are conducting for the Dittmer Oil Company site located in Fairfax, Minnesota.

The primary purpose for conducting an RI is to prepare a report that explains the potential of a petroleum release to cause harm to either the environment or to human health. The Minnesota Pollution Control Agency (MPCA) has established minimum criteria (including plume definition) that must be present in all RI reports that are submitted to them. After reviewing the data that have been collected to date for this RI, it is our opinion that additional field work will be necessary to define the groundwater plume. Our rationale for expanding the scope of services outlined in our initial proposal dated August 13, 1991, is explained below.

PROJECT SUMMARY

To date, we have completed seven environmental soil borings, installed three groundwater monitoring wells, collected soil and groundwater samples for chemical analyses, and conducted slug tests in the wells.

The environmental soil borings were used to assess the extent of the petroleum impacts to the soil. The results of the laboratory analyses conducted on soil samples collected from the borings are listed on Figure 1 and in Table 1.

Groundwater samples were collected on December 6, 1991, and January 21, 1992. The results of the chemical analyses of these samples indicate that there are significant groundwater impacts around monitoring well MW1. The direction of groundwater flow is generally to the south. Figures 2 and 3 are presented to show the groundwater flow direction. Please note that groundwater generally flows approximately from the former tank basin (the site of the petroleum release) towards monitoring well MW1.

MARK D. MILLSOP SANDRA J. FORREST It is apparent that monitoring well MW1 is in the plume of petroleum impacted groundwater. An estimate of the primary zone of petroleum impacted groundwater is presented as Figure 4. The results of the groundwater chemistry analyses are presented on Figure 4 and in Table 2.

In conclusion, the impacts to the soil have been sufficiently defined, but because only one well (MW1) exists downgradient of the release site and because this well is located within the primary zone of impacted groundwater, the lateral extent of the petroleum plume has not yet been defined. For this reason, it is our opinion that the following additional work is necessary.

SUPPLEMENTAL REMEDIAL INVESTIGATION SERVICES

Based on the above information, it is our opinion that five additional environmental soil borings and three additional groundwater monitoring wells are needed to better define the extent of the petroleum impacts. Our intention is to place the borings and wells south, southeast and southwest (downgradient) of monitoring well MW1. The specific locations for well placement would be determined while on-site. All six of the wells on-site would be sampled two additional times, prior to preparation of our final report.

COST ESTIMATE

Based on the scope of services described above and outlined in the table below, we estimate that the charges for this supplemental work would be approximately \$14,200.

<u>Service</u>		Estimated Cost
Work Plan Preparation and Project Management	\$	750.00
Environmental Soil Borings and	4	730.00
Monitoring Well Installations (assume mobilization, utility clearance, steam cleaning, drilling and sampling, grouting, equipment costs, permits, PVC well materials, well development, on-site geologist and mileage)	\$	5100.00
Monitoring Well Sampling (assume sampling 6 wells twice, and equipment costs)	\$	1475.00

Laboratory Costs	
(assume 5 soil analyses of BTEX, MTBE,	
DRO, GRO, and Lead, and 12 water analyses	of
BTEX, DRO, GRO, MTBE, and dissolved lead)	

4375.00

Additional Report Preparation \$
(assume preparation of boring logs, and writing, review, drafting, and typing report)

2500.00

TOTAL ESTIMATED COST FOR ADDITIONAL WORK

14,200.00

Our estimate is based on using Modified Level D Personal Protective Equipment (PPE) for field personnel. Our Health and Safety Plan provides for upgrading to level C PPE, if organic vapor readings in the breathing zone rise to greater than 5 ppm. There would be additional charges for upgrading to Level C PPE. Our estimate includes no allowance for client directed drill rig standby or delay time. Such time would be billed at \$125 per hour. We plan to leave the soil cuttings on the site. Additional charges for providing Mn/DOT approved drums to contain these materials would be \$65 per drum plus the drill crew hourly rate to load the drums.

In the event that additional or deeper borings, additional analytical testing, or additional on-site work is necessary, or if we must upgrade to Level C PPE, we would contact you to discuss the modifications in the scope of services and receive authorization to proceed.

Our work will be billed on a time and materials basis. The final charges for our above outlined scope of work and any further work due to changes in the original scope of work will be extended at the appropriate unit prices. The same unit prices and terms and conditions outlined in our original August 13, 1991, contract that you authorized will apply to this phase of the work, with the exception of our sub-contracted analytical testing costs.


Please be aware that Petrofund reimbursement typically is sent approximately 9 to 12 months after <u>submittal</u> of your application. We require payment prior to Petrofund disbursement, within 30 days after submittal of our invoice.


CLOSURE


We are submitting this contract amendment in two copies for acceptance. When it is accepted, we ask that one copy be signed by an authorized representative of the party responsible for payment of these services and that this copy be returned to us as our authorization to proceed.

We will be contacting you by telephone in the next week to discuss this project. However, if you have any immediate questions please feel free to call us at (218)546-6371. We look forward to continuing to work with you on this project.

Sincerely,		1
GME CONSULTANT	S. INC.	0[/
Douglas A. Fos	A. Juli Ssell	
Environmental		
Male D. Mi	llsop _{lb}	_
Mark D. Millso Senior Hydroge Corporate Envi	ologist	Division Manager
Enclosures:	Figure 1:	Soil some of recrotedm impacted
	Figure 3: Figure 4:	Groundwater Table Contour Man (1-21 00)
	Table 1: Table 2:	Soil Chemistry Results Groundwater Chemistry Results
ACCEPTED:		
DATE		
FIRM		
AUTHORIZED SIGNATURE		
TITLE		
DAF: MDM: fhs		










TABLE 1
SOIL CHEMISTRY RESULTS
DITTMER OIL COMPANY
FAIRFAX, MINNESOTA

Boring and Sample #	Depth(ft)	MDL	Parameter Analyzed	Concentration(ppm)
B1 (S-5)	8-10	5 0.059 0.063 0.041 0.18 1.6		
B1 (S-6)	10-12	0.059 0.063 0.041 0.18 1.6	Benzene Toluene Ethylbenzene Total Xylenes TPHCs as Gasoline TPHCs as Fuel Oi	
B2 (S-5)	8-10	5 0.059 0.063 0.041 0.18 1.6	Toluene	
B3 (S-5)	8-10	5 0.059 0.041 0.18 1.6		
B3 (S-6)	10-12	5 0.041 1.6 1.4	Lead Ethylbenzene TPHCs as Gasolin TPHCs as Fuel Oi	
B3 (S-7)	12-14	5	Lead	.6

TABLE 2 GROUNDWATER CHEMISTRY RESULTS DITTMER OIL COMPANY FAIRFAX, MINNESOTA

Well #	Sampling Date	MDL (ppb)	Parameter Analyzed	Concentration (ppb)
MW1	12-6-91	13 43 0.47 0.92 2.2	TPHCs as Gasoline TPHCs as Fuel Oil Benzene Toluene Total xylenes	29,000 20,000 7,300 3,700 3,000
MW2	12-6-91	0.68	MTBE	25
мwз	12-6-91	0.68 2.2	MTBE Total xylenes	8.2 2.8
MW1	1-21-92	13 45 0.47 0.92 2.2 0.42		27,000 8,500 6,700 1,700 2,500
MW2	1-21-92	0.68	MTBE	26
MW3	1-21-92	0.68	MTBE	8.6

MDL=method detection limit Notes:

TPHCs=total petroleum hydrocarbons

All results given in parts per billion (ppb).
Results for analyzed parameters below the MDLs are not

included in this table.

TABLE 1 SOIL CHEMISTRY RESULTS DITTMER OIL COMPANY FAIRFAX, MINNESOTA

Boring and Sample #	Depth(ft)	MDL	Parameter Analyzed	Concentration (ppm)
B4	8-10	5 .	Lead	7
(S-5)		0.059	Benzene	2.2
•		0.063	Toluene	2.4
		0.041	Ethylbenzene	1.5
		0.18		4.6
		1.6	TPHCs as Gasoline	
		1.4	TPHCs as Fuel Oi	L 48
B4	10-12	5	Lead	13
(S-6)		0.059		0.84
,		0.041	Ethylbenzene	0.81
		0.18		2.5
		1.6	TPHCs as Gasoline	e 72
		1.4	TPHCs as Fuel Oi	100
MW1 (S-6)	10-12	5	Lead	7
MW2	8-10	5	Lead	8
(S-5)		1.4	TPHCs as Fuel Oi	l 2.1
мwз	12-14	5	Lead	9
(S-7)	•	0.041	Ethylbenzene	0.32
•		0.18	Total Xylenes	2.8
	•	1.6	TPHCs as Gasoline	e 40
		1.4	TPHCs as Fuel Oi	1 38

MDL=method detection limit Notes:

TPHCs=total petroleum hydrocarbons
All results given in parts per million (ppm).
Results for analyzed parameters below the MDLs are not included in this table.